

Jags example

Patrick Brown

Wednesday 14 September 2016

```
> library('glmmBUGS')
> haveR2jags = require('R2jags', quietly=TRUE)
> print(haveR2jags)

[1] TRUE

> haveRjags = requireNamespace('rjags', quietly=TRUE)
> print(haveRjags)

[1] TRUE

> haveRjags = try(
+   loadNamespace('rjags'),
+   silent=TRUE)
> if(class(haveRjags) == 'try-error') {
+   haveRjags = FALSE
+ }
```

If Jags isn't available, the `rjags` namespace will give an error when loaded.

1 Muscle data

```
> data('Muscle', package='nlme')

> muscleRagged = glmmBUGS(conc ~ length, data=Muscle,
+   effects="Strip", family="gaussian",
+   modelFile='model.bug', reparam='Strip')
> startingValues = muscleRagged$startingValues

> source("getInits.R")
> if(haveR2jags) {
+   muscleResult = jags(
+     muscleRagged$ragged, getInits,
+     parameters.to.save = names(getInits()),
+     model.file="model.bug", n.chain=3, n.iter=1000,
```

```

+      n.burnin=100, n.thin=10, refresh=200,
+      working.directory=getwd())
+ } else {
+     muscleResult = NULL
+ }

```

Compiling model graph

Resolving undeclared variables
 Allocating nodes

Graph information:

Observed stochastic nodes: 60
 Unobserved stochastic nodes: 25
 Total graph size: 285

Initializing model

```

> if(!is.null(muscleResult)) {
+     muscleParams = restoreParams(
+     muscleResult$BUGSoutput,
+     muscleRagged$ragged)
+ summaryChain(muscleParams)$scalars[,c('mean','2.5pct','97.5pct')]
+ }


```

	mean	2.5pct	97.5pct
SDStrip	1.0348909	0.3046083	1.8081782
intercept	-1.1148962	-2.3487627	0.3694371
betas	0.1987191	0.1427875	0.2455235

```

> if(!is.null(muscleResult)) {
+     checkChain(muscleParams)
+ } else {
+     plot(1, main='Not run, some packages missing')
+ }

```



2 Bacteria

```

> data('bacteria', package='MASS')
> bacterianew <- bacteria
> bacterianew$yInt = as.integer(bacterianew$y == "y")
> levels(bacterianew$trt) <- c("placebo", "drug", "drugplus")

> bacrag <- glmmBUGS(formula = yInt ~ trt + week,
+   data = bacterianew,
+   effects = "ID", modelFile = "bacteria.txt",
+   family = "bernoulli", brugs=TRUE)
> source("getInits.R")
> startingValues = bacrag$startingValues

> if(haveR2jags) {
+   bacResult = R2jags::jags(bacrag$ragged,
+     inits=getInits,
+     model.file = "bacteria.txt", n.chain = 3,

```

```

+      n.iter = 600, n.burnin = 10, refresh=200,
+      parameters = names(getInits()),
+      n.thin = 4)
+ } else {
+     bacResult = NULL
+ }

```

Compiling model graph

Resolving undeclared variables

Allocating nodes

Graph information:

Observed stochastic nodes: 220

Unobserved stochastic nodes: 55

Total graph size: 1156

Initializing model

```

> if(!is.null(bacResult)) {
+   bacParams = restoreParams(bacResult$BUGSoutput,
+     bacrag$ragged)
+ }

> if(!is.null(bacResult)) {
+   bacsummary = summaryChain(bacParams)
+   bacsummary$betas[,c('mean', 'sd')]
+ }

               mean           sd
trtdrug        -1.4037641 0.76605160
trtdrugplus    -0.8977213 0.81224717
betaobservations -0.1564980 0.05750264

> if(!is.null(bacResult)) {
+   checkChain(bacParams, c("intercept", "SDID"), oneFigure=TRUE)
+ } else {
+   plot(1, main='Not run, some packages missing')
+ }

```

