

Package ‘sasLM’

September 5, 2022

Version 0.9.1

Title 'SAS' Linear Model

Description This is a core implementation of 'SAS' procedures for linear models - GLM, REG, ANOVA, FREQ, and UNIVARIATE. Some R packages provide type II and type III SS. However, the results of nested and complex designs are often different from those of 'SAS.' Different results does not necessarily mean incorrectness. However, many wants the same results to SAS. This package aims to achieve that.
Reference: Littell RC, Stroup WW, Freund RJ (2002, ISBN:0-471-22174-0).

Depends R (>= 3.0.0), mvtnorm

Imports methods

Author Kyun-Seop Bae [aut]

Maintainer Kyun-Seop Bae <k@acr.kr>

Copyright 2020-, Kyun-Seop Bae

License GPL-3

Repository CRAN

URL <https://cran.r-project.org/package=sasLM>

R topics documented:

sasLM-package	3
af	4
aov1	5
aov2	6
aov3	7
BEdata	8
bk	8
BY	9
CIest	10
Coll	11
CONTR	12
Cor.test	13
cSS	14
CV	15
Diffogram	15
e1	16
e2	17

e3	17
EMS	18
est	19
ESTM	20
estmb	21
G2SWEEP	21
geoCV	23
geoMean	23
GLM	24
is.cor	25
Kurtosis	26
KurtosisSE	26
LCL	27
lfit	28
lr	29
lr0	30
LSM	31
Max	32
Mean	33
Median	33
Min	34
ModelMatrix	34
N	35
OR	36
ORcmh	37
ORinv	38
ORmn	39
ORmn1	40
pB	41
Pcor.test	42
pD	43
PDIFF	43
pResD	45
QuartileRange	45
Range	46
RD	46
RDinv	47
RDmn	49
RDmn1	50
REG	51
regD	52
RR	53
RRinv	54
RRmn	55
RRmn1	56
satt	57
ScoreCI	58
SD	59
SEM	59
Skewness	60
SkewnessSE	60
SLICE	61

SS	62
T3MS	62
T3test	63
trimmedMean	64
tsum	64
tsum0	65
tsum1	66
tsum2	67
tsum3	68
UCL	69
UNIV	70

Index	72
--------------	-----------

sasLM-package	<i>'SAS' Linear Model</i>
---------------	---------------------------

Description

This is a core implementation of 'SAS' procedures for linear models - GLM, REG, and ANOVA. Some packages provide type II and type III SS. However, the results of nested and complex designs are often different from those of 'SAS'. Different results does not necessarily mean incorrectness. However, many wants the same results to 'SAS'. This package aims to achieve that. Reference: Littell RC, Stroup WW, Freund RJ (2002, ISBN:0-471-22174-0).

Details

This will serve those who want SAS PROC GLM, REG, and ANOVA in R.

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
## SAS PROC GLM Script for Typical Bioequivalence Data
# PROC GLM DATA=BEdata;
# CLASS SEQ SUBJ PRD TRT;
# MODEL LNCMAX = SEQ SUBJ(SEQ) PRD TRT;
# RANDOM SUBJ(SEQ)/TEST;
# LSMEANS TRT / DIFF=CONTROL("R") CL ALPHA=0.1;
# ODS OUTPUT LSMEandDiffCL=LSMD;

# DATA LSMD; SET LSMD;
# PE = EXP(DIFFERENCE);
# LL = EXP(LowerCL);
# UL = EXP(UpperCL);
# PROC PRINT DATA=LSMD; RUN;
##

## SAS PROC GLM equivalent
BEdata = af(BEdata, c("SEQ", "SUBJ", "PRD", "TRT")) # Columns as factor
formula1 = log(CMAX) ~ SEQ/SUBJ + PRD + TRT # Model
GLM(formula1, BEdata) # ANOVA tables of Type I, II, III SS
```

```

EMS(formula1, BEdata) # EMS table
T3test(formula1, BEdata, Error="SEQ:SUBJ") # Hypothesis test
ci0 = CIest(formula1, BEdata, "TRT", c(-1, 1), 0.90) # 90% CI
exp(ci0[, c("Estimate", "Lower CL", "Upper CL")]) # 90% CI of GMR

## 'nlme' or SAS PROC MIXED is preferred for an unbalanced case
## SAS PROC MIXED equivalent
# require(nlme)
# Result = lme(log(CMAX) ~ SEQ + PRD + TRT, random=~1|SUBJ, data=BEdata)
# summary(Result)
# VarCorr(Result)
# ci = intervals(Result, 0.90) ; ci
# exp(ci$fixed["TRTT",])
##

```

af

*Convert some columns of a data.frame to factors***Description**

Conveniently convert some columns of data.frame into factors.

Usage

```
af(DataFrame, Cols)
```

Arguments

DataFrame	a data.frame
Cols	column names or indices to be converted

Details

It performs conversion of some columns in a data.frame into factors conveniently.

Value

Returns a data.frame with converted columns.

Author(s)

Kyun-Seop Bae k@acr.kr

aov1	<i>ANOVA with Type I SS</i>
------	-----------------------------

Description

ANOVA with Type I SS.

Usage

```
aov1(Formula, Data, eps=1e-8)
```

Arguments

Formula	a conventional formula for a linear model.
Data	a <code>data.frame</code> to be analyzed
eps	Less than this value is considered as zero.

Details

It performs the core function of SAS PROC ANOVA.

Value

The result table is comparable to that of SAS PROC ANOVA.

Df	degree of freedom
Sum Sq	sum of square for the set of contrasts
Mean Sq	mean square
F value	F value for the F distribution
Pr(>F)	probability of larger than F value

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
aov1(uptake ~ Plant + Type + Treatment + conc, C02)
```

aov2

ANOVA with Type II SS

Description

ANOVA with Type II SS.

Usage

```
aov2(Formula, Data, eps=1e-8)
```

Arguments

Formula	a conventional formula for a linear model.
Data	a <code>data.frame</code> to be analyzed
eps	Less than this value is considered as zero.

Details

It performs the core function of SAS PROC ANOVA.

Value

The result table is comparable to that of SAS PROC ANOVA.

Df	degree of freedom
Sum Sq	sum of square for the set of contrasts
Mean Sq	mean square
F value	F value for the F distribution
Pr(>F)	probability of larger than F value

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
aov2(uptake ~ Plant + Type + Treatment + conc, C02)
aov2(uptake ~ Type, C02)
aov2(uptake ~ Type - 1, C02)
```

aov3	<i>ANOVA with Type III SS</i>
------	-------------------------------

Description

ANOVA with Type III SS.

Usage

```
aov3(Formula, Data, eps=1e-8)
```

Arguments

Formula	a conventional formula for a linear model.
Data	a <code>data.frame</code> to be analyzed
eps	Less than this value is considered as zero.

Details

It performs the core function of SAS PROC ANOVA.

Value

The result table is comparable to that of SAS PROC ANOVA.

Df	degree of freedom
Sum Sq	sum of square for the set of contrasts
Mean Sq	mean square
F value	F value for the F distribution
Pr(>F)	probability of larger than F value

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
aov3(uptake ~ Plant + Type + Treatment + conc, C02)
```

BEdata

*An Example Data of Bioequivalence Study***Description**

Contains Cmax data from a real bioequivalence study.

Usage

```
BEdata
```

Format

A data frame with 91 observations on the following 6 variables.

ADM Admission or Hospitalization Group Code: 1, 2, or 3

SEQ Group or Sequence character code: 'RT' or 'TR'

PRD Period numeric value: 1 or 2

TRT Treatment or Drug code: 'R' or 'T'

SUBJ Subject ID

CMAX Cmax values

Details

This contains a real data of 2x2 bioequivalence study, which have three different hospitalization groups. See Bae KS, Kang SH. Bioequivalence data analysis for the case of separate hospitalization. Transl Clin Pharmacol. 2017;25(2):93-100. doi.org/10.12793/tcp.2017.25.2.93

bk

*Beautify the output of knitr::kable***Description**

Trailing zeros after integer is somewhat annoying. This removes those in the vector of strings.

Usage

```
bk(ktab, rpltag=c("n", "N"), dig=10)
```

Arguments

ktab an output of knitr::kable

rpltag tag string of replacement rows. This is usually "n" which means the sample count.

dig maximum digits of decimals in the kable output

Details

This is convenient if used with tsum0, tsum1, tsum2, tsum3, This requires knitr::kable.

Value

A new processed vector of strings. The class is still `knitr_kable`.

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[tsum0](#), [tsum1](#), [tsum2](#), [tsum3](#)

Examples

```
## OUTPUT example
# t0 = tsum0(CO2, "uptake", c("mean", "median", "sd", "length", "min", "max"))
# bk(kable(t0)) # requires knitr package
#
# |          |          x|
# |:-----|-----:|
# |mean  | 27.21310|
# |median| 28.30000|
# |sd    | 10.81441|
# |n     | 84      |
# |min   | 7.70000|
# |max   | 45.50000|

# t1 = tsum(uptake ~ Treatment, CO2,
#           e=c("mean", "median", "sd", "min", "max", "length"),
#           ou=c("chilled", "nonchilled"),
#           repl=list(c("median", "length"), c("med", "N")))
#
# bk(kable(t1, digits=3)) # requires knitr package
#
# |      | chilled| nonchilled| Combined|
# |:----|-----:|-----:|-----:|
# |mean | 23.783| 30.643| 27.213|
# |med  | 19.700| 31.300| 28.300|
# |sd   | 10.884| 9.705| 10.814|
# |min  | 7.700| 10.600| 7.700|
# |max  | 42.400| 45.500| 45.500|
# |N    | 42    | 42    | 84    |
```

 BY

Analysis BY variable

Description

GLM, REG, aov1 etc. functions can be run by levels of a variable.

Usage

```
BY(FUN, Formula, Data, By, ...)
```

Arguments

<code>FUN</code>	Function name to be called such as GLM, REG
<code>Formula</code>	a conventional formula for a linear model.
<code>Data</code>	a <code>data.frame</code> to be analyzed
<code>By</code>	a variable name in the <code>Data</code>
<code>...</code>	arguments to be passed to <code>FUN</code> function

Details

This mimics SAS procedues' BY clause.

Value

a list of `FUN` function outputs. The names are after each level.

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
BY(GLM, uptake ~ Treatment + as.factor(conc), C02, By="Type")
BY(REG, uptake ~ conc, C02, By="Type")
```

CIest	<i>Confidence Interval Estimation</i>
-------	---------------------------------------

Description

Get point estimate and its confidence interval with given contrast and alpha value using t distribution.

Usage

```
CIest(Formula, Data, Term, Contrast, conf.level=0.95)
```

Arguments

<code>Formula</code>	a conventional formula for a linear model
<code>Data</code>	a <code>data.frame</code> to be analyzed
<code>Term</code>	a factor name to be estimated
<code>Contrast</code>	a level vector. Level is alphabetically ordered by default.
<code>conf.level</code>	confidence level of confidence interval

Details

Get point estimate and its confidence interval with given contrast and alpha value using t distribution.

Value

Estimate	point estimate of the input linear constrast
Lower CL	lower confidence limit
Upper CL	upper confidence limit
Std. Error	standard error of the point estimate
t value	value for t distribution
Df	degree of freedom
Pr(> t)	probability of larger than absolute t value from t distribution with residual's degree of freedom

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
CIest(log(CMAX) ~ SEQ/SUBJ + PRD + TRT, BEdata, "TRT", c(-1, 1), 0.90) # 90% CI
```

Coll	<i>Collinearity Diagnostics</i>
------	---------------------------------

Description

Collinearity diagnostics with tolerance, VIF, eigenvalue, condition index, variance proportions

Usage

```
Coll(Formula, Data)
```

Arguments

Formula	formula of the model
Data	input data as a matrix or data.frame

Details

Sometimes collinearity diagnostics after multiple linear regression are necessary.

Value

Tol	tolerance of independent variables
VIF	variance inflation factor of independent variables
Eigenvalue	eigenvalue of $Z'Z$ (crossproduct) of standardized independent variables
Cond. Index	condition index
Proportions of variances	under the names of coefficients

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
Coll(mpg ~ disp + hp + drat + wt + qsec, mtcars)
```

 CONTR

F Test with a Set of Contrasts

Description

Do F test with a given set of contrasts.

Usage

```
CONTR(L, Formula, Data, mu=0)
```

Arguments

L	contrast matrix. Each row is a contrast.
Formula	a conventional formula for a linear model
Data	a data.frame to be analyzed
mu	a vector of mu for the hypothesis L. The length should be equal to the row count of L.

Details

It performs F test with a given set of contrasts (a matrix). It is similar to the CONTRAST clause of SAS PROC GLM. This can test the hypothesis that the linear combination (function)'s mean vector is mu.

Value

Returns sum of square and its F value and p-value.

Df	degree of freedom
Sum Sq	sum of square for the set of contrasts
Mean Sq	mean square
F value	F value for the F distribution
Pr(>F)	probability of larger than F value

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[cSS](#)

Examples

```
CONTR(t(c(0, -1, 1)), uptake ~ Type, CO2) # sum of square
GLM(uptake ~ Type, CO2) # compare with the above
```

Cor.test	<i>Correlation test of multiple numeric columns</i>
----------	---

Description

Testing correlation between numerics columns of data with Pearson method.

Usage

```
Cor.test(Data, conf.level=0.95)
```

Arguments

Data	a matrix or a data.frame
conf.level	confidence level

Details

It uses all numeric columns of input data. It uses "pairwise.complete.obs" rows.

Value

Row names show which columns are used for the test

Estimate	point estimate of correlation
Lower CL	upper confidence limit
Upper CL	lower confidence limit
t value	t value of the t distribution
Df	degree of freedom
Pr(> t)	probability with the t distribution

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
Cor.test(mtcars)
```

cSS

*Sum of Square with a Given Contrast Set***Description**

Calculates sum of squares of a contrast from a `lfit` result.

Usage

```
cSS(K, rx, mu=0, eps=1e-8)
```

Arguments

K	contrast matrix. Each row is a contrast.
rx	a result of <code>lfit</code> function
mu	a vector of mu for the hypothesis K. The length should be equal to the row count of K.
eps	Less than this value is considered as zero.

Details

It calculates sum of squares with given a contrast matrix and a `lfit` result. It corresponds to SAS PROC GLM CONTRAST. This can test the hypothesis that the linear combination (function)'s mean vector is mu.

Value

Returns sum of square and its F value and p-value.

Df	degree of freedom
Sum Sq	sum of square for the set of contrasts
Mean Sq	mean square
F value	F value for the F distribution
Pr(>F)	probability of larger than F value

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[CONTR](#)

Examples

```
rx = REG(uptake ~ Type, CO2, summarize=FALSE)
cSS(t(c(0, -1, 1)), rx) # sum of square
GLM(uptake ~ Type, CO2) # compare with the above
```

CV	<i>Coefficient of Variation in percentage</i>
----	---

Description

Coefficient of variation in percentage.

Usage

```
CV(x)
```

Arguments

x a numeric vector

Details

It removes NA.

Value

Coefficient of variation in percentage.

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
CV(mtcars$mpg)
```

Diffogram	<i>Plot Pairwise Differences</i>
-----------	----------------------------------

Description

Plot pairwise differences by a common.

Usage

```
Diffogram(Formula, Data, Term, conf.level=0.95, adj="lsd", ...)
```

Arguments

Formula	a conventional formula for a linear model
Data	a data.frame to be analyzed
Term	a factor name to be estimated
conf.level	confidence level of confidence interval
adj	"lsd", "tukey", "scheffe", "bon", or "duncan" to adjust p-value and confidence limit
...	arguments to be passed to plot

Details

This usually shows the shortest interval. It corresponds to SAS PROC GLM PDIFF. For adjustment method "dunnett", see PDIFF function.

Value

no return value, but a plot on the current device

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[LSM](#), [PDIFF](#)

Examples

```
Diffogram(uptake ~ Type*Treatment + as.factor(conc), C02, "as.factor(conc)")
```

e1

Get a Contrast Matrix for Type I SS

Description

Makes a contrast matrix for type I SS using forward Doolittle method.

Usage

```
e1(Formula, Data, eps=1e-8)
```

Arguments

Formula	a conventional formula for a linear model
Data	a data.frame to be analyzed
eps	Less than this value is considered as zero.

Details

It makes a contrast matrix for type I SS. If zapsmall is used, the result becomes more inaccurate.

Value

A contrast matrix for type I SS.

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
round(e1(uptake ~ Plant + Type + Treatment + conc, C02), 12)
```

e2	<i>Get a Contrast Matrix for Type II SS</i>
----	---

Description

Makes a contrast matrix for type II SS.

Usage

```
e2(Formula, Data, eps=1e-8)
```

Arguments

Formula	a conventional formula for a linear model
Data	a <code>data.frame</code> to be analyzed
eps	Less than this value is considered as zero.

Details

It makes a contrast matrix for type II SS. If `zapsmall` is used, the result becomes more inaccurate.

Value

A contrast matrix for type II SS.

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
round(e2(uptake ~ Plant + Type + Treatment + conc, C02), 12)
round(e2(uptake ~ Type, C02), 12)
round(e2(uptake ~ Type - 1, C02), 12)
```

e3	<i>Get a Contrast Matrix for Type III SS</i>
----	--

Description

Makes a contrast matrix for type III SS.

Usage

```
e3(Formula, Data, eps=1e-8)
```

Arguments

Formula	a conventional formula for a linear model
Data	a <code>data.frame</code> to be analyzed
eps	Less than this value is considered as zero.

Details

It makes a contrast matrix for type III SS. If `zapsmall` is used, the result becomes more inaccurate.

Value

A contrast matrix for type III SS.

Author(s)

Kyun-Seop Bae `k@acr.kr`

Examples

```
round(e3(uptake ~ Plant + Type + Treatment + conc, C02), 12)
```

EMS	<i>Expected Mean Square Formula</i>
-----	-------------------------------------

Description

Calculates a formula table for expected mean square of the given contrast. The default is for Type III SS.

Usage

```
EMS(Formula, Data, Type=3, eps=1e-8)
```

Arguments

Formula	a conventional formula for a linear model
Data	a <code>data.frame</code> to be analyzed
Type	type of sum of squares. The default is 3. Type 4 is not supported yet.
eps	Less than this value is considered as zero.

Details

This is necessary for further hypothesis test of nesting factors.

Value

A coefficient matrix for Type III expected mean square

Author(s)

Kyun-Seop Bae `k@acr.kr`

Examples

```
f1 = log(CMAX) ~ SEQ/SUBJ + PRD + TRT
EMS(f1, BEdata)
EMS(f1, BEdata, Type=1)
EMS(f1, BEdata, Type=2)
```

est	<i>Estimate Linear Functions</i>
-----	----------------------------------

Description

Estimates Linear Functions with a given GLM result.

Usage

```
est(L, X, rx, conf.level=0.95, adj="lsd", paired=FALSE)
```

Arguments

L	a matrix of linear contrast rows to be tested
X	a model (design) matrix from <code>ModelMatrix</code>
rx	a result of <code>lfit</code> function
conf.level	confidence level of confidence limit
adj	adjustment method for grouping. This supports "tukey", "bon", "scheffe", "duncan", and "dunnett". This only affects grouping, not the confidence interval.
paired	If this is TRUE, L matrix is for the pairwise comparison such as <code>PDIFF</code> function.

Details

It tests rows of linear function. Linear function means linear combination of estimated coefficients. It corresponds to SAS PROC GLM ESTIMATE. Same sample size per group is assumed for the Tukey adjustment.

Value

Estimate	point estimate of the input linear contrast
Lower CL	lower confidence limit by "lsd" method
Upper CL	upper confidence limit by "lsd" method
Std. Error	standard error of the point estimate
t value	value for t distribution for other than "scheffe" method
F value	value for F distribution for "scheffe" method only
Df	degree of freedom of residuals
Pr(> t)	probability of larger than absolute t value from t distribution with residual's degree of freedom, for other than "scheffe" method
Pr(>F)	probability of larger than F value from F distribution with residual's degree of freedom, for "scheffe" method only

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[ESTM](#), [PDIFF](#)

Examples

```
x = ModelMatrix(uptake ~ Type, C02)
rx = REG(uptake ~ Type, C02, summarize=FALSE)
est(t(c(0, -1, 1)), x$X, rx) # Quevec - Mississippi
t.test(uptake ~ Type, C02) # compare with the above
```

ESTM

*Estimate Linear Function***Description**

Estimates Linear Function with a formula and a dataset.

Usage

```
ESTM(L, Formula, Data, conf.level=0.95)
```

Arguments

L	a matrix of linear functions rows to be tested
Formula	a conventional formula for a linear model
Data	a data.frame to be analyzed
conf.level	confidence level of confidence limit

Details

It tests rows of linear functions. Linear function means linear combination of estimated coefficients. It is similar to SAS PROC GLM ESTIMATE. This is a little convenient version of est function.

Value

Estimate	point estimate of the input linear contrast
Lower CL	lower confidence limit
Upper CL	upper confidence limit
Std. Error	standard error of the point estimate
t value	value for t distribution
Df	degree of freedom
Pr(> t)	probability of larger than absolute t value from t distribution with residual's degree of freedom

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[est](#)

Examples

```
ESTM(t(c(0, -1, 1)), uptake ~ Type, C02) # Quevec - Mississippi
```

estmb	<i>Estimability Check</i>
-------	---------------------------

Description

Check the estimability of row vectors of coefficients.

Usage

```
estmb(L, X, g2, eps=1e-8)
```

Arguments

- L row vectors of coefficients
- X a model (design) matrix from ModelMatrix
- g2 g2 generalized inverse of crossprod(X)
- eps absolute value less than this is considered to be zero.

Details

It checks estimability of L, row vectors of coefficients. This corresponds to SAS PROC GLM ESTIMATE. See <Kennedy Jr. WJ, Gentle JE. Statistical Computing. 1980> p361 or <Golub GH, Styan GP. Numerical Computations for Univariate Linear Models. 1971>.

Value

a vector of logical values indicating which row is estimable (as TRUE)

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[G2SWEEP](#)

G2SWEEP	<i>Generalized inverse matrix of type 2, g2 inverse</i>
---------	---

Description

Generalized invserve is usually not unique. Some programs use this algorithm to get a uniuqe generalized inverse matrix.

Usage

```
G2SWEEP(A, Augmented=FALSE, eps=1e-08)
```

Arguments

A	a matrix to be inverted
Augmented	If this is TRUE and A is a model(design) matrix X, the last column should be $X'y$, the last row $y'X$, and the last cell $y'y$. See the reference and example for the detail.
eps	Less than this value is considered as zero.

Details

Generalized inverse of g2-type is used by some softwares to do linear regression. See 'SAS Technical Report R106, The Sweep Operator: Its importance in Statistical Computing' by J. H. Goodnight for the detail.

Value

when Augmented=FALSE	ordinary g2 inverse
when Augmented=TRUE	g2 inverse and beta hats in the last column and the last row, and sum of square error (SSE) in the last cell
attribute "rank"	the rank of input matrix

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[lfit](#), [ModelMatrix](#)

Examples

```
f1 = uptake ~ Type + Treatment # formula
x = ModelMatrix(f1, C02) # Model matrix and relevant information
y = model.frame(f1, C02)[,1] # observation vector
nc = ncol(x$X) # number of columns of model matrix
XpY = crossprod(x$X, y)
aXpX = rbind(cbind(crossprod(x$X), XpY), cbind(t(XpY), crossprod(y)))
ag2 = G2SWEEP(aXpX, Augmented=TRUE)
b = ag2[1:nc, (nc + 1)] ; b # Beta hat
iXpX = ag2[1:nc, 1:nc] ; iXpX # g2 inverse of X'X
SSE = ag2[(nc + 1), (nc + 1)] ; SSE # Sum of Square Error
DFr = nrow(x$X) - attr(ag2, "rank") ; DFr # Degree of freedom for the residual

# Compare the below with the above
REG(f1, C02)
aov1(f1, C02)
```

`geoCV`*Geometric Coefficient of Variation in percentage*

Description

Geometric coefficient of variation in percentage.

Usage

```
geoCV(x)
```

Arguments

`x` a numeric vector

Details

It removes NA. This is $\sqrt{\exp(\text{var}(\log(x))) - 1} \cdot 100$.

Value

Geometric coefficient of variation in percentage.

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
CV(mtcars$mpg)
```

`geoMean`*Geometric Mean without NA*

Description

mean without NA values.

Usage

```
geoMean(x)
```

Arguments

`x` a vector of numerics

Details

It removes NA in the input vector.

Value

geometric mean value

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[geoCV](#)

GLM	<i>General Linear Model similar to SAS PROC GLM</i>
-----	---

Description

GLM is the main function of this package.

Usage

GLM(Formula, Data, BETA=FALSE, EMEAN=FALSE, conf.level=0.95, eps=1e-8)

Arguments

Formula	a conventional formula for a linear model.
Data	a data.frame to be analyzed
BETA	if TRUE, coefficients (parameters) of REG will be returned. This is equivalent to SOLUTION option of SAS PROC GLM
EMEAN	if TRUE, least square means (or expected means) will be returned. This is equivalent to LSMEANS clause of SAS PROC GLM
conf.level	confidence level for the confidence limit of the least square mean
eps	Less than this value is considered as zero.

Details

It performs the core function of SAS PROC GLM. Least square means for the interaction term of three variables is not supported yet.

Value

The result is comparable to that of SAS PROC GLM.

ANOVA	ANOVA table for the model
Fitness	Some measures of goodness of fit such as R-square and CV
Type I	Type I sum of square table
Type II	Type II sum of square table
Type III	Type III sum of square table
Parameter	Parameter table with standard error, t value, p value. TRUE is 1, and FALSE is 0 in the Estimable column. This is returned only with BETA=TRUE option.
Expected Mean	Least square (or expected) mean table with confidence limit. This is returned only with EMEAN=TRUE option.

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
GLM(uptake ~ Type*Treatment + conc, CO2[-1,]) # Making data unbalanced
GLM(uptake ~ Type*Treatment + conc, CO2[-1,], BETA=TRUE)
GLM(uptake ~ Type*Treatment + conc, CO2[-1,], EMEAN=TRUE)
GLM(uptake ~ Type*Treatment + conc, CO2[-1,], BETA=TRUE, EMEAN=TRUE)
```

is.cor

Is it a correlation matrix?

Description

Testing if the input matrix is a correlation matrix or not

Usage

```
is.cor(m, eps=1e-16)
```

Arguments

m	a presumed correlation matrix
eps	epsilon value. Absolute value less than this is considered as zero.

Details

Diagonal component should not be necessarily 1. But it should be close to 1.

Value

TRUE or FALSE

Author(s)

Kyun-Seop Bae k@acr.kr

Kurtosis	<i>Kurtosis</i>
----------	-----------------

Description

Kurtosis with a conventional formula.

Usage

```
Kurtosis(x)
```

Arguments

x a vector of numerics

Details

It removes NA in the input vector.

Value

Estimate of kurtosis

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[KurtosisSE](#)

KurtosisSE	<i>Standard Error of Kurtosis</i>
------------	-----------------------------------

Description

Standard error of the estimated kurtosis with a conventional formula.

Usage

```
KurtosisSE(x)
```

Arguments

x a vector of numerics

Details

It removes NA in the input vector.

Value

Standard error of the estimated kurtosis

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[Kurtosis](#)

LCL

Lower Confidence Limit

Description

The estimate of the lower bound of confidence limit using t-distribution

Usage

```
LCL(x, conf.level=0.95)
```

Arguments

<code>x</code>	a vector of numerics
<code>conf.level</code>	confidence level

Details

It removes NA in the input vector.

Value

The estimate of the lower bound of confidence limit using t-distribution

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[UCL](#)

`lfit`*Linear Fit*

Description

Fits a least square linear model.

Usage

```
lfit(x, y, eps=1e-8)
```

Arguments

<code>x</code>	a result of <code>ModelMatrix</code>
<code>y</code>	a column vector of response, dependent variable
<code>eps</code>	Less than this value is considered as zero.

Details

Minimum version of least square fit of a linear model

Value

<code>coefficients</code>	beta coefficients
<code>g2</code>	g2 inverse
<code>rank</code>	rank of the model matrix
<code>DFr</code>	degree of freedom for the residual
<code>SSE</code>	sum of squares error
<code>SST</code>	sum of squares total
<code>DFr2</code>	degree of freedom of the residual for beta coefficient

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[ModelMatrix](#)

Examples

```
f1 = uptake ~ Type*Treatment + conc
x = ModelMatrix(f1, CO2)
y = model.frame(f1, CO2)[,1]
lfit(x, y)
```

lr	<i>Linear Regression with g2 inverse</i>
----	--

Description

Coefficients calculated with g2 inverse. Output is similar to `summary(lm())`.

Usage

```
lr(Formula, Data, eps=1e-16)
```

Arguments

Formula	a conventional formula for a linear model
Data	a <code>data.frame</code> to be analyzed
eps	Less than this value is considered as zero.

Details

It uses G2SWEEP to get g2 inverse. The result is similar to `summary(lm())` without options.

Value

The result is comparable to that of SAS PROC REG.

Estimate	point estimate of parameters, coefficients
Std. Error	standard error of the point estimate
t value	value for t distribution
Pr(> t)	probability of larger than absolute t value from t distribution with residual's degree of freedom

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
lr(uptake ~ Plant + Type + Treatment + conc, C02)
lr(uptake ~ Plant + Type + Treatment + conc - 1, C02)
lr(uptake ~ Type, C02)
lr(uptake ~ Type - 1, C02)
```

`lr0`*Simple Linear Regressions with Each Independent Variable*

Description

Usually the first step to multiple linear regression is the simple linear regressions with single independent variable.

Usage

```
lr0(Formula, Data)
```

Arguments

Formula	a conventional formula for a linear model. Intercept will be added always.
Data	a <code>data.frame</code> to be analyzed

Details

It performs .

Value

Each row means one simple linear regression with that row name as the only independent variable.

Intercept	estimate of the intercept
SE(Intercept)	standard error of the intercept
Slope	estimate of the slope
SE(Slope)	standard error of the slope
Rsquared	R-squared for the simple linear model
Pr(>F)	p-value of slope or the model

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
lr0(uptake ~ Plant + Type + Treatment + conc, CO2)
lr0(mpg ~ ., mtcars)
```

LSM	<i>Least Square Means</i>
-----	---------------------------

Description

Estimates least square means using g2 inverse.

Usage

```
LSM(Formula, Data, Term, conf.level=0.95, adj="lsd", hideNonEst=TRUE,
    PLOT=FALSE, ...)
```

Arguments

Formula	a conventional formula of model
Data	data.frame
Term	term name to be returned. If there is only one independent variable, this can be omitted.
conf.level	confidence level for the confidence limit
adj	adjustment method for grouping, "lsd"(default), "tukey", "bon", "duncan", "scheffe" are available. This does not affects SE, Lower CL, Upper CL of the output table.
hideNonEst	hide non-estimables
PLOT	whether to plot LSMs and their confidence intervals
...	arguments to be passed to plot

Details

It corresponds to SAS PROC GLM LSMEANS. The result of the second example below may be different from emmeans. This is because SAS or this function calculates mean of the transformed continuous variable. However, emmeans calculates the average before the transformation. Interaction of three variables is not supported yet. For adjustmethod method "dunnett", see PDIFF function.

Value

Returns a table of expectations, t values and p-values.

Group	group character. This appears with one-way ANOVA or Term or adj argument is provided.
LSmean	point estimate of least square mean
LowerCL	lower confidence limit with the given confidence level by "lsd" method
UpperCL	upper confidence limit with the given confidence level by "lsd" method
SE	standard error of the point estimate
Df	degree of freedom of point estimate

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[PDIFF](#), [Diffogram](#)

Examples

```
LSM(uptake ~ Type, C02[-1,])
LSM(uptake ~ Type - 1, C02[-1,])
LSM(uptake ~ Type*Treatment + conc, C02[-1,])
LSM(uptake ~ Type*Treatment + conc - 1, C02[-1,])
LSM(log(uptake) ~ Type*Treatment + log(conc), C02[-1,])
LSM(log(uptake) ~ Type*Treatment + log(conc) - 1, C02[-1,])
LSM(log(uptake) ~ Type*Treatment + as.factor(conc), C02[-1,])
LSM(log(uptake) ~ Type*Treatment + as.factor(conc) - 1, C02[-1,])
LSM(log(CMAX) ~ SEQ/SUBJ + PRD + TRT, BEdata)
LSM(log(CMAX) ~ SEQ/SUBJ + PRD + TRT - 1, BEdata)
```

Max	Max without NA
-----	----------------

Description

maximum without NA values.

Usage

```
Max(x)
```

Arguments

x a vector of numerics

Details

It removes NA in the input vector.

Value

maximum value

Author(s)

Kyun-Seop Bae k@acr.kr

Mean	<i>Mean without NA</i>
------	------------------------

Description

mean without NA values.

Usage

```
Mean(x)
```

Arguments

x a vector of numerics

Details

It removes NA in the input vector.

Value

mean value

Author(s)

Kyun-Seop Bae k@acr.kr

Median	<i>Median without NA</i>
--------	--------------------------

Description

median without NA values.

Usage

```
Median(x)
```

Arguments

x a vector of numerics

Details

It removes NA in the input vector.

Value

median value

Author(s)

Kyun-Seop Bae k@acr.kr

Min	<i>Min without NA</i>
-----	-----------------------

Description

minimum without NA values.

Usage

```
Min(x)
```

Arguments

x a vector of numerics

Details

It removes NA in the input vector.

Value

minimum value

Author(s)

Kyun-Seop Bae k@acr.kr

ModelMatrix	<i>Model Matrix</i>
-------------	---------------------

Description

This model matrix is similar to `model.matrix`. But it does not omit unnecessary columns.

Usage

```
ModelMatrix(Formula, Data, KeepOrder=FALSE)
```

Arguments

Formula	a conventional formula for a linear model
Data	a <code>data.frame</code> to be analyzed
KeepOrder	If <code>KeepOrder</code> is TRUE, terms in <code>Formula</code> will be kept. This is for Type I SS.

Details

It makes the `model(design)` matrix for GLM.

Value

Model matrix and attributes similar to the output of `model.matrix`.

<code>X</code>	design matrix, i.e. model matrix
<code>terms</code>	detailed information about terms such as formula and labels
<code>termsIndices</code>	term indices
<code>assign</code>	assignment of columns for each terms in order, different way of expressing term indices

Author(s)

Kyun-Seop Bae k@acr.kr

N	<i>Number of observations</i>
---	-------------------------------

Description

Number of observations excluding NA values

Usage

`N(x)`

Arguments

`x` a vector of numerics

Details

It removes NA in the input vector.

Value

Count of the observation

Author(s)

Kyun-Seop Bae k@acr.kr

OR	<i>Odds Ratio of two groups</i>
----	---------------------------------

Description

Odds Ratio between two groups

Usage

```
OR(y1, n1, y2, n2, conf.level=0.95)
```

Arguments

y1	positive event count of test (the first) group
n1	total count of the test (the first) group
y2	positive event count of control (the second) group
n2	total count of control (the second) group
conf.level	confidence level

Details

It calculates odds ratio of two groups. No continuity correction here. If you need percent scale, multiply the output by 100.

Value

The result is a data.frame.

odd1	proportion from the first group
odd2	proportion from the second group
OR	odds ratio, odd1/odd2
SElog	standard error of log(OR)
lower	lower confidence limit of OR
upper	upper confidence limit of OR

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[RD](#), [RR](#), [RDmn1](#), [RRmn1](#), [ORmn1](#), [RDmn](#), [RRmn](#), [ORmn](#)

Examples

```
OR(104, 11037, 189, 11034) # no continuity correction
```

ORcmh

*Odds Ratio and Score CI of two groups with strata by CMH method***Description**

Odds ratio and its score confidence interval of two groups with stratification by Cochran-Mantel-Haenszel method

Usage

```
ORcmh(d0, conf.level=0.95)
```

Arguments

d0	A data.frame or matrix, of which each row means a strata. This should have four columns named y1, n1, y2, and n2; y1 and y2 for events of each group, n1 and n2 for sample size of each strata. The second group is usually the control group.
conf.level	confidence level

Details

It calculates odds ratio and its score confidence interval of two groups. This can be also used for meta-analysis.

Value

The following output will be returned for each strata and common value. There is no standard error.

odd1	odd from the first group, $y1/(n1 - y1)$
odd2	odd from the second group, $y2/(n2 - y2)$
OR	odds ratio, odd1/odd2. Point estimate of common OR is calculated with MH weight.
lower	lower confidence limit of OR
upper	upper confidence limit of OR

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[RDmn1](#), [RRmn1](#), [ORmn1](#), [RDmn](#), [RRmn](#), [RDinv](#), [RRinv](#), [ORinv](#)

Examples

```
d1 = matrix(c(25, 339, 28, 335, 23, 370, 40, 364), nrow=2, byrow=TRUE)
colnames(d1) = c("y1", "n1", "y2", "n2")
ORcmh(d1)
```

ORinv	<i>Odds Ratio and Score CI of two groups with strata by inverse variance method</i>
-------	---

Description

Odds ratio and its score confidence interval of two groups with stratification by inverse variance method

Usage

```
ORinv(d0, conf.level=0.95)
```

Arguments

d0	A data.frame or matrix, of which each row means a strata. This should have four columns named y1, n1, y2, and n2; y1 and y2 for events of each group, n1 and n2 for sample size of each strata. The second group is usually the control group.
conf.level	confidence level

Details

It calculates odds ratio and its score confidence interval of two groups. The confidence interval is asymmetric and there is no standard error in the output. This supports stratification. This implementation uses nlminb minimization function which usually gives about 7 significant digits. PropCIs::orscoreci function uses incremental or decremental search by the factor of 1.001 which gives only about 3 significant digits.

Value

The following output will be returned for each strata and common value. There is no standard error.

odd1	odd from the first group, $y1/(n1 - y1)$
odd2	odd from the second group, $y2/(n2 - y2)$
OR	odds ratio, odd1/odd2. Point estimate of common OR is calculated with MH weight.
lower	lower confidence limit of OR
upper	upper confidence limit of OR

Author(s)

Kyun-Seop Bae k@acr.kr

References

Miettinen O, Nurminen M. Comparative analysis of two rates. Stat Med 1985;4:213-26

See Also

[RDMn1](#), [RRmn1](#), [ORMn1](#), [RDMn](#), [RRmn](#), [RRinv](#), [ORinv](#), [ORcmh](#)

Examples

```
d1 = matrix(c(25, 339, 28, 335, 23, 370, 40, 364), nrow=2, byrow=TRUE)
colnames(d1) = c("y1", "n1", "y2", "n2")
ORinv(d1)
```

ORmn

*Odds Ratio and Score CI of two groups with strata by MN method***Description**

Odds ratio and its score confidence interval of two groups with stratification by Miettinen and Nurminen method

Usage

```
ORmn(d0, conf.level=0.95, eps=1e-8)
```

Arguments

d0	A data.frame or matrix, of which each row means a strata. This should have four columns named y1, n1, y2, and n2; y1 and y2 for events of each group, n1 and n2 for sample size of each strata. The second group is usually the control group.
conf.level	confidence level
eps	absolute value less than eps is regarded as 0

Details

It calculates odds ratio and its score confidence interval of two groups. The confidence interval is asymmetric and there is no standard error in the output. This supports stratification. This implementation uses nlminb minimization function which usually gives about 7 significant digits. PropCIs::orscoreci function uses incremental or decremental search by the factor of 1.001 which gives only about 3 significant digits.

Value

The following output will be returned for each strata and common value. There is no standard error.

odd1	odd from the first group, $y1/(n1 - y1)$
odd2	odd from the second group, $y2/(n2 - y2)$
OR	odds ratio, odd1/odd2. Point estimate of common OR is calculated with MH weight.
lower	lower confidence limit of OR
upper	upper confidence limit of OR

Author(s)

Kyun-Seop Bae k@acr.kr

References

Miettinen O, Nurminen M. Comparative analysis of two rates. Stat Med 1985;4:213-26

See Also

[RDMn1](#), [RRmn1](#), [ORmn1](#), [RDmn](#), [RRmn](#), [RDinv](#), [RRinv](#), [ORinv](#), [ORcmh](#)

Examples

```
d1 = matrix(c(25, 339, 28, 335, 23, 370, 40, 364), nrow=2, byrow=TRUE)
colnames(d1) = c("y1", "n1", "y2", "n2")
ORmn(d1)
```

ORmn1

Odds Ratio and Score CI of two groups by MN method

Description

Odds ratio and its score confidence interval of two groups without stratification

Usage

```
ORmn1(y1, n1, y2, n2, conf.level=0.95)
```

Arguments

y1	positive event count of test (the first) group
n1	total count of the test (the first) group
y2	positive event count of control (the second) group
n2	total count of control (the second) group
conf.level	confidence level

Details

It calculates odds ratio and its score confidence interval of two groups. The confidence interval is asymmetric and there is no standard error in the output. This does not support stratification. This implementation uses `nlminb` minimization function which usually gives about 7 significant digits. `PropCIs::orscoreci` function uses incremental or decremental search by the factor of 1.001 which gives only about 3 significant digits.

Value

The result is a data.frame. There is no standard error.

odd1	odd from the first group, $y1/(n1 - y1)$
odd2	odd from the second group, $y2/(n2 - y2)$
OR	odds ratio, $odd1/odd2$
lower	lower confidence limit of OR
upper	upper confidence limit of OR

Author(s)

Kyun-Seop Bae k@acr.kr

References

Miettinen O, Nurminen M. Comparative analysis of two rates. Stat Med 1985;4:213-26

See Also

[RDmn1](#), [RRmn1](#), [RDmn](#), [RRmn](#), [ORmn](#)

Examples

```
ORmn1(104, 11037, 189, 11034)
```

pB

Plot Confidence and Prediction Bands for Simple Linear Regression

Description

It plots bands of confidence interval and prediction interval for simple linear regression.

Usage

```
pB(Formula, Data, Resol=300, conf.level=0.95, lx, ly, ...)
```

Arguments

Formula	a formula
Data	a data.frame
Resol	resolution for the output
conf.level	confidence level
lx	x position of legend
ly	y position of legend
...	arguments to be passed to plot

Details

It plots. Discard return values. If lx or ly is missing, legend position is calculated automatically.

Value

Ignore return values.

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
pB(hp ~ disp, mtcars)
pB(mpg ~ disp, mtcars)
```

`Pcor.test`*Partial Correlation test of multiple columns*

Description

Testing partial correlation between many columns of data with Pearson method.

Usage

```
Pcor.test(Data, x, y)
```

Arguments

<code>Data</code>	a numeric matrix or data.frame
<code>x</code>	names of to be tested columns
<code>y</code>	names of control columns

Details

It performs multiple partial correlation test. It uses "complete.obs" rows of x and y columns.

Value

Row names show which columns are used for the test

<code>Estimate</code>	point estimate of correlation
<code>Df</code>	degree of freedom
<code>t value</code>	t value of the t distribution
<code>Pr(> t)</code>	probability with the t distribution

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
Pcor.test(mtcars, c("mpg", "hp", "qsec"), c("drat", "wt"))
```

pD

Diagnostic Plot for Regression

Description

Four standard diagnostic plots for regression.

Usage

```
pD(rx, Title=NULL)
```

Arguments

rx a result of lm, which can give fitted, residuals, and rstandard.
Title title to be printed on the plot

Details

Most frequently used diagnostic plots are 'observed vs. fitted', 'standarized residual vs. fitted', 'distribution plot of standard residuals', and 'Q-Q plot of standardized residuals'.

Value

Four diagnostic plots in a page.

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
pD(lm(uptake ~ Plant + Type + Treatment + conc, C02), "Diagnostic Plot")
```

PDIFF

Pairwise Difference

Description

Estimates pairwise difference by a common method.

Usage

```
PDIFF(Formula, Data, Term, conf.level=0.95, adj="lsd", ref, PLOT=FALSE,
       reverse=FALSE, ...)
```

Arguments

Formula	a conventional formula for a linear model
Data	a <code>data.frame</code> to be analyzed
Term	a factor name to be estimated
conf.level	confidence level of confidence interval
adj	"lsd", "tukey", "scheffe", "bon", "duncan", or "dunnett" to adjust p-value and confidence limit
ref	reference or control level for Dunnett test
PLOT	whether to plot or not the diffogram
reverse	reverse A - B to B - A
...	arguments to be passed to plot

Details

It corresponds to PDIFF option of SAS PROC GLM.

Value

Returns a table of expectations, t values and p-values. Outpuc columns may vary according to the adjustment option.

Estimate	point estimate of the input linear constrast
Lower CL	lower confidence limit
Upper CL	upper confidence limit
Std. Error	standard error of the point estimate
t value	value for t distribution
Df	degree of freedom
Pr(> t)	probability of larger than absolute t value from t distribution with residual's degree of freedom

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[LSM](#), [Diffogram](#)

Examples

```
PDIFF(uptake ~ Type*Treatment + as.factor(conc), C02, "as.factor(conc)")
PDIFF(uptake ~ Type*Treatment + as.factor(conc), C02, "as.factor(conc)", adj="tukey")
```

pResD	<i>Residual Diagnostic Plot for Regression</i>
-------	--

Description

Nine residual diagnostics plot.

Usage

```
pResD(rx, Title=NULL)
```

Arguments

rx	a result of lm, which can give fitted, residuals, and rstandard.
Title	title to be printed on the plot

Details

SAS style residual diagnostic plots.

Value

Nine residual diagnostic plots in a page.

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
pResD(lm(uptake ~ Plant + Type + Treatment + conc, CO2), "Residual Diagnostic Plot")
```

QuartileRange	<i>Inter-Quartile Range</i>
---------------	-----------------------------

Description

Interquartile range (Q3 - Q1) with a conventional formula.

Usage

```
QuartileRange(x, Type=2)
```

Arguments

x	a vector of numerics
Type	a type specifier to be passed to IQR function

Details

It removes NA in the input vector. Type 2 is SAS default, while Type 6 is SPSS default.

Value

The value of interquartile range

Author(s)

Kyun-Seop Bae k@acr.kr

Range	<i>Range</i>
-------	--------------

Description

The range, maximum - minimum, as a scalar value.

Usage

Range(x)

Arguments

x a vector of numerics

Details

It removes NA in the input vector.

Value

A scalar value of range

Author(s)

Kyun-Seop Bae k@acr.kr

RD	<i>Risk Difference between two groups</i>
----	---

Description

Risk (proportion) difference between two groups

Usage

RD(y1, n1, y2, n2, conf.level=0.95)

Arguments

y1	positive event count of test (the first) group
n1	total count of the test (the first) group
y2	positive event count of control (the second) group
n2	total count of control (the second) group
conf.level	confidence level

Details

It calculates risk difference between two groups. No continuity correction here. If you need percent scale, multiply the output by 100.

Value

The result is a data.frame.

p1	proportion from the first group
p2	proportion from the second group
RD	risk difference, $p1 - p2$
SE	standard error of RD
lower	lower confidence limit of RD
upper	upper confidence limit of RD

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[RR](#), [OR](#), [RDmn1](#), [RRmn1](#), [ORmn1](#), [RDmn](#), [RRmn](#), [ORmn](#)

Examples

```
RD(104, 11037, 189, 11034) # no continuity correction
```

RDinv

Risk Difference and Score CI between two groups with strata by inverse variance method

Description

Risk difference and its score confidence interval between two groups with stratification by inverse variance method

Usage

```
RDinv(d0, conf.level=0.95)
```

Arguments

<code>d0</code>	A data.frame or matrix, of which each row means a strata. This should have four columns named <code>y1</code> , <code>n1</code> , <code>y2</code> , and <code>n2</code> ; <code>y1</code> and <code>y2</code> for events of each group, <code>n1</code> and <code>n2</code> for sample size of each strata. The second group is usually the control group.
<code>conf.level</code>	confidence level

Details

It calculates risk difference and its score confidence interval between two groups. The confidence interval is asymmetric and there is no standard error in the output. If you need percent scale, multiply the output by 100. This supports stratification. This implementation uses `nlminb` minimization function.

Value

The following output will be returned for each strata and common value. There is no standard error.

<code>p1</code>	proportion from the first group, $y1/n1$
<code>p2</code>	proportion from the second group, $y2/n2$
<code>RD</code>	risk difference, $p1 - p2$. Point estimate of common RD is calculated with MH weight.
<code>lower</code>	lower confidence limit of RD
<code>upper</code>	upper confidence limit of RD

Author(s)

Kyun-Seop Bae k@acr.kr

References

Miettinen O, Nurminen M. Comparative analysis of two rates. *Stat Med* 1985;4:213-26

See Also

[RDmn1](#), [RRmn1](#), [ORmn1](#), [RRmn](#), [ORmn](#), [RRinv](#), [ORinv](#), [ORcmh](#)

Examples

```
d1 = matrix(c(25, 339, 28, 335, 23, 370, 40, 364), nrow=2, byrow=TRUE)
colnames(d1) = c("y1", "n1", "y2", "n2")
RDinv(d1)
```

RDmn	<i>Risk Difference and Score CI between two groups with strata by MN method</i>
------	---

Description

Risk difference and its score confidence interval between two groups with stratification by Miettinen and Nurminen method

Usage

```
RDmn(d0, conf.level=0.95, eps=1e-8)
```

Arguments

d0	A data.frame or matrix, of which each row means a strata. This should have four columns named y1, n1, y2, and n2; y1 and y2 for events of each group, n1 and n2 for sample size of each strata. The second group is usually the control group.
conf.level	confidence level
eps	absolute value less than eps is regarded as 0

Details

It calculates risk difference and its score confidence interval between two groups. The confidence interval is asymmetric and there is no standard error in the output. If you need percent scale, multiply the output by 100. This supports stratification. This implementation uses nlminb minimization function.

Value

The following output will be returned for each strata and common value. There is no standard error.

p1	proportion from the first group, y1/n1
p2	proportion from the second group, y2/n2
RD	risk difference, p1 - p2. Point estimate of common RD is calculated with MH weight.
lower	lower confidence limit of RD
upper	upper confidence limit of RD

Author(s)

Kyun-Seop Bae k@acr.kr

References

Miettinen O, Nurminen M. Comparative analysis of two rates. Stat Med 1985;4:213-26

See Also

[RDmn1](#), [RRmn1](#), [ORMn1](#), [RRmn](#), [ORMn](#), [RDinv](#), [RRinv](#), [ORinv](#), [ORcmh](#)

Examples

```
d1 = matrix(c(25, 339, 28, 335, 23, 370, 40, 364), nrow=2, byrow=TRUE)
colnames(d1) = c("y1", "n1", "y2", "n2")
RDmn(d1)
```

RDmn1

*Risk Difference and Score CI between two groups by MN method***Description**

Risk difference and its score confidence interval between two groups without stratification

Usage

```
RDmn1(y1, n1, y2, n2, conf.level=0.95)
```

Arguments

y1	positive event count of test (the first) group
n1	total count of the test (the first) group
y2	positive event count of control (the second) group
n2	total count of control (the second) group
conf.level	confidence level

Details

It calculates risk difference and its score confidence interval between two groups. The confidence interval is asymmetric and there is no standard error in the output. If you need percent scale, multiply the output by 100. This does not support stratification. This implementation uses nlminb minimization function.

Value

The result is a data.frame. There is no standard error.

p1	proportion from the first group, $y1/n1$
p2	proportion from the second group, $y2/n2$
RD	risk difference, $p1 - p2$
lower	lower confidence limit of RD
upper	upper confidence limit of RD

Author(s)

Kyun-Seop Bae k@acr.kr

References

Miettinen O, Nurminen M. Comparative analysis of two rates. Stat Med 1985;4:213-26

See Also

[RRmn1](#), [ORmn1](#), [RDmn](#), [RRmn](#), [ORmn](#)

Examples

```
RDmn1(104, 11037, 189, 11034)
```

REG

Regression of Linear Least Square, similar to SAS PROC REG

Description

REG is similar to SAS PROC REG.

Usage

```
REG(Formula, Data, eps=1e-8, summarize=TRUE)
```

Arguments

Formula	a conventional formula for a linear model
Data	a <code>data.frame</code> to be analyzed
eps	Less than this value is considered as zero.
summarize	If this is FALSE, REG returns just <code>lfit</code> result.

Details

It performs the core function of SAS PROC REG.

Value

The result is comparable to that of SAS PROC REG.

Estimate	point estimate of parameters, coefficients
Estimable	estimability: 1=TRUE, 0=FALSE. This appears only when at least one inestimability occurs.
Std. Error	standard error of the point estimate
t value	value for t distribution
Pr(> t)	probability of larger than absolute t value from t distribution with residual's degree of freedom

If `summarize=FALSE`, REG returns;

coefficients	beta coefficients
g2	g2 inverse
rank	rank of the model matrix
Dfr	degree of freedom for the residual
SSE	sum of square error

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[lr](#)

Examples

```
REG(uptake ~ Plant + Type + Treatment + conc, C02)
REG(uptake ~ conc, C02, summarize=FALSE)
```

regD	<i>Regression of Conventional Way with Rich Diagnostics</i>
------	---

Description

regD provides rich diagnostics such as student residual, leverage(hat), Cook’s D, studentized deleted residual, DFFITS, and DFBETAS.

Usage

```
regD(Formula, Data)
```

Arguments

Formula	a conventional formula for a linear model
Data	a <code>data.frame</code> to be analyzed

Details

It performs the conventional regression analysis. This does not use `g2` inverse, therefore it cannot handle singular matrix. If the `model(design)` matrix is not full rank, use `REG` or less parameters.

Value

Coefficients	conventional coefficients summary with Wald statistics
Diagnostics	Diagnostics table for detecting outlier or influential/leverage points. This includes fitted (Predicted), residual (Residual), standard error of residual(<code>se_resid</code>), studentized residual(<code>RStudent</code>), <code>hat</code> (Leverage), Cook’s D, studentized deleted residual(<code>sdResid</code>), <code>DIFFITS</code> , and <code>COVRATIO</code> .
DFBETAS	Column names are the names of coefficients. Each row shows how much each coefficient is affected by deleting the coressponding row of observation.

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
regD(uptake ~ conc, C02)
```

RR	<i>Relative Risk of two groups</i>
----	------------------------------------

Description

Relative Risk between two groups

Usage

```
RR(y1, n1, y2, n2, conf.level=0.95)
```

Arguments

y1	positive event count of test (the first) group
n1	total count of the test (the first) group
y2	positive event count of control (the second) group
n2	total count of control (the second) group
conf.level	confidence level

Details

It calculates relative risk of two groups. No continuity correction here. If you need percent scale, multiply the output by 100.

Value

The result is a data.frame.

p1	proportion from the first group
p2	proportion from the second group
RR	relative risk, p1/p2
SElog	standard error of log(RR)
lower	lower confidence limit of RR
upper	upper confidence limit of RR

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[RD](#), [OR](#), [RDmn1](#), [RRmn1](#), [ORMn1](#), [RDmn](#), [RRmn](#), [ORMn](#)

Examples

```
RR(104, 11037, 189, 11034) # no continuity correction
```

RRinv	<i>Relative Risk and Score CI of two groups with strata by inverse variance method</i>
-------	--

Description

Relative risk and its score confidence interval of two groups with stratification by inverse variance method

Usage

```
RRinv(d0, conf.level=0.95)
```

Arguments

d0	A data.frame or matrix, of which each row means a strata. This should have four columns named y1, n1, y2, and n2; y1 and y2 for events of each group, n1 and n2 for sample size of each strata. The second group is usually the control group.
conf.level	confidence level

Details

It calculates relative risk and its score confidence interval of two groups. The confidence interval is asymmetric and there is no standard error in the output. This supports stratification. This implementation uses nlminb minimization function which usually gives about 7 significant digits. PropCIs::riskscoreci function uses cubic equation approximation which gives only about 2 significant digits.

Value

The following output will be returned for each strata and common value. There is no standard error.

p1	proportion from the first group, y1/n1
p2	proportion from the second group, y2/n2
RR	relative risk, p1/p2. Point estimate of common RR is calculated with MH weight.
lower	lower confidence limit of RR
upper	upper confidence limit of RR

Author(s)

Kyun-Seop Bae k@acr.kr

References

Miettinen O, Nurminen M. Comparative analysis of two rates. Stat Med 1985;4:213-26

See Also

[RDMn1](#), [RRmn1](#), [ORMn1](#), [RDMn](#), [ORMn](#), [RDinv](#), [ORinv](#), [ORcmh](#)

Examples

```
d1 = matrix(c(25, 339, 28, 335, 23, 370, 40, 364), nrow=2, byrow=TRUE)
colnames(d1) = c("y1", "n1", "y2", "n2")
RRinv(d1)
```

RRmn

Relative Risk and Score CI of two groups with strata by MN method

Description

Relative risk and its score confidence interval of two groups with stratification by Miettinen and Nurminen method

Usage

```
RRmn(d0, conf.level=0.95, eps=1e-8)
```

Arguments

d0	A data.frame or matrix, of which each row means a strata. This should have four columns named y1, n1, y2, and n2; y1 and y2 for events of each group, n1 and n2 for sample size of each strata. The second group is usually the control group.
conf.level	confidence level
eps	absolute value less than eps is regarded as 0

Details

It calculates relative risk and its score confidence interval of two groups. The confidence interval is asymmetric and there is no standard error in the output. This supports stratification. This implementation uses nlminb minimization function which usually gives about 7 significant digits. PropCIs::riskscoreci function uses cubic equation approximation which gives only about 2 significant digits.

Value

The following output will be returned for each strata and common value. There is no standard error.

p1	proportion from the first group, y1/n1
p2	proportion from the second group, y2/n2
RR	relative risk, p1/p2. Point estimate of common RR is calculated with MH weight.
lower	lower confidence limit of RR
upper	upper confidence limit of RR

Author(s)

Kyun-Seop Bae k@acr.kr

References

Miettinen O, Nurminen M. Comparative analysis of two rates. Stat Med 1985;4:213-26

See Also

[RDMn1](#), [RRmn1](#), [ORMn1](#), [RDmn](#), [ORMn](#), [RDinv](#), [RRinv](#), [ORinv](#), [ORcmh](#)

Examples

```
d1 = matrix(c(25, 339, 28, 335, 23, 370, 40, 364), nrow=2, byrow=TRUE)
colnames(d1) = c("y1", "n1", "y2", "n2")
RRmn(d1)
```

RRmn1

Relative Risk and Score CI of two groups by MN method

Description

Relative risk and its score confidence interval of two groups without stratification

Usage

```
RRmn1(y1, n1, y2, n2, conf.level=0.95)
```

Arguments

y1	positive event count of test (the first) group
n1	total count of the test (the first) group
y2	positive event count of control (the second) group
n2	total count of control (the second) group
conf.level	confidence level

Details

It calculates relative risk and its score confidence interval of two groups. The confidence interval is asymmetric and there is no standard error in the output. This does not support stratification. This implementation uses `nlminb` minimization function which usually gives about 7 significant digits. `PropCIs::riskscoreci` function uses cubic equation approximation which gives only about 2 significant digits.

Value

The result is a data.frame. There is no standard error.

p1	proportion from the first group, y1/n1
p2	proportion from the second group, y2/n2
RR	relative risk, p1/p2
lower	lower confidence limit of RR
upper	upper confidence limit of RR

Author(s)

Kyun-Seop Bae k@acr.kr

References

Miettinen O, Nurminen M. Comparative analysis of two rates. Stat Med 1985;4:213-26

See Also

[RDmn1](#), [ORmn1](#), [RDmn](#), [RRmn](#), [ORmn](#)

Examples

RRmn1(104, 11037, 189, 11034)

satt	<i>Satterthwaite Approximation of Variance and Degree of Freedom</i>
------	--

Description

Calculates pooled variance and degree of freedom using Satterthwaite equation.

Usage

satt(vars, dfs, ws=c(1, 1))

Arguments

- vars a vector of variances
- dfs a vector of degree of freedoms
- ws a vector of weights

Details

The input can be more than two variances.

Value

- Variance approximated variance
- Df degree of freedom

Author(s)

Kyun-Seop Bae k@acr.kr

ScoreCI	<i>Score CI of a proportion</i>
---------	---------------------------------

Description

Score confidence of a proportion in one group

Usage

```
ScoreCI(y, n, conf.level=0.95)
```

Arguments

y	positive event count of a group
n	total count of a group
conf.level	confidence level

Details

It calculates score confidence interval of a proportion in one group. The confidence interval is asymmetric and there is no standard error in the output. If you need percent scale, multiply the output by 100.

Value

The result is a data.frame. There is no standard error.

Prop	proportion from the first group
lower	lower confidence limit of Prop
upper	upper confidence limit of Prop

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[binom.test](#)

Examples

```
ScoreCI(104, 11037)
```

SD	<i>Standard Deviation</i>
----	---------------------------

Description

Standard deviation of sample.

Usage

SD(x)

Arguments

x a vector of numerics

Details

It removes NA in the input vector. The length of the vector should be larger than 1.

Value

Sample standard deviation

Author(s)

Kyun-Seop Bae k@acr.kr

SEM	<i>Standard Error of the Sample Mean</i>
-----	--

Description

The estimate of the standard error of the sample mean

Usage

SEM(x)

Arguments

x a vector of numerics

Details

It removes NA in the input vector.

Value

The estimate of the standard error of the sample mean

Author(s)

Kyun-Seop Bae k@acr.kr

Skewness	<i>Skewness</i>
----------	-----------------

Description

Skewness with a conventional formula.

Usage

`Skewness(x)`

Arguments

`x` a vector of numerics

Details

It removes NA in the input vector.

Value

Estimate of skewness

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[SkewnessSE](#)

SkewnessSE	<i>Standard Error of Skewness</i>
------------	-----------------------------------

Description

Standard error of the skewness with a conventional formula.

Usage

`SkewnessSE(x)`

Arguments

`x` a vector of numerics

Details

It removes NA in the input vector.

Value

Standard error of the estimated skewness

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[Skewness](#)

SLICE	<i>F Test with Slice</i>
-------	--------------------------

Description

Do F test with a given slice term.

Usage

```
SLICE(Formula, Data, mTerm, sTerm)
```

Arguments

Formula	a conventional formula for a linear model
Data	a <code>data.frame</code> to be analyzed
mTerm	a factor name (not interaction) to calculate sum of square and do F test with least square means
sTerm	a factor name to be used for slice

Details

It performs F test with a given slice term. It is similar to the SLICE option SAS PROC GLM.

Value

Returns sum of square and its F value and p-value.

Df	degree of freedom
Sum Sq	sum of square for the set of contrasts
Mean Sq	mean square
F value	F value for the F distribution
Pr(>F)	probability of larger than F value

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
SLICE(uptake ~ Type*Treatment, CO2, "Type", "Treatment")
SLICE(uptake ~ Type*Treatment, CO2, "Treatment", "Type")
```

SS	<i>Sum of Square</i>
----	----------------------

Description

Sum of squares with ANOVA.

Usage

```
SS(x, rx, L, eps=1e-8)
```

Arguments

x	a result of <code>ModelMatrix</code> containing design information
rx	a result of <code>lfit</code>
L	linear hypothesis, a full matrix matching the information in x
eps	Less than this value is considered as zero.

Details

It calculates sum of squares and completes the ANOVA table.

Value

ANOVA table	a classical ANOVA table without the residual(Error) part.
-------------	---

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[ModelMatrix](#), [lfit](#)

T3MS	<i>Type III Expected Mean Square Formula</i>
------	--

Description

Calculates a formula table for expected mean square of Type III SS.

Usage

```
T3MS(Formula, Data, L0, eps=1e-8)
```

Arguments

Formula	a conventional formula for a linear model
Data	a data.frame to be analyzed
L0	a matrix of row linear contrasts, if missed, e3 is used
eps	Less than this value is considered as zero.

Details

This is necessary for further hypothesis test of nesting factors.

Value

A coefficient matrix for Type III expected mean square

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
T3MS(log(CMAX) ~ SEQ/SUBJ + PRD + TRT, BEdata)
```

T3test	<i>Test Type III SS using error term other than MSE</i>
--------	---

Description

Hypothesis test of Type III SS using an error term other than MSE. This corresponds to SAS PROC GLM's RANDOM /TEST clause.

Usage

```
T3test(Formula, Data, Error="", eps=1e-8)
```

Arguments

Formula	a conventional formula for a linear model
Data	a data.frame to be analyzed
Error	an error term. Term name should be exactly same one listed the ANOVA output.
eps	Less than this value is considered as zero.

Details

It tests a factor of type III SS using some other term as an error term. Here the error term should not be MSE.

Value

Returns one or more ANOVA table(s) of type III SS.

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
T3test(log(CMAX) ~ SEQ/SUBJ + PRD + TRT, BEdata, "SEQ:SUBJ")
```

trimmedMean	<i>Trimmed Mean</i>
-------------	---------------------

Description

Trimmed mean wrapping mean function .

Usage

```
trimmedMean(x, Trim=0.05)
```

Arguments

- x a vector of numerics
- Trim trimming proportion. Default is 0.05

Details

It removes NA in the input vector.

Value

The value of trimmed mean

Author(s)

Kyun-Seop Bae k@acr.kr

tsum	<i>Table Summary</i>
------	----------------------

Description

Summarize a continuous dependent variable with or without independent variables.

Usage

```
tsum(Formula=NULL, Data=NULL, ColNames=NULL, MaxLevel=30, ...)
```


Arguments

Formula	a conventional formula
Data	a data.frame or a matrix
ColNames	If there is no Formula, this will be used.
MaxLevel	More than this will not be handled.
...	arguments to be passed to tsum0, tsum1, tsum2, or tsum3

Details

A convenient summarization function for a continuous variable. This is a wrapper function to tsum0, tsum1, tsum2, or tsum3.

Value

A data.frame of descriptive summarization values.

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[tsum0](#), [tsum1](#), [tsum2](#), [tsum3](#)

Examples

```
tsum(lh)
t(tsum(CO2))
t(tsum(uptake ~ Treatment, CO2))
tsum(uptake ~ Type + Treatment, CO2)
print(tsum(uptake ~ conc + Type + Treatment, CO2), digits=3)
```

tsum0	<i>Table Summary 0 independent(x) variable</i>
-------	--

Description

Summarize a continuous dependent(y) variable without any independent(x) variable.

Usage

```
tsum0(d, y, e=c("Mean", "SD", "N"), repl=list(c("length"), c("n")))
```

Arguments

d	a data.frame or matrix with colnames
y	y variable name, a continuous variable
e	a vector of summarize function names
repl	list of strings to replace after summarize. Length of list should be 2, and both should have the same length.

Details

A convenient summarization function for a continuous variable.

Value

A vector of summarized values

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[tsum](#), [tsum1](#), [tsum2](#), [tsum3](#)

Examples

```
tsum0(CO2, "uptake")
tsum0(CO2, "uptake", repl=list(c("mean", "length"), c("Mean", "n")))
```

tsum1	<i>Table Summary 1 independent(x) variable</i>
-------	--

Description

Summarize a continuous dependent(y) variable with one independent(x) variable.

Usage

```
tsum1(d, y, u, e=c("Mean", "SD", "N"), ou="", repl=list(c("length"), ("n")))
```

Arguments

- d a data.frame or matrix with colnames
- y y variable name. a continuous variable
- u x variable name, upper side variable
- e a vector of summarize function names
- ou order of levels of upper side x variable
- repl list of strings to replace after summarize. Length of list should be 2, and both should have the same length.

Details

A convenient summarization function for a continuous variable with one x variable.

Value

A data.frame of summarized values. Row names are from e names. Column names are from the levels of x variable.

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[tsum](#), [tsum0](#), [tsum2](#), [tsum3](#)

Examples

```
tsum1(CO2, "uptake", "Treatment")
tsum1(CO2, "uptake", "Treatment",
      e=c("mean", "median", "sd", "min", "max", "length"),
      ou=c("chilled", "nonchilled"),
      repl=list(c("median", "length"), c("med", "n")))
```

tsum2	<i>Table Summary 2 independent(x) variables</i>
-------	---

Description

Summarize a continuous dependent(y) variable with two independent(x) variables.

Usage

```
tsum2(d, y, l, u, e=c("Mean", "SD", "N"), h=NULL, ol="", ou="", rm.dup=TRUE,
      repl=list(c("length"), c("n")))
```

Arguments

d	a data.frame or matrix with colnames
y	y variable name. a continuous variable
l	x variable name to be shown on the left side
u	x variable name to be shown on the upper side
e	a vector of summarize function names
h	a vector of summarize function names for the horizontal subgroup. If NULL, it becomes same to e argument.
ol	order of levels of left side x variable
ou	order of levels of upper side x variable
rm.dup	if TRUE, duplicated name of levels are specified on the first occurrence only.
repl	list of strings to replace after summarize. Length of list should be 2, and both should have the same length.

Details

A convenient summarization function for a continuous variable with two x variables; one on the left side, the other on the upper side.

Value

A data.frame of summarized values. Column names are from the levels of u. Row names are basically from the levels of l.

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[tsum](#), [tsum0](#), [tsum1](#), [tsum3](#)

Examples

```
tsum2(CO2, "uptake", "Type", "Treatment")
tsum2(CO2, "uptake", "Type", "conc")
tsum2(CO2, "uptake", "Type", "Treatment",
      e=c("mean", "median", "sd", "min", "max", "length"),
      ou=c("chilled", "nonchilled"),
      repl=list(c("median", "length"), c("med", "n")))
```

tsum3	<i>Table Summary 3 independent(x) variables</i>
-------	---

Description

Summarize a continuous dependent(y) variable with three independent(x) variables.

Usage

```
tsum3(d, y, l, u, e=c("Mean", "SD", "N"), h=NULL, ol1="", ol2="", ou="",
      rm.dup=TRUE, repl=list(c("length"), c("n")))
```

Arguments

- d a data.frame or matrix with colnames
- y y variable name. a continuous variable
- l a vector of two x variable name to be shown on the left side. The length should be 2.
- u x variable name to be shown on the upper side
- e a vector of summarize function names
- h a list of two vectors of summarize function names for the first and second horizontal subgroups. If NULL, it becomes same to e argument.
- ol1 order of levels of 1st left side x variable
- ol2 order of levels of 2nd left side x variable
- ou order of levels of upper side x variable
- rm.dup if TRUE, duplicated name of levels are specified on the first occurrence only.
- repl list of strings to replace after summarize. Length of list should be 2, and both should have the same length.

Details

A convenient summarization function for a continuous variable with three x variables; two on the left side, the other on the upper side.

Value

A data.frame of summarized values. Column names are from the levels of u. Row names are basically from the levels of l.

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[tsum](#), [tsum0](#), [tsum1](#), [tsum2](#)

Examples

```
tsum3(CO2, "uptake", c("Type", "Treatment"), "conc")
tsum3(CO2, "uptake", c("Type", "Treatment"), "conc",
      e=c("mean", "median", "sd", "min", "max", "length"),
      h=list(c("mean", "sd", "length"), c("mean", "length")),
      ol2=c("chilled", "nonchilled"),
      repl=list(c("median", "length"), c("med", "n")))
```

UCL

Upper Confidence Limit

Description

The estimate of the upper bound of confidence limit using t-distribution

Usage

```
UCL(x, conf.level=0.95)
```

Arguments

x	a vector of numerics
conf.level	confidence level

Details

It removes NA in the input vector.

Value

The estimate of the upper bound of confidence limit using t-distribution

Author(s)

Kyun-Seop Bae k@acr.kr

UNIV

*Univariate Descriptive Statistics***Description**

Returns descriptive statistics of a numeric vector.

Usage

```
UNIV(x, conf.level = 0.95)
```

Arguments

<code>x</code>	a numeric vector
<code>conf.level</code>	confidence level for confidence limit

Details

A convenient and comprehensive descriptive statistics. NA is removed during the calculation. This is similar to SAS PROC UNIVARIATE.

Value

<code>nAll</code>	count of all element in the input vector
<code>nNA</code>	count of NA element
<code>nFinite</code>	count of finite numbers
<code>Mean</code>	mean excluding NA
<code>SD</code>	standard deviation excluding NA
<code>CV</code>	coefficient of variation in percent
<code>SEM</code>	standard error of the sample mean, sample mean divided by <code>nFinite</code>
<code>LowerConfLimit</code>	lower confidence limit of given confidence interval
<code>UpperConfLimit</code>	upper confidence limit of given confidence interval
<code>TrimmedMean</code>	trimmed mean with trimming 1 - confidence level
<code>Min</code>	minimum value
<code>Q1</code>	first quartile value
<code>Median</code>	median value
<code>Q3</code>	third quartile value
<code>Max</code>	maximum value
<code>Range</code>	range of finite numbers. maximum - minimum
<code>IQR</code>	inter-quartile range type 2 which is SAS default
<code>MAD</code>	mean absolute deviation
<code>Skewness</code>	skewness
<code>SkewnessSE</code>	standard error of skewness
<code>Kurtosis</code>	kurtosis
<code>KurtosisSE</code>	kurtosis
<code>GeometricMean</code>	geometric mean, calculated only when all given values are positive.
<code>GeometricCV</code>	geometric coefficient of variation in percent, calculated only when all given values are positive.

UNIV

71

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

UNIV(1h)

Index

* Descriptive Statistics

UNIV, [70](#)

* Table Summary

tsum, [64](#)

tsum0, [65](#)

tsum1, [66](#)

tsum2, [67](#)

tsum3, [68](#)

* datasets

BEdata, [8](#)

af, [4](#)

aov1, [5](#)

aov2, [6](#)

aov3, [7](#)

BEdata, [8](#)

binom.test, [58](#)

bk, [8](#)

BY, [9](#)

CIest, [10](#)

Coll, [11](#)

CONTR, [12](#), [14](#)

Cor.test, [13](#)

cSS, [12](#), [14](#)

CV, [15](#)

Diffogram, [15](#), [32](#), [44](#)

e1, [16](#)

e2, [17](#)

e3, [17](#)

EMS, [18](#)

est, [19](#), [20](#)

ESTM, [19](#), [20](#)

estmb, [21](#)

ESTMIMATE (ESTM), [20](#)

G2SWEEP, [21](#), [21](#)

geoCV, [23](#), [24](#)

geoMean, [23](#)

GLM, [24](#)

is.cor, [25](#)

Kurtosis, [26](#), [27](#)

KurtosisSE, [26](#), [26](#)

LCL, [27](#)

lfit, [22](#), [28](#), [62](#)

lr, [29](#), [52](#)

lr0, [30](#)

LSM, [16](#), [31](#), [44](#)

Max, [32](#)

Mean, [33](#)

Median, [33](#)

Min, [34](#)

ModelMatrix, [22](#), [28](#), [34](#), [62](#)

N, [35](#)

OR, [36](#), [47](#), [53](#)

ORcmh, [37](#), [38](#), [40](#), [48](#), [49](#), [54](#), [56](#)

ORinv, [37](#), [38](#), [38](#), [40](#), [48](#), [49](#), [54](#), [56](#)

ORMn, [36](#), [39](#), [41](#), [47–49](#), [51](#), [53](#), [54](#), [56](#), [57](#)

ORMn1, [36–38](#), [40](#), [40](#), [47–49](#), [51](#), [53](#), [54](#), [56](#), [57](#)

pB, [41](#)

Pcor.test, [42](#)

pD, [43](#)

PDIFF, [16](#), [19](#), [32](#), [43](#)

pResD, [45](#)

QuartileRange, [45](#)

Range, [46](#)

RD, [36](#), [46](#), [53](#)

RDinv, [37](#), [40](#), [47](#), [49](#), [54](#), [56](#)

RDmn, [36–38](#), [40](#), [41](#), [47](#), [49](#), [51](#), [53](#), [54](#), [56](#), [57](#)

RDmn1, [36–38](#), [40](#), [41](#), [47–49](#), [50](#), [53](#), [54](#), [56](#), [57](#)

REG, [51](#)

regD, [52](#)

RR, [36](#), [47](#), [53](#)

RRinv, [37](#), [38](#), [40](#), [48](#), [49](#), [54](#), [56](#)

RRmn, [36–38](#), [40](#), [41](#), [47–49](#), [51](#), [53](#), [55](#), [57](#)

RRmn1, [36–38](#), [40](#), [41](#), [47–49](#), [51](#), [53](#), [54](#), [56](#), [56](#)

sasLM (sasLM-package), [3](#)

sasLM-package, [3](#)

satt, 57
ScoreCI, 58
SD, 59
SEM, 59
Skewness, 60, 61
SkewnessSE, 60, 60
SLICE, 61
SS, 62

T3MS, 62
T3test, 63
trimmedMean, 64
tsum, 64, 66–69
tsum0, 9, 65, 65, 67–69
tsum1, 9, 65, 66, 66, 68, 69
tsum2, 9, 65–67, 67, 69
tsum3, 9, 65–68, 68

UCL, 27, 69
UNIV, 70