

Package ‘manymome’

January 8, 2026

Title Mediation, Moderation and Moderated-Mediation After Model Fitting

Version 0.3.3

Description Computes indirect effects, conditional effects, and conditional indirect effects in a structural equation model or path model after model fitting, with no need to define any user parameters or label any paths in the model syntax, using the approach presented in Cheung and Cheung (2024) <[doi:10.3758/s13428-023-02224-z](https://doi.org/10.3758/s13428-023-02224-z)>. Can also form bootstrap confidence intervals by doing bootstrapping only once and reusing the bootstrap estimates in all subsequent computations. Supports bootstrap confidence intervals for standardized (partially or completely) indirect effects, conditional effects, and conditional indirect effects as described in Cheung (2009) <[doi:10.3758/BRM.41.2.425](https://doi.org/10.3758/BRM.41.2.425)> and Cheung, Cheung, Lau, Hui, and Vong (2022) <[doi:10.1037/hea0001188](https://doi.org/10.1037/hea0001188)>. Model fitting can be done by structural equation modeling using lavaan() or regression using lm().

URL <https://sfcheung.github.io/manymome/>

BugReports <https://github.com/sfcheung/manymome/issues>

License GPL (>= 3)

Encoding UTF-8

RoxygenNote 7.3.3

Suggests knitr, rmarkdown, lavaan.mi, Amelia, mice, semPlot, semptools (>= 0.3.2), testthat (>= 3.0.0)

Config/testthat/edition 3

Config/testthat/parallel true

Config/testthat/start-first cond_indirect_*

Imports lavaan, boot, parallel, pbapply, stats, ggplot2, igraph, MASS, methods, lmhelps

Depends R (>= 3.5.0)

LazyData true

VignetteBuilder knitr

NeedsCompilation no

Author Shu Fai Cheung [aut, cre] (ORCID: <<https://orcid.org/0000-0002-9871-9448>>),
 Sing-Hang Cheung [aut] (ORCID: <<https://orcid.org/0000-0001-5182-0752>>),
 Rong Wei Sun [ctb] (ORCID: <<https://orcid.org/0000-0003-0034-1422>>)

Maintainer Shu Fai Cheung <shufai.cheung@gmail.com>

Repository CRAN

Date/Publication 2026-01-08 06:10:52 UTC

Contents

all_indirect_paths	4
check_path	6
coef.cond_indirect_diff	8
coef.cond_indirect_effects	9
coef.delta_med	10
coef.indirect	11
coef.indirect_list	12
coef.indirect_proportion	14
coef.lm_from_lavaan	15
cond_indirect	16
cond_indirect_diff	26
confint.cond_indirect_diff	28
confint.cond_indirect_effects	29
confint.delta_med	31
confint.indirect	32
confint.indirect_list	34
data_med	36
data_med_complicated	36
data_med_complicated_mg	37
data_med_mg	38
data_med_mod_a	39
data_med_mod_ab	40
data_med_mod_ab1	41
data_med_mod_b	42
data_med_mod_b_mod	43
data_med_mod_parallel	44
data_med_mod_parallel_cat	45
data_med_mod_serial	46
data_med_mod_serial_cat	47
data_med_mod_serial_parallel	48
data_med_mod_serial_parallel_cat	49
data_mod	50
data_mod2	50
data_mod_cat	51
data_mome_demo	52

data_mome_demo_missing	53
data_parallel	54
data_sem	55
data_serial	56
data_serial_parallel	57
data_serial_parallel_latent	58
delta_med	59
do_boot	62
do_mc	64
factor2var	67
fit2boot_out	68
fit2mc_out	70
get_one_cond_indirect_effect	71
get_prod	73
index_of_mome	75
indirect_effects_from_list	79
indirect_i	81
indirect_proportion	84
lm2boot_out	85
lm2list	87
lm_from_lavaan_list	89
math_indirect	90
merge_mod_levels	92
modmed_x1m3w4y1	93
mod_levels	94
plot.cond_indirect_effects	97
plot.q_mediation	101
plot_effect_vs_w	105
predict.lm_from_lavaan	110
predict.lm_from_lavaan_list	111
predict.lm_list	112
print.all_paths	113
print.boot_out	114
print.cond_indirect_diff	115
print.cond_indirect_effects	117
print.delta_med	120
print.indirect	122
print.indirect_list	125
print.indirect_proportion	127
print.lm_list	128
print.mc_out	129
pseudo_johnson_neyman	130
q_mediation	133
simple_mediation_latent	144
subsetting_cond_indirect_effects	145
subsetting_wlevels	146
summary.lm_list	147
terms.lm_from_lavaan	149

total_indirect_effect	150
Index	152

all_indirect_paths	<i>Enumerate All Indirect Effects in a Model</i>
--------------------	--

Description

Check all indirect paths in a model and return them as a list of arguments of `x`, `y`, and `m`, to be used by `indirect_effect()`.

Usage

```
all_indirect_paths(
  fit = NULL,
  exclude = NULL,
  x = NULL,
  y = NULL,
  group = NULL
)
all_paths_to_df(all_paths)
```

Arguments

<code>fit</code>	A fit object. It can be the output of <code>lavaan::lavaan()</code> or its wrapper such as <code>lavaan::sem()</code> , or a list of the output of <code>lm()</code> or the output of <code>lm2list()</code> . If it is a single model fitted by <code>lm()</code> , it will be automatically converted to a list by <code>lm2list()</code> .
<code>exclude</code>	A character vector of variables to be excluded in the search, such as control variables.
<code>x</code>	A character vector of variables that will be included as the <code>x</code> variables. If supplied, only paths that start from these variables will be included in the search. If <code>NULL</code> , the default, then all variables that are one of the predictors in at least one regression equation will be included in the search.
<code>y</code>	A character vector of variables that will be included as the <code>y</code> variables. If supplied, only paths that start from these variables will be included in the search. If <code>NULL</code> , the default, then all variables that are the outcome variables in at least one regression equation will be included in the search.
<code>group</code>	Either the group number as appeared in the <code>summary()</code> or <code>lavaan::parameterEstimates()</code> output of a <code>lavaan::lavaan</code> object, or the group label as used in the <code>lavaan::lavaan</code> object. Used only when the number of groups is greater than one. Default is <code>NULL</code> . If not specified by the model has more than one group, than paths that appears in at least one group will be included in the output.
<code>all_paths</code>	An <code>all_paths</code> -class object. For example, the output of <code>all_indirect_paths()</code> .

Details

It makes use of `igraph::all_simple_paths()` to identify paths in a model.

Multigroup Models:

Since Version 0.1.14.2, support for multigroup models has been added for models fitted by `lavaan`. If a model has more than one group and `group` is not specified, than paths in all groups will be returned. If `group` is specified, than only paths in the selected group will be returned.

Value

`all_indirect_paths()` returns a list of the class `all_paths`. Each argument is a list of three character vectors, `x`, the name of the predictor that starts a path, `y`, the name of the outcome that ends a path, and `m`, a character vector of one or more names of the mediators, from `x` to `y`. This class has a `print` method.

`all_paths_to_df()` returns a data frame with three columns, `x`, `y`, and `m`, which can be used by functions such as `indirect_effect()`.

Functions

- `all_indirect_paths()`: Enumerate all indirect paths.
- `all_paths_to_df()`: Convert the output of `all_indirect_paths()` to a data frame with three columns: `x`, `y`, and `m`.

Author(s)

Shu Fai Cheung <https://orcid.org/0000-0002-9871-9448>

See Also

`indirect_effect()`, `lm2list()`, `many_indirect_effects()`

Examples

```
library(lavaan)
data(data_serial_parallel)
mod <-
"
m11 ~ x + c1 + c2
m12 ~ m11 + x + c1 + c2
m2 ~ x + c1 + c2
y ~ m12 + m2 + m11 + x + c1 + c2
"
fit <- sem(mod, data_serial_parallel,
           fixed.x = FALSE)
# All indirect paths
out1 <- all_indirect_paths(fit)
out1
names(out1)

# Exclude c1 and c2 in the search
```

```

out2 <- all_indirect_paths(fit, exclude = c("c1", "c2"))
out2
names(out2)

# Exclude c1 and c2, and only consider paths start
# from x and end at y
out3 <- all_indirect_paths(fit, exclude = c("c1", "c2"),
                           x = "x",
                           y = "y")
out3
names(out3)

# Multigroup models

data(data_med_complicated_mg)
mod <-
"
m11 ~ x1 + x2 + c1 + c2
m12 ~ m11 + c1 + c2
m2 ~ x1 + x2 + c1 + c2
y1 ~ m11 + m12 + x1 + x2 + c1 + c2
y2 ~ m2 + x1 + x2 + c1 + c2
"
fit <- sem(mod, data_med_complicated_mg, group = "group")
summary(fit)

all_indirect_paths(fit,
                   x = "x1",
                   y = "y1")
all_indirect_paths(fit,
                   x = "x1",
                   y = "y1",
                   group = 1)
all_indirect_paths(fit,
                   x = "x1",
                   y = "y1",
                   group = "Group B")

```

check_path*Check a Path Exists in a Model*

Description

It checks whether a path, usually an indirect path, exists in a model.

Usage

```
check_path(x, y, m = NULL, fit = NULL, est = NULL)
```

Arguments

x	Character. The name of predictor at the start of the path.
y	Character. The name of the outcome variable at the end of the path.
m	A vector of the variable names of the mediators. The path goes from the first mediator successively to the last mediator. If NULL, the default, the path goes from x to y.
fit	The fit object. Currently only supports a lavaan::lavaan-class object or a list of outputs of <code>lm()</code> . It can also be a lavaan.mi object returned by <code>lavaan.mi::lavaan.mi()</code> or its wrapper, such as <code>lavaan.mi::sem.mi()</code> . If it is a single model fitted by <code>lm()</code> , it will be automatically converted to a list by <code>lm2list()</code> .
est	The output of <code>lavaan::parameterEstimates()</code> . If NULL, the default, it will be generated from fit. If supplied, fit will be ignored.

Details

It checks whether the path defined by a predictor (x), an outcome (y), and optionally a sequence of mediators (m), exists in a model. It can check models in a lavaan::lavaan-class object or a list of outputs of `lm()`. It also supports lavaan.mi objects returned by `lavaan.mi::lavaan.mi()` or its wrapper, such as `lavaan.mi::sem.mi()`.

For example, in the following model in lavaan syntax

```
m1 ~ x
m2 ~ m1
m3 ~ x
y ~ m2 + m3
```

This path is valid: x = "x", y = "y", m = c("m1", "m2")

This path is invalid: x = "x", y = "y", m = c("m2")

This path is also invalid: x = "x", y = "y", m = c("m1", "m2")

Value

A logical vector of length one. TRUE if the path is valid, FALSE if the path is invalid.

Examples

```
library(lavaan)
data(data_serial_parallel)
dat <- data_serial_parallel
mod <-
"
m11 ~ x + c1 + c2
m12 ~ m11 + x + c1 + c2
m2 ~ x + c1 + c2
y ~ m12 + m2 + m11 + x + c1 + c2
"
fit <- sem(mod, dat,
```

```

meanstructure = TRUE, fixed.x = FALSE)

# The following paths are valid
check_path(x = "x", y = "y", m = c("m11", "m12"), fit = fit)
check_path(x = "x", y = "y", m = "m2", fit = fit)
# The following paths are invalid
check_path(x = "x", y = "y", m = c("m11", "m2"), fit = fit)
check_path(x = "x", y = "y", m = c("m12", "m11"), fit = fit)

```

coef.cond_indirect_diff*Print the Output of 'cond_indirect_diff()'***Description**

Extract the change in conditional indirect effect.

Usage

```
## S3 method for class 'cond_indirect_diff'
coef(object, ...)
```

Arguments

object	The output of cond_indirect_diff() .
...	Optional arguments. Ignored.

Details

The `coef` method of the `cond_indirect_diff`-class object.

Value

Scalar: The change of conditional indirect effect in `object`.

See Also

[cond_indirect_diff\(\)](#)

coef.cond_indirect_effects

Estimates of Conditional Indirect Effects or Conditional Effects

Description

Return the estimates of the conditional indirect effects or conditional effects for all levels in the output of `cond_indirect_effects()`.

Usage

```
## S3 method for class 'cond_indirect_effects'  
coef(object, ...)
```

Arguments

object	The output of <code>cond_indirect_effects()</code> .
...	Optional arguments. Ignored by the function.

Details

It extracts and returns the column `ind` or `std` in the output of `cond_indirect_effects()`.

Value

A numeric vector: The estimates of the conditional effects or conditional indirect effects.

See Also

cond_indirect_effects()

Examples

```

out1
coef(out1)

# Conditional indirect effects from x1 through m1 and m2 to y,
out2 <- cond_indirect_effects(x = "x", y = "y", m = c("m1", "m2"),
                               wlevels = c("w1", "w4"), fit = fit)
out2
coef(out2)

# Standardized conditional indirect effects from x1 through m1 and m2 to y,
out2std <- cond_indirect_effects(x = "x", y = "y", m = c("m1", "m2"),
                                   wlevels = c("w1", "w4"), fit = fit,
                                   standardized_x = TRUE, standardized_y = TRUE)
out2std
coef(out2std)

```

coef.delta_med *Delta_Med in a 'delta_med'-Class Object*

Description

Return the estimate of Delta_Med in a 'delta_med'-class object.

Usage

```
## S3 method for class 'delta_med'
coef(object, ...)
```

Arguments

object	The output of <code>delta_med()</code> .
...	Optional arguments. Ignored.

Details

It just extracts and returns the element `delta_med` in the output of `delta_med()`, the estimate of the Delta_Med proposed by Liu, Yuan, and Li (2023), an R^2 -like measure of indirect effect.

Value

A scalar: The estimate of Delta_Med.

Author(s)

Shu Fai Cheung <https://orcid.org/0000-0002-9871-9448>

References

Liu, H., Yuan, K.-H., & Li, H. (2023). A systematic framework for defining R-squared measures in mediation analysis. *Psychological Methods*. Advance online publication. <https://doi.org/10.1037/met0000571>

See Also

[delta_med\(\)](#)

Examples

```
library(lavaan)
dat <- data_med
mod <-
"
m ~ x
y ~ m + x
"
fit <- sem(mod, dat)
dm <- delta_med(x = "x",
                  y = "y",
                  m = "m",
                  fit = fit)
dm
print(dm, full = TRUE)
coef(dm)
```

coef.indirect

Extract the Indirect Effect or Conditional Indirect Effect

Description

Return the estimate of the indirect effect in the output of [indirect_effect\(\)](#) or or the conditional indirect in the output of [cond_indirect\(\)](#).

Usage

```
## S3 method for class 'indirect'
coef(object, ...)
```

Arguments

object	The output of indirect_effect() or cond_indirect() .
...	Optional arguments. Ignored by the function.

Details

It extracts and returns the element `indirect.` in an object.

If standardized effect is requested when calling `indirect_effect()` or `cond_indirect()`, the effect returned is also standardized.

Value

A scalar: The estimate of the indirect effect or conditional indirect effect.

See Also

`indirect_effect()` and `cond_indirect()`.

Examples

```
library(lavaan)
dat <- modmed_x1m3w4y1
mod <-
"
m1 ~ x + w1 + x:w1
m2 ~ x
y ~ m1 + m2 + x
"
fit <- sem(mod, dat,
            meanstructure = TRUE, fixed.x = FALSE,
            se = "none", baseline = FALSE)
est <- parameterEstimates(fit)

# Examples for indirect_effect():

# Indirect effect from x through m2 to y
out1 <- indirect_effect(x = "x", y = "y", m = "m2", fit = fit)
out1
coef(out1)

# Conditional Indirect effect from x1 through m1 to y,
# when w1 is 1 SD above mean
hi_w1 <- mean(dat$w1) + sd(dat$w1)
out2 <- cond_indirect(x = "x", y = "y", m = "m1",
                      wvalues = c(w1 = hi_w1), fit = fit)
out2
coef(out2)
```

`coef.indirect_list` *Extract the Indirect Effects from a 'indirect_list' Object*

Description

Return the estimates of the indirect effects in the output of `many_indirect_effects()`.

Usage

```
## S3 method for class 'indirect_list'
coef(object, ...)
```

Arguments

object	The output of many_indirect_effects() .
...	Optional arguments. Ignored by the function.

Details

It extracts the estimates in each 'indirect'-class object in the list.

If standardized effect is requested when calling [many_indirect_effects\(\)](#), the effects returned are also standardized.

Value

A numeric vector of the indirect effects.

See Also

[many_indirect_effects\(\)](#)

Examples

```
library(lavaan)
data(data_serial_parallel)
mod <-
"
m11 ~ x + c1 + c2
m12 ~ m11 + x + c1 + c2
m2 ~ x + c1 + c2
y ~ m12 + m2 + m11 + x + c1 + c2
"
fit <- sem(mod, data_serial_parallel,
           fixed.x = FALSE)
# All indirect paths from x to y
paths <- all_indirect_paths(fit,
                           x = "x",
                           y = "y")
paths
# Indirect effect estimates
out <- many_indirect_effects(paths,
                             fit = fit)
out
coef(out)
```

coef.indirect_proportion*Extract the Proportion of Effect Mediated*

Description

Return the proportion of effect mediated in the output of [indirect_proportion\(\)](#).

Usage

```
## S3 method for class 'indirect_proportion'
coef(object, ...)
```

Arguments

object	The output of indirect_proportion()
...	Not used.

Details

It extracts and returns the element proportion in the input object.

Value

A scalar: The proportion of effect mediated.

See Also

[indirect_proportion\(\)](#)

Examples

```
library(lavaan)
dat <- data_med
head(dat)
mod <-
"
m ~ x + c1 + c2
y ~ m + x + c1 + c2
"
fit <- sem(mod, dat, fixed.x = FALSE)
out <- indirect_proportion(x = "x",
                           y = "y",
                           m = "m",
                           fit = fit)
out
coef(out)
```

coef.lm_from_lavaan *Coefficients of an 'lm_from_lavaan'-Class Object*

Description

Returns the path coefficients of the terms in an lm_from_lavaan-class object.

Usage

```
## S3 method for class 'lm_from_lavaan'
coef(object, ...)
```

Arguments

object	A 'lm_from_lavaan'-class object.
...	Additional arguments. Ignored.

Details

An lm_from_lavaan-class object converts a regression model for a variable in a lavaan-class object to a formula-class object. This function simply extracts the path coefficients estimates. Intercept is always included, and set to zero if mean structure is not in the source lavaan-class object.

This is an advanced helper used by [plot.cond_indirect_effects\(\)](#). Exported for advanced users and developers.

Value

A numeric vector of the path coefficients.

See Also

[lm_from_lavaan_list\(\)](#)

Examples

```
library(lavaan)
data(data_med)
mod <-
"
m ~ a * x + c1 + c2
y ~ b * m + x + c1 + c2
"
fit <- sem(mod, data_med, fixed.x = FALSE)
fit_list <- lm_from_lavaan_list(fit)
coef(fit_list$m)
coef(fit_list$y)
```

 cond_indirect *Conditional, Indirect, and Conditional Indirect Effects*

Description

Compute the conditional effects, indirect effects, or conditional indirect effects in a structural model fitted by `lm()`, `lavaan::sem()`, or `lavaan.mi::sem.mi()`.

Usage

```
cond_indirect(
  x,
  y,
  m = NULL,
  fit = NULL,
  est = NULL,
  implied_stats = NULL,
  wvalues = NULL,
  standardized_x = FALSE,
  standardized_y = FALSE,
  boot_ci = FALSE,
  level = 0.95,
  boot_out = NULL,
  R = 100,
  seed = NULL,
  parallel = TRUE,
  ncores = max(parallel::detectCores(logical = FALSE) - 1, 1),
  make_cluster_args = list(),
  progress = TRUE,
  save_boot_full = FALSE,
  prods = NULL,
  get_prods_only = FALSE,
  save_boot_out = TRUE,
  mc_ci = FALSE,
  mc_out = NULL,
  save_mc_full = FALSE,
  save_mc_out = TRUE,
  ci_out = NULL,
  save_ci_full = FALSE,
  save_ci_out = TRUE,
  ci_type = NULL,
  group = NULL,
  boot_type = c("perc", "bc"),
  skip_indicators = TRUE,
  internal_options = list()
)
```

```
cond_indirect_effects(  
  wlevels,  
  x,  
  y,  
  m = NULL,  
  fit = NULL,  
  w_type = "auto",  
  w_method = "sd",  
  sd_from_mean = NULL,  
  percentiles = NULL,  
  est = NULL,  
  implied_stats = NULL,  
  boot_ci = FALSE,  
  R = 100,  
  seed = NULL,  
  parallel = TRUE,  
  ncores = max(parallel::detectCores(logical = FALSE) - 1, 1),  
  make_cluster_args = list(),  
  progress = TRUE,  
  boot_out = NULL,  
  output_type = "data.frame",  
  mod_levels_list_args = list(),  
  mc_ci = FALSE,  
  mc_out = NULL,  
  ci_out = NULL,  
  ci_type = NULL,  
  boot_type = c("perc", "bc"),  
  groups = NULL,  
  ...  
)  
  
indirect_effect(  
  x,  
  y,  
  m = NULL,  
  fit = NULL,  
  est = NULL,  
  implied_stats = NULL,  
  standardized_x = FALSE,  
  standardized_y = FALSE,  
  boot_ci = FALSE,  
  level = 0.95,  
  boot_out = NULL,  
  R = 100,  
  seed = NULL,  
  parallel = TRUE,  
  ncores = max(parallel::detectCores(logical = FALSE) - 1, 1),  
  make_cluster_args = list(),
```

```

progress = TRUE,
save_boot_full = FALSE,
save_boot_out = TRUE,
mc_ci = FALSE,
mc_out = NULL,
save_mc_full = FALSE,
save_mc_out = TRUE,
ci_out = NULL,
save_ci_full = FALSE,
save_ci_out = TRUE,
ci_type = NULL,
boot_type = c("perc", "bc"),
group = NULL,
skip_indicators = TRUE,
internal_options = list()
)

cond_effects(
  wlevels,
  x,
  y,
  m = NULL,
  fit = NULL,
  w_type = "auto",
  w_method = "sd",
  sd_from_mean = NULL,
  percentiles = NULL,
  est = NULL,
  implied_stats = NULL,
  boot_ci = FALSE,
  R = 100,
  seed = NULL,
  parallel = TRUE,
  ncores = max(parallel::detectCores(logical = FALSE) - 1, 1),
  make_cluster_args = list(),
  progress = TRUE,
  boot_out = NULL,
  output_type = "data.frame",
  mod_levels_list_args = list(),
  mc_ci = FALSE,
  mc_out = NULL,
  ci_out = NULL,
  ci_type = NULL,
  boot_type = c("perc", "bc"),
  groups = NULL,
  ...
)

```

```
many_indirect_effects(paths, ...)
```

Arguments

x	Character. The name of the predictor at the start of the path.
y	Character. The name of the outcome variable at the end of the path. If the model has only one outcome variable (e.g., moderation only and no mediator), then this argument can be omitted.
m	A vector of the variable names of the mediator(s). The path goes from the first mediator successively to the last mediator. If NULL, the default, the path goes from x to y.
fit	The fit object. Can be a <code>lavaan::lavaan</code> object or a list of <code>lm()</code> outputs. It can also be a <code>lavaan.mi</code> object returned by <code>lavaan.mi::lavaan.mi()</code> or its wrapper, such as <code>lavaan.mi::sem.mi()</code> . If it is a single model fitted by <code>lm()</code> , it will be automatically converted to a list by <code>lm2list()</code> .
est	The output of <code>lavaan:::parameterEstimates()</code> . If NULL, the default, it will be generated from fit. If supplied, fit will be ignored.
implied_stats	Implied means, variances, and covariances of observed variables, of the form of the output of <code>lavaan:::lavInspect()</code> with what set to "implied". The standard deviations are extracted from this object for standardization. Default is NULL, and implied statistics will be computed from fit if required.
wvalues	A numeric vector of named elements. The names are the variable names of the moderators, and the values are the values to which the moderators will be set to. Default is NULL.
standardized_x	Logical. Whether x will be standardized. Default is FALSE. For multigroup models, model implied standard deviation for the selected group will be used.
standardized_y	Logical. Whether y will be standardized. Default is FALSE. For multigroup models, model implied standard deviation for the selected group will be used.
boot_ci	Logical. Whether bootstrap confidence interval will be formed. Default is FALSE.
level	The level of confidence for the bootstrap confidence interval. Default is .95.
boot_out	If boot_ci is TRUE, users can supply pregenerated bootstrap estimates. This can be the output of <code>do_boot()</code> . For <code>indirect_effect()</code> and <code>cond_indirect_effects()</code> , this can be the output of a previous call to <code>cond_indirect_effects()</code> , <code>indirect_effect()</code> , or <code>cond_indirect()</code> with bootstrap confidence intervals requested. These stored estimates will be reused such that there is no need to do bootstrapping again. If not supplied, the function will try to generate them from fit.
R	Integer. If boot_ci is TRUE, boot_out is NULL, and bootstrap standard errors not requested if fit is a <code>lavaan::lavaan</code> object, this function will do bootstrapping on fit. R is the number of bootstrap samples. Default is 100. For Monte Carlo simulation, this is the number of replications.
seed	If bootstrapping or Monte Carlo simulation is conducted, this is the seed for the bootstrapping or simulation. Default is NULL and seed is not set.

parallel	Logical. If bootstrapping is conducted, whether parallel processing will be used. Default is TRUE. If fit is a list of <code>lm()</code> outputs, parallel processing will not be used.
ncores	Integer. The number of CPU cores to use when parallel is TRUE. Default is the number of non-logical cores minus one (one minimum). Will raise an error if greater than the number of cores detected by <code>parallel::detectCores()</code> . If ncores is set, it will override <code>make_cluster_args</code> in <code>do_boot()</code> .
make_cluster_args	A named list of additional arguments to be passed to <code>parallel::makeCluster()</code> . For advanced users. See <code>parallel::makeCluster()</code> for details. Default is <code>list()</code> .
progress	Logical. Display bootstrapping progress or not. Default is TRUE.
save_boot_full	If TRUE, full bootstrapping results will be stored. Default is FALSE.
prods	The product terms found. For internal use.
get_prods_only	IF TRUE, will quit early and return the product terms found. The results can be passed to the prod argument when calling this function. Default is FALSE. This function is for internal use.
save_boot_out	If boot_out is supplied, whether it will be saved in the output. Default is TRUE.
mc_ci	Logical. Whether Monte Carlo confidence interval will be formed. Default is FALSE.
mc_out	If mc_ci is TRUE, users can supply pregenerated Monte Carlo estimates. This can be the output of <code>do_mc()</code> . For <code>indirect_effect()</code> and <code>cond_indirect_effects()</code> , this can be the output of a previous call to <code>cond_indirect_effects()</code> , <code>indirect_effect()</code> , or <code>cond_indirect()</code> with Monte Carlo confidence intervals requested. These stored estimates will be reused such that there is no need to do Monte Carlo simulation again. If not supplied, the function will try to generate them from fit.
save_mc_full	If TRUE, full Monte Carlo results will be stored. Default is FALSE.
save_mc_out	If mc_out is supplied, whether it will be saved in the output. Default is TRUE.
ci_out	If ci_type is supplied, this is the corresponding argument. If ci_type is "boot", this argument will be used as boot_out. If ci_type is "mc", this argument will be used as mc_out.
save_ci_full	If TRUE, full bootstrapping or Monte Carlo results will be stored. Default is FALSE.
save_ci_out	If either mc_out or boot_out is supplied, whether it will be saved in the output. Default is TRUE.
ci_type	The type of confidence intervals to be formed. Can be either "boot" (bootstrapping) or "mc" (Monte Carlo). If not supplied or is NULL, will check other arguments (e.g, boot_ci and mc_ci). If supplied, will override boot_ci and mc_ci.
group	Either the group number as appeared in the <code>summary()</code> or <code>lavaan::parameterEstimates()</code> output of a <code>lavaan::lavaan</code> object, or the group label as used in the <code>lavaan::lavaan</code> object. Used only when the number of groups is greater than one. Default is NULL.

boot_type	If bootstrap confidence interval is to be formed, the type of bootstrap confidence interval. The supported types are "perc" (percentile bootstrap confidence interval, the default and recommended type) and "bc" (bias-corrected, or BC, bootstrap confidence interval).
skip_indicators	Whether observed indicators are skipped from the search for product terms. Default is TRUE.
internal_options	A named list of internal options. For advanced options.
wlevels	The output of merge_mod_levels() , or the moderator(s) to be passed to mod_levels_list() . If all the moderators can be represented by one variable, that is, each moderator is (a) a numeric variable, (b) a dichotomous categorical variable, or (c) a factor or string variable used in lm() in fit, then it is a vector of the names of the moderators as appeared in the data frame. If at least one of the moderators is a categorical variable represented by more than one variable, such as user-created dummy variables used in lavaan::sem() , then it must be a list of the names of the moderators, with such moderators represented by a vector of names. For example: list("w1", c("gpgp2", "gpgp3"), the first moderator w1 and the second moderator a three-categorical variable represented by gpgp2 and gpgp3.
w_type	Character. Whether the moderator is a "numeric" variable or a "categorical" variable. If "auto", the function will try to determine the type automatically. See mod_levels_list() for further information.
w_method	Character, either "sd" or "percentile". If "sd", the levels are defined by the distance from the mean in terms of standard deviation. If "percentile", the levels are defined in percentiles. See mod_levels_list() for further information.
sd_from_mean	A numeric vector. Specify the distance in standard deviation from the mean for each level. Default is c(-1, 0, 1) when there is only one moderator, and c(-1, 1) when there are more than one moderator. Ignored if w_method is not equal to "sd". See mod_levels_list() for further information.
percentiles	A numeric vector. Specify the percentile (in proportion) for each level. Default is c(.16, .50, .84) if there is one moderator, and c(.16, .84) when there are more than one moderator. Ignored if w_method is not equal to "percentile". See mod_levels_list() for further information.
output_type	The type of output of cond_indirect_effects() . If "data.frame", the default, the output will be converted to a data frame. If any other values, the output is a list of the outputs from cond_indirect() .
mod_levels_list_args	Additional arguments to be passed to mod_levels_list() if it is called for creating the levels of moderators. Default is list().
groups	Either a vector of group numbers as appeared in the summary() or lavaan::parameterEstimates() output of a lavaan::lavaan object, or a vector of group labels as used in the lavaan::lavaan object. Used only when the number of groups is greater than one. Default is NULL.
...	For many_indirect_effects() , these are arguments to be passed to indirect_effect() .
paths	The output of all_indirect_paths()

Details

For a model with a mediation path moderated by one or more moderators, `cond_indirect_effects()` can be used to compute the conditional indirect effect from one variable to another variable, at one or more set of selected value(s) of the moderator(s).

If only the effect for one set of value(s) of the moderator(s) is needed, `cond_indirect()` can be used.

If only the mediator(s) is/are specified (`m`) and no values of moderator(s) are specified, then the indirect effect from one variable (`x`) to another variable (`y`) is computed. A convenient wrapper `indirect_effect()` can be used to compute the indirect effect.

If only the value(s) of moderator(s) is/are specified (`wvalues` or `wlevels`) and no mediators (`m`) are specified when calling `cond_indirect_effects()` or `cond_indirect()`, then the conditional direct effects from one variable to another are computed.

All three functions support using nonparametric bootstrapping (for `lavaan` or `lm` outputs) or Monte Carlo simulation (for `lavaan` outputs only) to form confidence intervals. Bootstrapping or Monte Carlo simulation only needs to be done once. These are the possible ways to form bootstrapping:

1. Do bootstrapping or Monte Carlo simulation in the first call to one of these functions, by setting `boot_ci` or `mc_ci` to `TRUE` and `R` to the number of bootstrap samples or replications, `level` to the level of confidence (default `.95` or `95%`), and `seed` to reproduce the results (`parallel` and `ncores` are optional for bootstrapping). This will take some time to run for bootstrapping. The output will have all bootstrap or Monte Carlo estimates stored. This output, whether it is from `indirect_effect()`, `cond_indirect_effects()`, or `cond_indirect()`, can be reused by any of these three functions by setting `boot_out` (for bootstrapping) or `mc_out` (for Monte Carlo simulation) to this output. They will form the confidence intervals using the stored bootstrap or Monte Carlo estimates.
2. Do bootstrapping using `do_boot()` or Monte Carlo simulation using `do_mc()`. The output can be used in the `boot_out` (for bootstrapping) or `mc_out` (for Monte Carlo simulation) argument of `indirect_effect()`, `cond_indirect_effects()` and `cond_indirect()`.
3. For bootstrapping, if `lavaan::sem()` is used to fit a model and `se = "boot"` is used, `do_boot()` can extract them to generate a `boot_out`-class object that again can be used in the `boot_out` argument.

If `boot_out` or `mc_out` is set, arguments such as `R`, `seed`, and `parallel` will be ignored.

Multigroup Models:

Since Version 0.1.14.2, support for multigroup models has been added for models fitted by `lavaan`. Both bootstrapping and Monte Carlo confidence intervals are supported. When used on a multigroup model:

- For `cond_indirect()` and `indirect_effect()`, users need to specify the `group` argument (by number or label). When using `cond_indirect_effects()`, if `group` is not set, all groups will be used and the indirect effect in each group will be computed, kind of treating group as a moderator.
- For `many_indirect_effects()`, the paths can be generated from a multigroup models.
- Currently, `cond_indirect_effects()` does not support a multigroup model with moderators on the path selected. The function `cond_indirect()` does not have this limitation but users need to manually specify the desired value of the moderator(s).

many_indirect_effects():

If bootstrapping or Monte Carlo confidence intervals are requested, it is advised to use `do_boot()` first to simulate the estimates. Nevertheless, In Version 0.1.14.9 and later versions, if `boot_ci` or `mc_ci` is TRUE when calling `many_indirect_effects()` but `boot_out` or `mc_out` is not set, bootstrapping or simulation will be done only once, and then the bootstrapping or simulated estimates will be used for all paths. This prevents accidentally repeating the process once for each direct path.

Value

`indirect_effect()` and `cond_indirect()` return an `indirect`-class object.

`cond_indirect_effects()` returns a `cond_indirect_effects`-class object.

These two classes of objects have their own print methods for printing the results (see `print.indirect()` and `print.cond_indirect_effects()`). They also have a `coef` method for extracting the estimates (`coef.indirect()` and `coef.cond_indirect_effects()`) and a `confint` method for extracting the confidence intervals (`confint.indirect()` and `confint.cond_indirect_effects()`). Addition and subtraction can also be conducted on `indirect`-class object to estimate and test a function of effects (see `math.indirect`)

Functions

- `cond_indirect()`: Compute conditional, indirect, or conditional indirect effects for one set of levels.
- `cond_indirect_effects()`: Compute the conditional effects or conditional indirect effects for several sets of levels of the moderator(s).
- `indirect_effect()`: Compute the indirect effect. A wrapper of `cond_indirect()`. Can be used when there is no moderator.
- `cond_effects()`: Just an alias to `cond_indirect_effects()`, a better name when a path has no moderator.
- `many_indirect_effects()`: Compute the indirect effects along more than one paths. It call `indirect_effect()` once for each of the path.

See Also

`mod_levels()` and `merge_mod_levels()` for generating levels of moderators. `do_boot` for doing bootstrapping before calling these functions.

Examples

```
library(lavaan)
dat <- modmed_x1m3w4y1
mod <-
"
m1 ~ a1 * x + d1 * w1 + e1 * x:w1
m2 ~ a2 * x
y ~ b1 * m1 + b2 * m2 + cp * x
"
fit <- sem(mod, dat, meanstructure = TRUE, fixed.x = FALSE, se = "none", baseline = FALSE)
```

```

est <- parameterEstimates(fit)
hi_w1 <- mean(dat$w1) + sd(dat$w1)

# Examples for cond_indirect():

# Conditional effect from x to m1 when w1 is 1 SD above mean
cond_indirect(x = "x", y = "m1",
               wvalues = c(w1 = hi_w1), fit = fit)

# Direct effect from x to y (direct because no 'm' variables)
indirect_effect(x = "x", y = "y", fit = fit)

# Conditional Indirect effect from x1 through m1 to y, when w1 is 1 SD above mean
cond_indirect(x = "x", y = "y", m = "m1",
               wvalues = c(w1 = hi_w1), fit = fit)

# Examples for cond_indirect_effects():

# Create levels of w1, the moderators
w1levels <- mod_levels("w1", fit = fit)
w1levels

# Conditional effects from x to m1 when w1 is equal to each of the levels
cond_indirect_effects(x = "x", y = "m1",
                      wlevels = w1levels, fit = fit)

# Conditional Indirect effect from x1 through m1 to y,
# when w1 is equal to each of the levels
cond_indirect_effects(x = "x", y = "y", m = "m1",
                      wlevels = w1levels, fit = fit)

# Multigroup models for cond_indirect_effects()

dat <- data_med_mg
mod <-
"
m ~ x + c1 + c2
y ~ m + x + c1 + c2
"
fit <- sem(mod, dat, meanstructure = TRUE, fixed.x = FALSE, se = "none", baseline = FALSE,
           group = "group")

# If a model has more than one group,
# it will be used as a 'moderator'.
cond_indirect_effects(x = "x", y = "y", m = "m",
                      fit = fit)

# Multigroup model for indirect_effect()

dat <- data_med_mg

```

```

mod <-
"
m ~ x + c1 + c2
y ~ m + x + c1 + c2
"
fit <- sem(mod, dat, meanstructure = TRUE, fixed.x = FALSE, se = "none", baseline = FALSE,
           group = "group")

# If a model has more than one group,
# the argument 'group' must be set.
ind1 <- indirect_effect(x = "x",
                        y = "y",
                        m = "m",
                        fit = fit,
                        group = "Group A")
ind1
ind2 <- indirect_effect(x = "x",
                        y = "y",
                        m = "m",
                        fit = fit,
                        group = 2)
ind2

# Examples for many_indirect_effects():

library(lavaan)
data(data_serial_parallel)
mod <-
"
m11 ~ x + c1 + c2
m12 ~ m11 + x + c1 + c2
m2 ~ x + c1 + c2
y ~ m12 + m2 + m11 + x + c1 + c2
"
fit <- sem(mod, data_serial_parallel,
           fixed.x = FALSE)
# All indirect paths from x to y
paths <- all_indirect_paths(fit,
                           x = "x",
                           y = "y")
paths
# Indirect effect estimates
out <- many_indirect_effects(paths,
                             fit = fit)
out

# Multigroup models for many_indirect_effects()

data(data_med_complicated_mg)
mod <-
"
m11 ~ x1 + x2 + c1 + c2

```

```

m12 ~ m11 + c1 + c2
m2 ~ x1 + x2 + c1 + c2
y1 ~ m11 + m12 + x1 + x2 + c1 + c2
y2 ~ m2 + x1 + x2 + c1 + c2
"
fit <- sem(mod, data_med_complicated_mg, group = "group")
summary(fit)

paths <- all_indirect_paths(fit,
                           x = "x1",
                           y = "y1")
paths
# Indirect effect estimates for all paths in all groups
out <- many_indirect_effects(paths,
                             fit = fit)
out

```

cond_indirect_diff *Differences In Conditional Indirect Effects*

Description

Compute the difference in conditional indirect effects between two sets of levels of the moderators.

Usage

```
cond_indirect_diff(output, from = NULL, to = NULL, level = 0.95)
```

Arguments

output	A cond_indirect_effects-class object: The output of cond_indirect_effects() .
from	A row number of output.
to	A row number of output. The change in indirect effects is computed by the change in the level(s) of the moderator(s) from Row from to Row to.
level	The level of confidence for the confidence interval. Default is .95.

Details

This function takes the output of [cond_indirect_effects\(\)](#) and computes the difference in conditional indirect effects between any two rows, that is, between levels of the moderator, or two sets of levels of the moderators when the path has more than one moderator.

The difference is meaningful when the difference between the two levels or sets of levels are meaningful. For example, if the two levels are the mean of the moderator and one standard deviation above mean of the moderator, then this difference is the change in indirect effect when the moderator increases by one standard deviation.

If the two levels are 0 and 1, then this difference is the index of moderated mediation as proposed by Hayes (2015). (This index can also be computed directly by [index_of_mome\(\)](#), designed specifically for this purpose.)

The function can also compute the change in the standardized indirect effect between two levels of a moderator or two sets of levels of the moderators.

This function is intended to be a general purpose function that allows users to compute the difference between any two levels or sets of levels that are meaningful in a context.

This function itself does not set the levels of comparison. The levels to be compared need to be set when calling [cond_indirect_effects\(\)](#). This function extracts required information from the output of [cond_indirect_effects\(\)](#).

If bootstrap or Monte Carlo estimates are available in the input or bootstrap or Monte Carlo confidence intervals are requested in calling [cond_indirect_effects\(\)](#), [cond_indirect_diff\(\)](#) will also form the bootstrap confidence interval for the difference in conditional indirect effects using the stored estimates.

If bootstrap confidence interval is to be formed and both effects used the same type of interval, then that type will be used. Otherwise, percentile confidence interval will be formed.

Value

A cond_indirect_diff-class object. This class has a print method ([print.cond_indirect_diff\(\)](#)), a coef method ([coef.cond_indirect_diff\(\)](#)), and a confint method ([confint.cond_indirect_diff\(\)](#)).

Functions

- [cond_indirect_diff\(\)](#): Compute the difference in in conditional indirect effect between two rows in the output of [cond_indirect_effects\(\)](#).

References

Hayes, A. F. (2015). An index and test of linear moderated mediation. *Multivariate Behavioral Research*, 50(1), 1-22. doi:10.1080/00273171.2014.962683

See Also

[index_of_mome\(\)](#) for computing the index of moderated mediation, [index_of_momome\(\)](#) for computing the index of moderated moderated mediation, [cond_indirect_effects\(\)](#), [mod_levels\(\)](#), and [merge_mod_levels\(\)](#) for preparing the levels to be compared.

Examples

```
library(lavaan)
dat <- modmed_x1m3w4y1
dat$xw1 <- dat$x * dat$w1
mod <-
"
m1 ~ a * x + f * w1 + d * xw1
y ~ b * m1 + cp * x
"
fit <- sem(mod, dat,
```

```

meanstructure = TRUE, fixed.x = FALSE,
se = "none", baseline = FALSE)
est <- parameterEstimates(fit)

# Create levels of w1, the moderators
w1levels <- mod_levels("w1", fit = fit)
w1levels

# Conditional effects from x to y when w1 is equal to each of the levels
boot_out <- fit2boot_out_do_boot(fit, R = 40, seed = 4314, progress = FALSE)
out <- cond_indirect_effects(x = "x", y = "y", m = "m1",
                             wlevels = w1levels, fit = fit,
                             boot_ci = TRUE, boot_out = boot_out)
out
out_ind <- cond_indirect_diff(out, from = 2, to = 1)
out_ind
coef(out_ind)
confint(out_ind)

```

confint.cond_indirect_diff

Confidence Interval of the Output of 'cond_indirect_diff()'

Description

Extract the confidence interval the output of [cond_indirect_diff\(\)](#).

Usage

```
## S3 method for class 'cond_indirect_diff'
confint(object, parm, level = 0.95, ...)
```

Arguments

object	The output of cond_indirect_diff() .
parm	Ignored.
level	The level of confidence for the confidence interval. Default is .95. Must match the level of the stored confidence interval.
...	Optional arguments. Ignored.

Details

The `confint` method of the `cond_indirect_diff`-class object.

The type of confidence intervals depends on the call used to create the object. This function merely extracts the stored confidence intervals.

Value

A one-row-two-column data frame of the confidence limits. If confidence interval is not available, the limits are NAs.

`confint.cond_indirect_effects`

Confidence Intervals of Indirect Effects or Conditional Indirect Effects

Description

Return the confidence intervals of the conditional indirect effects or conditional effects in the output of `cond_indirect_effects()`.

Usage

```
## S3 method for class 'cond_indirect_effects'
confint(object, parm, level = 0.95, ...)
```

Arguments

<code>object</code>	The output of <code>cond_indirect_effects()</code> .
<code>parm</code>	Ignored. Always returns the confidence intervals of the effects for all levels stored.
<code>level</code>	The level of confidence, default is .95, returning the 95% confidence interval. Ignored for now and will use the level of the stored intervals.
<code>...</code>	Additional arguments. Ignored by the function.

Details

It extracts and returns the columns for confidence intervals, if available.

The type of confidence intervals depends on the call used to compute the effects. If confidence intervals have already been formed (e.g., by bootstrapping or Monte Carlo), then this function merely retrieves the confidence intervals stored.

If the following conditions are met, the stored standard errors, if available, will be used to test an effect and form its confidence interval:

- Confidence intervals have not been formed (e.g., by bootstrapping or Monte Carlo).
- The path has no mediators.
- The model has only one group.
- The path is moderated by one or more moderator.
- Both the x-variable and the y-variable are not standardized.

If the model is fitted by OLS regression (e.g., using `stats::lm()`), then the variance-covariance matrix of the coefficient estimates will be used, and confidence intervals are computed from the t statistic.

If the model is fitted by structural equation modeling using lavaan, then the variance-covariance computed by lavaan will be used, and confidence intervals are computed from the z statistic.

Caution:

If the model is fitted by structural equation modeling and has moderators, the standard errors, p -values, and confidence interval computed from the variance-covariance matrices for conditional effects can only be trusted if all covariances involving the product terms are free. If any of them are fixed, for example, fixed to zero, it is possible that the model is not invariant to linear transformation of the variables.

Value

A data frame with two columns, one for each confidence limit of the confidence intervals. The number of rows is equal to the number of rows of object.

See Also

cond_indirect_effects()

Examples

```
confint(out1)
```

confint.delta_med	<i>Confidence Interval for Delta_Med in a 'delta_med'-Class Object</i>
-------------------	--

Description

Return the confidence interval of the Delta_Med in the output of [delta_med\(\)](#).

Usage

```
## S3 method for class 'delta_med'  
confint(object, parm, level = NULL, boot_type, ...)
```

Arguments

object	The output of delta_med() .
parm	Not used because only one parameter, the Delta_Med, is allowed.
level	The level of confidence, default is NULL and the level used when the object was created will be used.
boot_type	If bootstrap confidence interval is to be formed, the type of bootstrap confidence interval. The supported types are "perc" (percentile bootstrap confidence interval, the recommended method) and "bc" (bias-corrected, or BC, bootstrap confidence interval). If not supplied, the stored boot_type will be used.
...	Optional arguments. Ignored.

Details

It returns the nonparametric bootstrap percentile confidence interval of Delta_Med, proposed by Liu, Yuan, and Li (2023). The object must be the output of [delta_med\(\)](#), with bootstrap confidence interval requested when calling [delta_med\(\)](#). However, the level of confidence can be different from that used when call [delta_med\(\)](#).

Value

A one-row matrix of the confidence interval. All values are NA if bootstrap confidence interval was not requested when calling [delta_med\(\)](#).

Author(s)

Shu Fai Cheung <https://orcid.org/0000-0002-9871-9448>

See Also

[delta_med\(\)](#)

Examples

```

library(lavaan)
dat <- data_med
mod <-
"
m ~ x
y ~ m + x
"
fit <- sem(mod, dat)

# Call do_boot() to generate
# bootstrap estimates
# Use 2000 or even 5000 for R in real studies
# Set parallel to TRUE in real studies for faster bootstrapping
boot_out <- do_boot(fit,
                      R = 45,
                      seed = 879,
                      parallel = FALSE,
                      progress = FALSE)
# Remove 'progress = FALSE' in practice
dm_boot <- delta_med(x = "x",
                      y = "y",
                      m = "m",
                      fit = fit,
                      boot_out = boot_out,
                      progress = FALSE)
dm_boot
confint(dm_boot)

```

confint.indirect *Confidence Interval of Indirect Effect or Conditional Indirect Effect*

Description

Return the confidence interval of the indirect effect or conditional indirect effect stored in the output of [indirect_effect\(\)](#) or [cond_indirect\(\)](#).

Usage

```
## S3 method for class 'indirect'
confint(object, parm, level = 0.95, boot_type, ...)
```

Arguments

object	The output of indirect_effect() or cond_indirect() .
parm	Ignored because the stored object always has only one parameter.
level	The level of confidence, default is .95, returning the 95% confidence interval.

boot_type	If bootstrap confidence interval is to be formed, the type of bootstrap confidence interval. The supported types are "perc" (percentile bootstrap confidence interval, the recommended method) and "bc" (bias-corrected, or BC, bootstrap confidence interval). If not supplied, the stored boot_type will be used.
...	Additional arguments. Ignored by the function.

Details

It extracts and returns the stored confidence interval if available.

The type of confidence interval depends on the call used to compute the effect. This function merely retrieves the stored estimates, which could be generated by nonparametric bootstrapping, Monte Carlo simulation, or other methods to be supported in the future, and uses them to form the percentile confidence interval.

If the following conditions are met, the stored standard errors, if available, will be used test an effect and form it confidence interval:

- Confidence intervals have not been formed (e.g., by bootstrapping or Monte Carlo).
- The path has no mediators.
- The model has only one group.
- The path is moderated by one or more moderator.
- Both the x-variable and the y-variable are not standardized.

If the model is fitted by OLS regression (e.g., using `stats::lm()`), then the variance-covariance matrix of the coefficient estimates will be used, and confidence intervals are computed from the t statistic.

If the model is fitted by structural equation modeling using lavaan, then the variance-covariance computed by lavaan will be used, and confidence intervals are computed from the z statistic.

Caution:

If the model is fitted by structural equation modeling and has moderators, the standard errors, p -values, and confidence interval computed from the variance-covariance matrices for conditional effects can only be trusted if all covariances involving the product terms are free. If any of them are fixed, for example, fixed to zero, it is possible that the model is not invariant to linear transformation of the variables.

Value

A numeric vector of two elements, the limits of the confidence interval.

See Also

`indirect_effect()` and `cond_indirect()`

Examples

```
dat <- modmed_x1m3w4y1

# Indirect Effect

library(lavaan)
mod1 <-
"
m1 ~ x
m2 ~ m1
y ~ m2 + x
"
fit <- sem(mod1, dat,
            meanstructure = TRUE, fixed.x = FALSE,
            se = "none", baseline = FALSE)
# R should be at least 2000 or 5000 in real research.
out1 <- indirect_effect(x = "x", y = "y",
                         m = c("m1", "m2"),
                         fit = fit,
                         boot_ci = TRUE, R = 45, seed = 54151,
                         parallel = FALSE,
                         progress = FALSE)
out1
confint(out1)
```

confint.indirect_list *Confidence Intervals of Indirect Effects in an 'indirect_list' Object*

Description

Return the confidence intervals of the indirect effects stored in the output of [many_indirect_effects\(\)](#).

Usage

```
## S3 method for class 'indirect_list'
confint(object, parm = NULL, level = 0.95, ...)
```

Arguments

<code>object</code>	The output of many_indirect_effects() .
<code>parm</code>	Ignored for now.
<code>level</code>	The level of confidence, default is .95, returning the 95% confidence interval.
<code>...</code>	Additional arguments. Ignored by the function.

Details

It extracts and returns the stored confidence interval if available.

The type of confidence intervals depends on the call used to compute the effects. This function merely retrieves the stored estimates, which could be generated by nonparametric bootstrapping, Monte Carlo simulation, or other methods to be supported in the future, and uses them to form the percentile confidence interval.

Value

A two-column data frame. The columns are the limits of the confidence intervals.

See Also

many_indirect_effects()

Examples

```

library(lavaan)
data(data_serial_parallel)
mod <-
  "
m11 ~ x + c1 + c2
m12 ~ m11 + x + c1 + c2
m2 ~ x + c1 + c2
y ~ m12 + m2 + m11 + x + c1 + c2
"
fit <- sem(mod, data_serial_parallel,
            fixed.x = FALSE)
# All indirect paths from x to y
paths <- all_indirect_paths(fit,
                           x = "x",
                           y = "y")
paths
# Indirect effect estimates
# R should be 2000 or even 5000 in real research
# parallel should be used in real research.
fit_boot <- do_boot(fit, R = 45, seed = 8974,
                     parallel = FALSE,
                     progress = FALSE)
out <- many_indirect_effects(paths,
                             fit = fit,
                             boot_ci = TRUE,
                             boot_out = fit_boot)
out
confint(out)

```

data_med

Sample Dataset: Simple Mediation

Description

A simple mediation model.

Usage

data_med

Format

A data frame with 100 rows and 5 variables:

- x** Predictor. Numeric.
- m** Mediator. Numeric.
- y** Outcome variable. Numeric.
- c1** Control variable. Numeric.
- c2** Control variable. Numeric.

Examples

```
library(lavaan)
data(data_med)
mod <-
  "
m ~ a * x + c1 + c2
y ~ b * m + x + c1 + c2
ab := a * b
"
fit <- sem(mod, data_med, fixed.x = FALSE)
parameterEstimates(fit)
```

data_med_complicated *Sample Dataset: A Complicated Mediation Model*

Description

A mediation model with two predictors, two pathways,

Usage

data_med_complicated

Format

A data frame with 300 rows and 5 variables:

- x1** Predictor 1. Numeric.
- x2** Predictor 2. Numeric.
- m11** Mediator 1 in Path 1. Numeric.
- m12** Mediator 2 in Path 1. Numeric.
- m2** Mediator in Path 2. Numeric.
- y1** Outcome variable 1. Numeric.
- y2** Outcome variable 2. Numeric.
- c1** Control variable. Numeric.
- c2** Control variable. Numeric.

Examples

```
data(data_med_complicated)
dat <- data_med_complicated
summary(lm_m11 <- lm(m11 ~ x1 + x1 + x2 + c1 + c2, dat))
summary(lm_m12 <- lm(m12 ~ m11 + x1 + x2 + c1 + c2, dat))
summary(lm_m2 <- lm(m2 ~ x1 + x2 + c1 + c2, dat))
summary(lm_y1 <- lm(y1 ~ m11 + m12 + m2 + x1 + x2 + c1 + c2, dat))
summary(lm_y2 <- lm(y2 ~ m11 + m12 + m2 + x1 + x2 + c1 + c2, dat))
```

data_med_complicated_mg

Sample Dataset: A Complicated Mediation Model With Two Groups

Description

A mediation model with two predictors, two pathways, and two groups.

Usage

data_med_complicated_mg

Format

A data frame with 300 rows and 5 variables:

- x1** Predictor 1. Numeric.
- x2** Predictor 2. Numeric.
- m11** Mediator 1 in Path 1. Numeric.
- m12** Mediator 2 in Path 1. Numeric.
- m2** Mediator in Path 2. Numeric.

y1 Outcome variable 1. Numeric.
y2 Outcome variable 2. Numeric.
c1 Control variable. Numeric.
c2 Control variable. Numeric.
group Group variable. Character. 'Group A' or 'Group B'

Examples

```

library(lavaan)
data(data_med_complicated_mg)
dat <- data_med_complicated_mg
mod <-
"
m11 ~ x1 + x2 + c1 + c2
m12 ~ m11 + c1 + c2
m2 ~ x1 + x2 + c1 + c2
y1 ~ m11 + m12 + x1 + x2 + c1 + c2
y2 ~ m2 + x1 + x2 + c1 + c2
"
fit <- sem(mod, dat, group = "group")
summary(fit)
  
```

data_med_mg

Sample Dataset: Simple Mediation With Two Groups

Description

A simple mediation model with two groups.

Usage

data_med_mg

Format

A data frame with 100 rows and 5 variables:

x Predictor. Numeric.
m Mediator. Numeric.
y Outcome variable. Numeric.
c1 Control variable. Numeric.
c2 Control variable. Numeric.
group Group variable. Character. "Group A" or "Group B"

Examples

```
library(lavaan)
data(data_med_mg)
mod <-
"
m ~ c(a1, a2) * x + c1 + c2
y ~ c(b1, b2) * m + x + c1 + c2
a1b1 := a1 * b1
a2b2 := a2 * b2
abdiff := a2b2 - a1b1
"
fit <- sem(mod, data_med_mg, fixed.x = FALSE,
            group = "group")
parameterEstimates(fit)
```

data_med_mod_a

Sample Dataset: Simple Mediation with a-Path Moderated

Description

A simple mediation model with a-path moderated.

Usage

data_med_mod_a

Format

A data frame with 100 rows and 6 variables:

- x** Predictor. Numeric.
- w** Moderator. Numeric.
- m** Mediator. Numeric.
- y** Outcome variable. Numeric.
- c1** Control variable. Numeric.
- c2** Control variable. Numeric.

Examples

```
library(lavaan)
data(data_med_mod_a)
data_med_mod_a$xw <-
  data_med_mod_a$x *
  data_med_mod_a$w
mod <-
"
m ~ a * x + w + d * xw + c1 + c2
```

```

y ~ b * m + x + w + c1 + c2
w ~~ v_w * w
w ~ m_w * 1
ab := a * b
ab_lo := (a + d * (m_w - sqrt(v_w))) * b
ab_hi := (a + d * (m_w + sqrt(v_w))) * b
"
fit <- sem(mod, data_med_mod_a,
            meanstructure = TRUE, fixed.x = FALSE)
parameterEstimates(fit)[c(1, 3, 6, 11, 12, 31:33), ]

```

data_med_mod_ab

Sample Dataset: Simple Mediation with Both Paths Moderated (Two Moderators)

Description

A simple mediation model with a-path and b-path each moderated by a moderator.

Usage

data_med_mod_ab

Format

A data frame with 100 rows and 7 variables:

- x** Predictor. Numeric.
- w1** Moderator 1. Numeric.
- w2** Moderator 2. Numeric.
- m** Mediator. Numeric.
- y** Outcome variable. Numeric.
- c1** Control variable. Numeric.
- c2** Control variable. Numeric.

Examples

```

library(lavaan)
data(data_med_mod_ab)
data_med_mod_ab$xw1 <-
  data_med_mod_ab$x *
  data_med_mod_ab$w1
data_med_mod_ab$mw2 <-
  data_med_mod_ab$m *
  data_med_mod_ab$w2
mod <-
"
m ~ a * x + w1 + d1 * xw1 + c1 + c2

```

```

y ~ b * m + x + w1 + w2 + d2 * mw2 + c1 + c2
w1 ~~ v_w1 * w1
w1 ~ m_w1 * 1
w2 ~~ v_w2 * w2
w2 ~ m_w2 * 1
ab := a * b
ab_lolo := (a + d1 * (m_w1 - sqrt(v_w1))) * (b + d2 * (m_w2 - sqrt(v_w2)))
ab_lohi := (a + d1 * (m_w1 - sqrt(v_w1))) * (b + d2 * (m_w2 + sqrt(v_w2)))
ab_hilo := (a + d1 * (m_w1 + sqrt(v_w1))) * (b + d2 * (m_w2 - sqrt(v_w2)))
ab_hihi := (a + d1 * (m_w1 + sqrt(v_w1))) * (b + d2 * (m_w2 + sqrt(v_w2)))
"
fit <- sem(mod, data_med_mod_ab,
            meanstructure = TRUE, fixed.x = FALSE)
parameterEstimates(fit)[c(1, 3, 6, 10, 41:45), ]

```

data_med_mod_ab1

Sample Dataset: Simple Mediation with Both Paths Moderated By a Moderator

Description

A simple mediation model with a-path and b-path moderated by one moderator.

Usage

data_med_mod_ab1

Format

A data frame with 100 rows and 6 variables:

- x** Predictor. Numeric.
- w** Moderator. Numeric.
- m** Mediator. Numeric.
- y** Outcome variable. Numeric.
- c1** Control variable. Numeric.
- c2** Control variable. Numeric.

Examples

```

library(lavaan)
data(data_med_mod_ab1)
data_med_mod_ab1$xw <-
  data_med_mod_ab1$x *
  data_med_mod_ab1$w
data_med_mod_ab1$mw <-
  data_med_mod_ab1$m *
  data_med_mod_ab1$w

```

```

mod <-
"
m ~ a * x + w + da * xw + c1 + c2
y ~ b * m + x + w + db * mw + c1 + c2
w ~~ v_w * w
w ~ m_w * 1
ab := a * b
ab_lo := (a + da * (m_w - sqrt(v_w))) * (b + db * (m_w - sqrt(v_w)))
ab_hi := (a + da * (m_w + sqrt(v_w))) * (b + db * (m_w + sqrt(v_w)))
"
fit <- sem(mod, data_med_mod_ab1,
            meanstructure = TRUE, fixed.x = FALSE)
parameterEstimates(fit)[c(1, 3, 6, 9, 38:40), ]

```

data_med_mod_b

Sample Dataset: Simple Mediation with b-Path Moderated

Description

A simple mediation model with b-path moderated.

Usage

data_med_mod_b

Format

A data frame with 100 rows and 6 variables:

- x** Predictor. Numeric.
- w** Moderator. Numeric.
- m** Mediator. Numeric.
- y** Outcome variable. Numeric.
- c1** Control variable. Numeric.
- c2** Control variable. Numeric.

Examples

```

library(lavaan)
data(data_med_mod_b)
data_med_mod_b$mw <-
  data_med_mod_b$m *
  data_med_mod_b$w
mod <-
"
m ~ a * x + w + c1 + c2
y ~ b * m + x + d * mw + c1 + c2
w ~~ v_w * w

```

```
w ~ m_w * 1
ab := a * b
ab_lo := a * (b + d * (m_w - sqrt(v_w)))
ab_hi := a * (b + d * (m_w + sqrt(v_w)))
"
fit <- sem(mod, data_med_mod_b,
            meanstructure = TRUE, fixed.x = FALSE)
parameterEstimates(fit)[c(1, 5, 7, 10, 11, 30:32), ]
```

data_med_mod_b_mod

Sample Dataset: A Simple Mediation Model with b-Path Moderated-Moderation

Description

A simple mediation model with moderated-mediation on the b-path.

Usage

data_med_mod_b_mod

Format

A data frame with 100 rows and 5 variables:

- x** Predictor. Numeric.
- w1** Moderator on b-path. Numeric.
- w2** Moderator on the moderating effect of w1. Numeric.
- m** Mediator. Numeric.
- y** Outcome variable. Numeric.
- c1** Control variable. Numeric.
- c2** Control variable. Numeric.

Examples

```
data(data_med_mod_b_mod)
dat <- data_med_mod_b_mod
summary(lm_m <- lm(m ~ x + c1 + c2, dat))
summary(lm_y <- lm(y ~ m*w1*w2 + x + c1 + c2, dat))
```

data_med_mod_parallel *Sample Dataset: Parallel Mediation with Two Moderators*

Description

A parallel mediation model with a1-path and b2-path moderated.

Usage

data_med_mod_parallel

Format

A data frame with 100 rows and 8 variables:

- x** Predictor. Numeric.
- w1** Moderator 1. Numeric.
- w2** Moderator 2. Numeric.
- m1** Mediator 1. Numeric.
- m2** Mediator 2. Numeric.
- y** Outcome variable. Numeric.
- c1** Control variable. Numeric.
- c2** Control variable. Numeric.

Examples

```
library(lavaan)
data(data_med_mod_parallel)
data_med_mod_parallel$xw1 <-
  data_med_mod_parallel$x *
  data_med_mod_parallel$w1
data_med_mod_parallel$m2w2 <-
  data_med_mod_parallel$m2 *
  data_med_mod_parallel$w2
mod <-
  "
m1 ~ a1 * x + w1 + da1 * xw1 + c1 + c2
m2 ~ a2 * x + w1 + c1 + c2
y ~ b1 * m1 + b2 * m2 + x + w1 + w2 + db2 * m2w2 + c1 + c2
w1 ~~ v_w1 * w1
w1 ~ m_w1 * 1
w2 ~~ v_w2 * w2
w2 ~ m_w2 * 1
a1b1 := a1 * b1
a2b2 := a2 * b2
a1b1_w1lo := (a1 + da1 * (m_w1 - sqrt(v_w1))) * b1
a1b1_w1hi := (a1 + da1 * (m_w1 + sqrt(v_w1))) * b2
```

```

a2b2_w2lo := a2 * (b2 + db2 * (m_w2 - sqrt(v_w2)))
a2b2_w2hi := a2 * (b2 + db2 * (m_w2 + sqrt(v_w2)))
"
fit <- sem(mod, data_med_mod_parallel,
            meanstructure = TRUE, fixed.x = FALSE)
parameterEstimates(fit)[c(1, 3, 6, 10, 11, 15, 48:53), ]

```

data_med_mod_parallel_cat

Sample Dataset: Parallel Moderated Mediation with Two Categorical Moderators

Description

A parallel mediation model with two categorical moderators.

Usage

```
data_med_mod_parallel_cat
```

Format

A data frame with 300 rows and 8 variables:

- x** Predictor. Numeric.
- w1** Moderator. String. Values: "group1", "group2", "group3"
- w2** Moderator. String. Values: "team1", "team2"
- m1** Mediator 1. Numeric.
- m2** Mediator 2. Numeric.
- y** Outcome variable. Numeric.
- c1** Control variable. Numeric.
- c2** Control variable. Numeric.

Examples

```

data(data_med_mod_parallel_cat)
dat <- data_med_mod_parallel_cat
summary(lm_m1 <- lm(m1 ~ x*w1 + c1 + c2, dat))
summary(lm_m2 <- lm(m2 ~ x*w1 + c1 + c2, dat))
summary(lm_y <- lm(y ~ m1*w2 + m2*w2 + m1 + x + w1 + c1 + c2, dat))

```

data_med_mod_serial *Sample Dataset: Serial Mediation with Two Moderators*

Description

A simple mediation model with a-path and b2-path moderated.

Usage

data_med_mod_serial

Format

A data frame with 100 rows and 8 variables:

- x** Predictor. Numeric.
- w1** Moderator 1. Numeric.
- w2** Moderator 2. Numeric.
- m1** Mediator 1. Numeric.
- m2** Mediator 2. Numeric.
- y** Outcome variable. Numeric.
- c1** Control variable. Numeric.
- c2** Control variable. Numeric.

Examples

```
library(lavaan)
data(data_med_mod_serial)
data_med_mod_serial$xw1 <-
  data_med_mod_serial$x *
  data_med_mod_serial$w1
data_med_mod_serial$m2w2 <-
  data_med_mod_serial$m2 *
  data_med_mod_serial$w2
mod <-
  "
m1 ~ a * x + w1 + da1 * xw1 + c1 + c2
m2 ~ b1 * m1 + x + w1 + c1 + c2
y ~ b2 * m2 + m1 + x + w1 + w2 + db2 * m2w2 + c1 + c2
w1 ~~ v_w1 * w1
w1 ~ m_w1 * 1
w2 ~~ v_w2 * w2
w2 ~ m_w2 * 1
ab1b2 := a * b1 * b2
ab1b2_lolo := (a + da1 * (m_w1 - sqrt(v_w1))) * b1 * (b2 + db2 * (m_w2 - sqrt(v_w2)))
ab1b2_lohi := (a + da1 * (m_w1 - sqrt(v_w1))) * b1 * (b2 + db2 * (m_w2 + sqrt(v_w2)))
ab1b2_hilo := (a + da1 * (m_w1 + sqrt(v_w1))) * b1 * (b2 + db2 * (m_w2 - sqrt(v_w2)))
```

```

ab1b2_hihi := (a + da1 * (m_w1 + sqrt(v_w1))) * b1 * (b2 + db2 * (m_w2 + sqrt(v_w2)))
"
fit <- sem(mod, data_med_mod_serial,
            meanstructure = TRUE, fixed.x = FALSE)
parameterEstimates(fit)[c(1, 3, 6, 11, 16, 49:53), ]

```

data_med_mod_serial_cat

Sample Dataset: Serial Moderated Mediation with Two Categorical Moderators

Description

A serial mediation model with two categorical moderators.

Usage

data_med_mod_serial_cat

Format

A data frame with 300 rows and 8 variables:

- x** Predictor. Numeric.
- w1** Moderator. String. Values: "group1", "group2", "group3"
- w2** Moderator. String. Values: "team1", "team2"
- m1** Mediator 1. Numeric.
- m2** Mediator 2. Numeric.
- y** Outcome variable. Numeric.
- c1** Control variable. Numeric.
- c2** Control variable. Numeric.

Examples

```

data(data_med_mod_serial_cat)
dat <- data_med_mod_serial_cat
summary(lm_m1 <- lm(m1 ~ x*w1 + c1 + c2, dat))
summary(lm_m2 <- lm(m2 ~ m1 + x + w1 + c1 + c2, dat))
summary(lm_y <- lm(y ~ m2*w2 + m1 + x + w1 + c1 + c2, dat))

```

data_med_mod_serial_parallel

Sample Dataset: Serial-Parallel Mediation with Two Moderators

Description

A serial-parallel mediation model with some paths moderated.

Usage

```
data_med_mod_serial_parallel
```

Format

A data frame with 100 rows and 9 variables:

- x** Predictor. Numeric.
- w1** Moderator 1. Numeric.
- w2** Moderator 2. Numeric.
- m11** Mediator 1 in Path 1. Numeric.
- m12** Mediator 2 in Path 2. Numeric.
- m2** Mediator 2. Numeric.
- y** Outcome variable. Numeric.
- c1** Control variable. Numeric.
- c2** Control variable. Numeric.

Examples

```
library(lavaan)
data(data_med_mod_serial_parallel)
data_med_mod_serial_parallel$xw1 <-
  data_med_mod_serial_parallel$x *
  data_med_mod_serial_parallel$w1
data_med_mod_serial_parallel$m2w2 <-
  data_med_mod_serial_parallel$m2 *
  data_med_mod_serial_parallel$w2
mod <-
"
m11 ~ a1 * x + w1 + da11 * xw1 + c1 + c2
m12 ~ b11 * m11 + x + w1 + c1 + c2
m2 ~ a2 * x + c1 + c2
y ~ b12 * m12 + b2 * m2 + m11 + x + w1 + w2 + db2 * m2w2 + c1 + c2
w1 ~~ v_w1 * w1
w1 ~ m_w1 * 1
w2 ~~ v_w2 * w2
w2 ~ m_w2 * 1
```

```

a1b11b22 := a1 * b11 * b12
a2b2 := a2 * b2
ab := a1b11b22 + a2b2
a1b11b12_w1lo := (a1 + da11 * (m_w1 - sqrt(v_w1))) * b11 * b12
a1b11b12_w1hi := (a1 + da11 * (m_w1 + sqrt(v_w1))) * b11 * b12
a2b2_w2lo := a2 * (b2 + db2 * (m_w2 - sqrt(v_w2)))
a2b2_w2hi := a2 * (b2 + db2 * (m_w2 + sqrt(v_w2)))
"
fit <- sem(mod, data_med_mod_serial_parallel,
            meanstructure = TRUE, fixed.x = FALSE)
parameterEstimates(fit)[parameterEstimates(fit)$label != "", ]

```

data_med_mod_serial_parallel_cat

Sample Dataset: Serial-Parallel Moderated Mediation with Two Categorical Moderators

Description

A serial-parallel mediation model with two categorical moderators.

Usage

```
data_med_mod_serial_parallel_cat
```

Format

A data frame with 300 rows and 8 variables:

- x** Predictor. Numeric.
- w1** Moderator. String. Values: "group1", "group2", "group3"
- w2** Moderator. String. Values: "team1", "team2"
- m11** Mediator 1 in Path 1. Numeric.
- m12** Mediator 2 in Path 1. Numeric.
- m2** Mediator in Path 2. Numeric.
- y** Outcome variable. Numeric.
- c1** Control variable. Numeric.
- c2** Control variable. Numeric.

Examples

```

data(data_med_mod_serial_parallel_cat)
dat <- data_med_mod_serial_parallel_cat
summary(lm_m11 <- lm(m11 ~ x*w1 + c1 + c2, dat))
summary(lm_m12 <- lm(m12 ~ m11 + x + w1 + c1 + c2, dat))
summary(lm_m2 <- lm(m2 ~ x + w1 + c1 + c2, dat))
summary(lm_y <- lm(y ~ m12 + m2*w2 + m12 + x + c1 + c2, dat))

```

data_mod

*Sample Dataset: One Moderator***Description**

A one-moderator model.

Usage

data_mod

Format

A data frame with 100 rows and 5 variables:

- x** Predictor. Numeric.
- w** Moderator. Numeric.
- y** Outcome variable. Numeric.
- c1** Control variable. Numeric.
- c2** Control variable. Numeric.

Examples

```
library(lavaan)
data(data_mod)
data_mod$xw <- data_mod$x * data_mod$w
mod <-
"
y ~ a * x + w + d * xw + c1 + c2
w ~~ v_w * w
w ~ m_w * 1
a_lo := a + d * (m_w - sqrt(v_w))
a_hi := a + d * (m_w + sqrt(v_w))
"
fit <- sem(mod, data_mod, fixed.x = FALSE)
parameterEstimates(fit)[c(1, 3, 6, 7, 24, 25), ]
```

data_mod2

*Sample Dataset: Two Moderators***Description**

A two-moderator model.

Usage

data_mod2

Format

A data frame with 100 rows and 6 variables:

- x** Predictor. Numeric.
- w1** Moderator 1. Numeric.
- w2** Moderator 2. Numeric.
- y** Outcome variable. Numeric.
- c1** Control variable. Numeric.
- c2** Control variable. Numeric.

Examples

```
library(lavaan)
data(data_mod2)
data_mod2$xw1 <- data_mod2$x * data_mod2$w1
data_mod2$xw2 <- data_mod2$x * data_mod2$w2
mod <-
"
y ~ a * x + w1 + w2 + d1 * xw1 + d2 * xw2 + c1 + c2
w1 ~~ v_w1 * w1
w1 ~ m_w1 * 1
w2 ~~ v_w2 * w2
w2 ~ m_w2 * 1
a_lolo := a + d1 * (m_w1 - sqrt(v_w1)) + d2 * (m_w2 - sqrt(v_w2))
a_lohi := a + d1 * (m_w1 - sqrt(v_w1)) + d2 * (m_w2 + sqrt(v_w2))
a_hilo := a + d1 * (m_w1 + sqrt(v_w1)) + d2 * (m_w2 - sqrt(v_w2))
a_hihi := a + d1 * (m_w1 + sqrt(v_w1)) + d2 * (m_w2 + sqrt(v_w2))
"
fit <- sem(mod, data_mod2, fixed.x = FALSE)
parameterEstimates(fit)[c(1, 4, 5, 8:11, 34:37), ]
```

data_mod_cat

Sample Dataset: Moderation with One Categorical Moderator

Description

A moderation model with a categorical moderator.

Usage

data_mod_cat

Format

A data frame with 300 rows and 5 variables:

- x** Predictor. Numeric.
- w** Moderator. String. Values: "group1", "group2", "group3"
- y** Outcome variable. Numeric.
- c1** Control variable. Numeric.
- c2** Control variable. Numeric.

Examples

```
data(data_mod_cat)
dat <- data_mod_cat
summary(lm_y <- lm(y ~ x*w + c1 + c2, dat))
```

data_mome_demo

Sample Dataset: A Complicated Moderated-Mediation Model

Description

Generated from a complicated moderated-mediation model for demonstration.

Usage

```
data_mome_demo
```

Format

A data frame with 200 rows and 11 variables:

- x1** Predictor 1. Numeric.
- x2** Predictor 2. Numeric.
- m1** Mediator 1. Numeric.
- m2** Mediator 2. Numeric.
- m3** Mediator 3. Numeric.
- y1** Outcome Variable 1. Numeric.
- y2** Outcome Variable 2. Numeric.
- w1** Moderator 1. Numeric.
- w2** Moderator 2. Numeric.
- c1** Control Variable 1. Numeric.
- c2** Control Variable 2. Numeric.

Details

The model:

```
# w1x1 <- x1 * w1
# w2m2 <- w2 * m2
m1 ~ x1 + w1 + w1x1 + x2 + c1 + c2
m2 ~ m1 + c1 + c2
m3 ~ x2 + x1 + c1 + c2
y1 ~ m2 + w2 + w2m2 + x1 + x2 + m3 + c1 + c2
y2 ~ m3 + x2 + x1 + m2 + c1 + c2
# Covariances excluded for brevity
```

data_mome_demo_missing

Sample Dataset: A Complicated Moderated-Mediation Model With Missing Data

Description

Generated from a complicated moderated-mediation model for demonstration, with missing data

Usage

data_mome_demo_missing

Format

A data frame with 200 rows and 11 variables:

x1 Predictor 1. Numeric.
x2 Predictor 2. Numeric.
m1 Mediator 1. Numeric.
m2 Mediator 2. Numeric.
m3 Mediator 3. Numeric.
y1 Outcome Variable 1. Numeric.
y2 Outcome Variable 2. Numeric.
w1 Moderator 1. Numeric.
w2 Moderator 2. Numeric.
c1 Control Variable 1. Numeric.
c2 Control Variable 2. Numeric.

Details

A copy of [data_mome_demo](#) with some randomly selected cells changed to NA. The number of cases with no missing data is 169.

The model:

```
# w1x1 <- x1 * w1
# w2m2 <- w2 * m2
m1 ~ x1 + w1 + w1x1 + x2 + c1 + c2
m2 ~ m1 + c1 + c2
m3 ~ x2 + x1 + c1 + c2
y1 ~ m2 + w2 + w2m2 + x1 + x2 + m3 + c1 + c2
y2 ~ m3 + x2 + x1 + m2 + c1 + c2
# Covariances excluded for brevity
```

data_parallel

Sample Dataset: Parallel Mediation

Description

A parallel mediation model.

Usage

data_parallel

Format

A data frame with 100 rows and 6 variables:

- x** Predictor. Numeric.
- m1** Mediator 1. Numeric.
- m2** Mediator 2. Numeric.
- y** Outcome variable. Numeric.
- c1** Control variable. Numeric.
- c2** Control variable. Numeric.

Examples

```
library(lavaan)
data(data_parallel)
mod <-
"
m1 ~ a1 * x + c1 + c2
m2 ~ a2 * x + c1 + c2
y ~ b2 * m2 + b1 * m1 + x + c1 + c2
indirect1 := a1 * b1
```

```
indirect2 := a2 * b2
indirect := a1 * b1 + a2 * b2
"
fit <- sem(mod, data_parallel,
            meanstructure = TRUE, fixed.x = FALSE)
parameterEstimates(fit)[c(1, 4, 7, 8, 27:29), ]
```

data_sem*Sample Dataset: A Latent Variable Mediation Model With 4 Factors*

Description

This data set is for testing functions in a four-factor structural model.

Usage

```
data_sem
```

Format

A data frame with 200 rows and 14 variables:

x01 Indicator. Numeric.
x02 Indicator. Numeric.
x03 Indicator. Numeric.
x04 Indicator. Numeric.
x05 Indicator. Numeric.
x06 Indicator. Numeric.
x07 Indicator. Numeric.
x08 Indicator. Numeric.
x09 Indicator. Numeric.
x10 Indicator. Numeric.
x11 Indicator. Numeric.
x12 Indicator. Numeric.
x13 Indicator. Numeric.
x14 Indicator. Numeric.

Examples

```
data(data_sem)
dat <- data_med_mod_b_mod
mod <-
  'f1 =~ x01 + x02 + x03
  f2 =~ x04 + x05 + x06 + x07
  f3 =~ x08 + x09 + x10
  f4 =~ x11 + x12 + x13 + x14
  f3 ~ a1*f1 + a2*f2
  f4 ~ b1*f1 + b3*f3
  a1b3 := a1 * b3
  a2b3 := a2 * b3
  '
fit <- lavaan::sem(model = mod, data = data_sem)
summary(fit)
```

data_serial

Sample Dataset: Serial Mediation

Description

A serial mediation model.

Usage

data_serial

Format

A data frame with 100 rows and 6 variables:

- x** Predictor. Numeric.
- m1** Mediator 1. Numeric.
- m2** Mediator 2. Numeric.
- y** Outcome variable. Numeric.
- c1** Control variable. Numeric.
- c2** Control variable. Numeric.

Examples

```
library(lavaan)
data(data_serial)
mod <-
  "
m1 ~ a * x + c1 + c2
m2 ~ b1 * m1 + x + c1 + c2
```

```

y ~ b2 * m2 + m1 + x + c1 + c2
indirect := a * b1 * b2
"
fit <- sem(mod, data_serial,
            meanstructure = TRUE, fixed.x = FALSE)
parameterEstimates(fit)[c(1, 4, 8, 28), ]

```

data_serial_parallel *Sample Dataset: Serial-Parallel Mediation*

Description

A mediation model with both serial and parallel components.

Usage

`data_serial_parallel`

Format

A data frame with 100 rows and 7 variables:

- x** Predictor. Numeric.
- m11** Mediator 1 in Path 1. Numeric.
- m12** Mediator 2 in Path 1. Numeric.
- m2** Mediator in Path 2. Numeric.
- y** Outcome variable. Numeric.
- c1** Control variable. Numeric.
- c2** Control variable. Numeric.

Examples

```

library(lavaan)
data(data_serial_parallel)
mod <-
"
m11 ~ a11 * x + c1 + c2
m12 ~ b11 * m11 + x + c1 + c2
m2 ~ a2 * x + c1 + c2
y ~ b12 * m12 + b2 * m2 + m11 + x + c1 + c2
indirect1 := a11 * b11 * b12
indirect2 := a2 * b2
indirect := a11 * b11 * b12 + a2 * b2
"
fit <- sem(mod, data_serial_parallel,
            meanstructure = TRUE, fixed.x = FALSE)
parameterEstimates(fit)[c(1, 4, 8, 11, 12, 34:36), ]

```

data_serial_parallel_latent

Sample Dataset: A Latent Mediation Model With Three Mediators

Description

Generated from a 3-mediator mediation model among eight latent factors, fx1, fx2, fm11, fm12, fy1, and fy2, each has three indicators.

Usage

```
data_serial_parallel_latent
```

Format

A data frame with 500 rows and 21 variables:

x1 Indicator of fx1. Numeric.
x2 Indicator of fx1. Numeric.
x3 Indicator of fx1. Numeric.
x4 Indicator of fx2. Numeric.
x5 Indicator of fx2. Numeric.
x6 Indicator of fx2. Numeric.
m11a Indicator of fm11. Numeric.
m11b Indicator of fm11. Numeric.
m11c Indicator of fm11. Numeric.
m12a Indicator of fm12. Numeric.
m12b Indicator of fm12. Numeric.
m12c Indicator of fm12. Numeric.
m2a Indicator of fm2. Numeric.
m2b Indicator of fm2. Numeric.
m2c Indicator of fm2. Numeric.
y1 Indicator of fy1. Numeric.
y2 Indicator of fy1. Numeric.
y3 Indicator of fy1. Numeric.
y4 Indicator of fy2. Numeric.
y5 Indicator of fy2. Numeric.
y6 Indicator of fy2. Numeric.

Details

The model:

```

fx1 =~ x1 + x2 + x3
fx2 =~ x4 + x5 + x6
fm11 =~ m11a + m11b + m11c
fm12 =~ m12a + m12b + m12c
fm2 =~ m2a + m2b + m2c
fy1 =~ y1 + y2 + y3
fy2 =~ y3 + y4 + y5
fm11 ~ a1 * fx1
fm12 ~ b11 * fm11 + a2m * fx2
fm2 ~ a2 * fx2
fy1 ~ b12 * fm12 + b11y1 * fm11 + cp1 * fx1
fy2 ~ b2 * fm2 + cp2 * fx2
a1b11b12 := a1 * b11 * b12
a1b11y1 := a1 * b11y1
a2b2 := a2 * b2
a2mb12 := a2m * b12

```

delta_med

Delta_Med by Liu, Yuan, and Li (2023)

Description

It computes the Delta_Med proposed by Liu, Yuan, and Li (2023), an R^2 -like measure of indirect effect.

Usage

```

delta_med(
  x,
  y,
  m,
  fit,
  paths_to_remove = NULL,
  boot_out = NULL,
  level = 0.95,
  progress = TRUE,
  skip_check_single_x = FALSE,
  skip_check_m_between_x_y = FALSE,
  skip_check_x_to_y = FALSE,
  skip_check_latent_variables = FALSE,
  boot_type = c("perc", "bc")
)

```

Arguments

x	The name of the x variable. Must be supplied as a quoted string.
y	The name of the y variable. Must be supplied as a quoted string.
m	A vector of the variable names of the mediator(s). If more than one mediators, they do not have to be on the same path from x to y. Cannot be NULL for this function.
fit	The fit object. Must be a lavaan::lavaan object.
paths_to_remove	A character vector of paths users want to manually remove, specified in lavaan model syntax. For example, c("m2~x", "m3~m2") removes the path from x to m2 and the path from m2 to m3. The default is NULL, and the paths to remove will be determined using the method by Liu et al. (2023). If supplied, then only paths specified explicitly will be removed.
boot_out	The output of do_boot(). If supplied, the stored bootstrap estimates will be used to form the nonparametric percentile bootstrap confidence interval of Delta_Med.
level	The level of confidence of the bootstrap confidence interval. Default is .95.
progress	Logical. Display bootstrapping progress or not. Default is TRUE.
skip_check_single_x	Logical. Check whether the model has one and only one x-variable. Default is TRUE.
skip_check_m_between_x_y	Logical. Check whether all m variables are along a path from x to y. Default is TRUE.
skip_check_x_to_y	Logical. Check whether there is a direct path from x to y. Default is TRUE.
skip_check_latent_variables	Logical. Check whether the model has any latent variables. Default is TRUE.
boot_type	If bootstrap confidence interval is to be formed, the type of bootstrap confidence interval. The supported types are "perc" (percentile bootstrap confidence interval, the default and recommended type) and "bc" (bias-corrected, or BC, bootstrap confidence interval).

Details

It computes Delta_Med, an R^2 -like effect size measure for the indirect effect from one variable (the y-variable) to another variable (the x-variable) through one or more mediators (m, or m1, m2, etc. when there are more than one mediator).

The Delta_Med of one or more mediators was computed as the difference between two R^2 s:

- R_1^2 , the R^2 when y is predicted by x and all mediators.
- R_2^2 , the R^2 when the mediator(s) of interest is/are removed from the models, while the error term(s) of the mediator(s) is/are kept.

Delta_Med is given by $R_1^2 - R_2^2$.

Please refer to Liu et al. (2023) for the technical details.

The function can also form a nonparametric percentile bootstrap confidence of Delta_Med.

Value

A delta_med class object. It is a list-like object with these major elements:

- delta_med: The Delta_Med.
- x: The name of the x-variable.
- y: The name of the y-variable.
- m: A character vector of the mediator(s) along a path. The path runs from the first element to the last element.

This class has a `print` method, a `coef` method, and a `confint` method. See `print.delta_med()`, `coef.delta_med()`, and `confint.delta_med()`.

Implementation

The function identifies all the path(s) pointing to the mediator(s) of concern and fixes the path(s) to zero, effectively removing the mediator(s). However, the model is not refitted, hence keeping the estimates of all other parameters unchanged. It then uses `lavaan::lav_model_set_parameters()` to update the parameters, `lavaan::lav_model_implied()` to update the implied statistics, and then calls `lavaan::lavInspect()` to retrieve the implied variance of the predicted values of y for computing the R^2_2 . Subtracting this R^2_2 from R^2_1 of y can then yield Delta_Med.

Model Requirements

For now, by default, it only computes Delta_Med for the types of models discussed in Liu et al. (2023):

- Having one predictor (the x-variable).
- Having one or more mediators, the m-variables, with arbitrary way to mediate the effect of x on the outcome variable (y-variable).
- Having one or more outcome variables. Although their models only have outcome variables, the computation of the Delta_Med is not affected by the presence of other outcome variables.
- Having no control variables.
- The mediator(s), m, and the y-variable are continuous.
- x can be continuous or categorical. If categorical, it needs to be handle appropriately when fitting the model.
- x has a direct path to y.
- All the mediators listed in the argument m is present in at least one path from x to y.
- None of the paths from x to y are moderated.

It can be used for other kinds of models but support for them is disabled by default. To use this function for cases not discussed in Liu et al. (2023), please disable relevant requirements stated above using the relevant `skip_check_*` arguments. An error will be raised if the models failed any of the checks not skipped by users.

References

Liu, H., Yuan, K.-H., & Li, H. (2025). A systematic framework for defining R-squared measures in mediation analysis. *Psychological Methods*, 30(2), 306-321. <https://doi.org/10.1037/met0000571>

See Also

[print.delta_med\(\)](#), [coef.delta_med\(\)](#), and [confint.delta_med\(\)](#).

Examples

```
library(lavaan)
dat <- data_med
mod <-
"
m ~ x
y ~ m + x
"
fit <- sem(mod, dat)
dm <- delta_med(x = "x",
                 y = "y",
                 m = "m",
                 fit = fit)
dm
print(dm, full = TRUE)

# Call do_boot() to generate
# bootstrap estimates
# Use 2000 or even 5000 for R in real studies
# Set parallel to TRUE in real studies for faster bootstrapping
boot_out <- do_boot(fit,
                      R = 45,
                      seed = 879,
                      parallel = FALSE,
                      progress = FALSE)
# Remove 'progress = FALSE' in practice
dm_boot <- delta_med(x = "x",
                      y = "y",
                      m = "m",
                      fit = fit,
                      boot_out = boot_out,
                      progress = FALSE)
dm_boot
confint(dm_boot)
```

do_boot

Bootstrap Estimates for 'indirect_effects' and 'cond_indirect_effects'

Description

Generate bootstrap estimates to be used by [cond_indirect_effects\(\)](#), [indirect_effect\(\)](#), and [cond_indirect\(\)](#),

Usage

```
do_boot(
  fit,
  R = 100,
  seed = NULL,
  parallel = TRUE,
  ncores = max(parallel::detectCores(logical = FALSE) - 1, 1),
  make_cluster_args = list(),
  progress = TRUE,
  compute_implied_stats = TRUE
)
```

Arguments

fit	It can be (a) a list of <code>lm</code> class objects, or the output of <code>lm2list()</code> (i.e., an <code>lm_list</code> -class object), or (b) the output of <code>lavaan::sem()</code> . If it is a single model fitted by <code>lm()</code> , it will be automatically converted to a list by <code>lm2list()</code> .
R	The number of bootstrap samples. Default is 100.
seed	The seed for the bootstrapping. Default is <code>NULL</code> and seed is not set.
parallel	Logical. Whether parallel processing will be used. Default is <code>TRUE</code> .
ncores	Integer. The number of CPU cores to use when <code>parallel</code> is <code>TRUE</code> . Default is the number of non-logical cores minus one (one minimum). Will raise an error if greater than the number of cores detected by <code>parallel::detectCores()</code> . If <code>ncores</code> is set, it will override <code>make_cluster_args</code> .
make_cluster_args	A named list of additional arguments to be passed to <code>parallel::makeCluster()</code> . For advanced users. See <code>parallel::makeCluster()</code> for details. Default is <code>list()</code> , no additional arguments.
progress	Logical. Display progress or not. Default is <code>TRUE</code> .
compute_implied_stats	If <code>TRUE</code> , default, implied statistics will be computed for each bootstrap sample. Letting users to disable this is an experimental features to let the process run faster.

Details

It does nonparametric bootstrapping to generate bootstrap estimates of the parameter estimates in a model fitted either by `lavaan::sem()` or by a sequence of calls to `lm()`. The stored estimates can then be used by `cond_indirect_effects()`, `indirect_effect()`, and `cond_indirect()` to form bootstrapping confidence intervals.

This approach removes the need to repeat bootstrapping in each call to `cond_indirect_effects()`, `indirect_effect()`, and `cond_indirect()`. It also ensures that the same set of bootstrap samples is used in all subsequent analysis.

It determines the type of the `fit` object automatically and then calls `lm2boot_out()`, `fit2boot_out()`, or `fit2boot_out_do_boot()`.

Multigroup Models:

Since Version 0.1.14.2, support for multigroup models has been added for models fitted by lavaan. The implementation of bootstrapping is identical to that used by lavaan, with resampling done within each group.

Value

A boot_out-class object that can be used for the boot_out argument of `cond_indirect_effects()`, `indirect_effect()`, and `cond_indirect()` for forming bootstrap confidence intervals. The object is a list with the number of elements equal to the number of bootstrap samples. Each element is a list of the parameter estimates and sample variances and covariances of the variables in each bootstrap sample.

See Also

`lm2boot_out()`, `fit2boot_out()`, and `fit2boot_out_do_boot()`, which implements the bootstrapping.

Examples

```
data(data_med_mod_ab1)
dat <- data_med_mod_ab1
lm_m <- lm(m ~ x*w + c1 + c2, dat)
lm_y <- lm(y ~ m*w + x + c1 + c2, dat)
lm_out <- lm2list(lm_m, lm_y)
# In real research, R should be 2000 or even 5000
# In real research, no need to set parallel and progress to FALSE
# Parallel processing is enabled by default and
# progress is displayed by default.
lm_boot_out <- do_boot(lm_out, R = 50, seed = 1234,
                       parallel = FALSE,
                       progress = FALSE)
wlevels <- mod_levels(w = "w", fit = lm_out)
wlevels
out <- cond_indirect_effects(wlevels = wlevels,
                             x = "x",
                             y = "y",
                             m = "m",
                             fit = lm_out,
                             boot_ci = TRUE,
                             boot_out = lm_boot_out)
out
```

Description

Generate Monte Carlo estimates to be used by `cond_indirect_effects()`, `indirect_effect()`, and `cond_indirect()`.

Usage

```
do_mc(
  fit,
  R = 100,
  seed = NULL,
  parallel = TRUE,
  ncores = max(parallel::detectCores(logical = FALSE) - 1, 1),
  make_cluster_args = list(),
  progress = TRUE,
  compute_implied_stats = TRUE
)
gen_mc_est(fit, R = 100, seed = NULL)
```

Arguments

<code>fit</code>	The output of <code>lavaan::sem()</code> . It can also be a <code>lavaan.mi</code> object returned by <code>lavaan.mi::lavaan.mi()</code> or its wrapper, such as <code>lavaan.mi::sem.mi()</code> . The output of <code>stats::lm()</code> is not supported.
<code>R</code>	The number of replications. Default is 100.
<code>seed</code>	The seed for the generating Monte Carlo estimates. Default is <code>NULL</code> and seed is not set.
<code>parallel</code>	Not used. Kept for compatibility with <code>do_boot()</code> .
<code>ncores</code>	Not used. Kept for compatibility with <code>do_boot()</code> .
<code>make_cluster_args</code>	Not used. Kept for compatibility with <code>do_boot()</code> .
<code>progress</code>	Logical. Display progress or not. Default is <code>TRUE</code> .
<code>compute_implied_stats</code>	If <code>TRUE</code> , default, implied statistics will be computed for each replication. Letting users to disable this is an experimental features to let the process run faster.

Details

It uses the parameter estimates and their variance-covariance matrix to generate Monte Carlo estimates of the parameter estimates in a model fitted by `lavaan::sem()`. The stored estimates can then be used by `cond_indirect_effects()`, `indirect_effect()`, and `cond_indirect()` to form Monte Carlo confidence intervals.

It also supports a model estimated by multiple imputation using `lavaan.mi::lavaan.mi()` or its wrapper, such as `lavaan.mi::sem.mi()`. The pooled estimates and their variance-covariance matrix will be used to generate the Monte Carlo estimates.

This approach removes the need to repeat Monte Carlo simulation in each call to `cond_indirect_effects()`, `indirect_effect()`, and `cond_indirect()`. It also ensures that the same set of Monte Carlo estimates is used in all subsequent analysis.

Multigroup Models:

Since Version 0.1.14.2, support for multigroup models has been added for models fitted by lavaan.

Value

A `mc_out`-class object that can be used for the `mc_out` argument of `cond_indirect_effects()`, `indirect_effect()`, and `cond_indirect()` for forming Monte Carlo confidence intervals. The object is a list with the number of elements equal to the number of Monte Carlo replications. Each element is a list of the parameter estimates and sample variances and covariances of the variables in each Monte Carlo replication.

Functions

- `do_mc()`: A general purpose function for creating Monte Carlo estimates to be reused by other functions. It returns a `mc_out`-class object.
- `gen_mc_est()`: Generate Monte Carlo estimates and store them in the `external` slot: `external$manyMome$mc`. For advanced users.

See Also

`fit2mc_out()`, which implements the Monte Carlo simulation.

Examples

```
library(lavaan)
data(data_med_mod_ab1)
dat <- data_med_mod_ab1
mod <-
"
m ~ x + w + x:w + c1 + c2
y ~ m + w + m:w + x + c1 + c2
"
fit <- sem(mod, dat)
# In real research, R should be 5000 or even 10000
mc_out <- do_mc(fit, R = 100, seed = 1234)
wlevels <- mod_levels(w = "w", fit = fit)
wlevels
out <- cond_indirect_effects(wlevels = wlevels,
                               x = "x",
                               y = "y",
                               m = "m",
                               fit = fit,
                               mc_ci = TRUE,
                               mc_out = mc_out)
out
```

factor2var	<i>Create Dummy Variables</i>
------------	-------------------------------

Description

Create dummy variables from a categorical variable.

Usage

```
factor2var(  
  x_value,  
  x_contrasts = "contr.treatment",  
  prefix = "",  
  add_rownames = TRUE  
)
```

Arguments

x_value	The vector of categorical variable.
x_contrasts	The contrast to be used. Default is "contr.treatment".
prefix	The prefix to be added to the variables to be created. Default is "".
add_rownames	Whether row names will be added to the output. Default is TRUE.

Details

Its main use is for creating dummy variables (indicator variables) from a categorical variable, to be used in [lavaan::sem\(\)](#).

Optionally, the other contrasts can be used through the argument `x_contrasts`.

Value

It always returns a matrix with the number of rows equal to the length of the vector (`x_value`). If the categorical has only two categories and so only one dummy variable is needed, the output is still a one-column "matrix" in R.

Examples

```
dat <- data_mod_cat  
dat <- data.frame(dat,  
                  factor2var(dat$w, prefix = "gp", add_rownames = FALSE))  
head(dat[, c("w", "gpgroup2", "gpgroup3")], 15)
```

<code>fit2boot_out</code>	<i>Bootstrap Estimates for a lavaan Output</i>
---------------------------	--

Description

Generate bootstrap estimates from the output of [lavaan::sem\(\)](#).

Usage

```
fit2boot_out(fit, compute_implied_stats = TRUE)

fit2boot_out_do_boot(
  fit,
  R = 100,
  seed = NULL,
  parallel = FALSE,
  ncores = max(parallel::detectCores(logical = FALSE) - 1, 1),
  make_cluster_args = list(),
  progress = TRUE,
  compute_implied_stats = TRUE,
  compute_rsquare = FALSE,
  internal = list()
)
```

Arguments

<code>fit</code>	The fit object. This function only supports a lavaan::lavaan object.
<code>compute_implied_stats</code>	If TRUE, default, implied statistics will be computed for each bootstrap sample. Letting users to disable this is an experimental features to let the process run faster.
<code>R</code>	The number of bootstrap samples. Default is 100.
<code>seed</code>	The seed for the random resampling. Default is NULL.
<code>parallel</code>	Logical. Whether parallel processing will be used. Default is NULL.
<code>ncores</code>	Integer. The number of CPU cores to use when <code>parallel</code> is TRUE. Default is the number of non-logical cores minus one (one minimum). Will raise an error if greater than the number of cores detected by parallel::detectCores() . If <code>ncores</code> is set, it will override <code>make_cluster_args</code> .
<code>make_cluster_args</code>	A named list of additional arguments to be passed to parallel::makeCluster() . For advanced users. See parallel::makeCluster() for details. Default is list().
<code>progress</code>	Logical. Display progress or not. Default is TRUE.

compute_rsquare

If TRUE, R-squares will be computed for each bootstrap sample (given by `lavaan:::parameterEstimates`). Default is FALSE because it is rarely necessary, and enabling it slows down the computation.

internal

A list of arguments to be used internally for debugging. Default is `list()`.

Details

This function is for advanced users. `do_boot()` is a function users should try first because `do_boot()` has a general interface for input-specific functions like this one.

If bootstrapping confidence intervals was requested when calling `lavaan:::sem()` by setting `se = "boot"`, `fit2boot_out()` can be used to extract the stored bootstrap estimates so that they can be reused by `indirect_effect()`, `cond_indirect_effects()` and related functions to form bootstrapping confidence intervals for effects such as indirect effects and conditional indirect effects.

If bootstrapping confidence was not requested when fitting the model by `lavaan:::sem()`, `fit2boot_out_do_boot()` can be used to generate nonparametric bootstrap estimates from the output of `lavaan:::sem()` and store them for use by `indirect_effect()`, `cond_indirect_effects()`, and related functions.

This approach removes the need to repeat bootstrapping in each call to `indirect_effect()`, `cond_indirect_effects()`, and related functions. It also ensures that the same set of bootstrap samples is used in all subsequent analyses.

Value

A `boot_out`-class object that can be used for the `boot_out` argument of `indirect_effect()`, `cond_indirect_effects()`, and related functions for forming bootstrapping confidence intervals.

The object is a list with the number of elements equal to the number of bootstrap samples. Each element is a list of the parameter estimates and sample variances and covariances of the variables in each bootstrap sample.

Functions

- `fit2boot_out()`: Process stored bootstrap estimates for functions such as `cond_indirect_effects()`.
- `fit2boot_out_do_boot()`: Do bootstrapping and store information to be used by `cond_indirect_effects()` and related functions. Support parallel processing.

See Also

`do_boot()`, the general purpose function that users should try first before using this function.

Examples

```
library(lavaan)
data(data_med_mod_ab1)
dat <- data_med_mod_ab1
dat$"x:w" <- dat$x * dat$w
dat$"m:w" <- dat$m * dat$w
mod <-
"
m ~ x + w + x:w + c1 + c2
```

```

y ~ m + w + m:w + x + c1 + c2
"

# Bootstrapping not requested in calling lavaan::sem()
fit <- sem(model = mod, data = dat, fixed.x = FALSE,
            se = "none", baseline = FALSE)
fit_boot_out <- fit2boot_out_do_boot(fit = fit,
                                      R = 40,
                                      seed = 1234,
                                      progress = FALSE)
out <- cond_indirect_effects(wlevels = "w",
                             x = "x",
                             y = "y",
                             m = "m",
                             fit = fit,
                             boot_ci = TRUE,
                             boot_out = fit_boot_out)
out

```

fit2mc_out*Monte Carlo Estimates for a lavaan Output*

Description

Generate Monte Carlo estimates from the output of [lavaan::sem\(\)](#).

Usage

```
fit2mc_out(fit, progress = TRUE, compute_implied_stats = TRUE)
```

Arguments

fit The fit object. This function only supports a [lavaan::lavaan](#) object. It can also be a [lavaan.mi](#) object returned by [lavaan.mi::lavaan.mi\(\)](#) or its wrapper, such as [lavaan.mi::sem.mi\(\)](#).

progress Logical. Display progress or not. Default is TRUE.

compute_implied_stats If TRUE, default, implied statistics will be computed for each replication. Letting users to disable this is an experimental features to let the process run faster.

Details

This function is for advanced users. [do_mc\(\)](#) is a function users should try first because [do_mc\(\)](#) has a general interface for input-specific functions like this one.

[fit2mc_out\(\)](#) can be used to extract the stored Monte Carlo estimates so that they can be reused by [indirect_effect\(\)](#), [cond_indirect_effects\(\)](#) and related functions to form Monte Carlo confidence intervals for effects such as indirect effects and conditional indirect effects.

This approach removes the need to repeat Monte Carlo simulation in each call to `indirect_effect()`, `cond_indirect_effects()`, and related functions. It also ensures that the same set of Monte Carlo estimates is used in all subsequent analyses.

Value

A `mc_out`-class object that can be used for the `mc_out` argument of `indirect_effect()`, `cond_indirect_effects()`, and related functions for forming Monte Carlo confidence intervals.

The object is a list with the number of elements equal to the number of Monte Carlo replications. Each element is a list of the parameter estimates and sample variances and covariances of the variables in each Monte Carlo replication.

See Also

`do_mc()`, the general purpose function that users should try first before using this function.

Examples

```
library(lavaan)
data(data_med_mod_ab1)
dat <- data_med_mod_ab1
dat$"x:w" <- dat$x * dat$w
dat$"m:w" <- dat$m * dat$w
mod <-
"
m ~ x + w + x:w + c1 + c2
y ~ m + w + m:w + x + c1 + c2
"

fit <- sem(model = mod, data = dat, fixed.x = FALSE,
           baseline = FALSE)
# In real research, R should be 5000 or even 10000.
fit <- gen_mc_est(fit, R = 100, seed = 453253)
fit_mc_out <- fit2mc_out(fit)
out <- cond_indirect_effects(wlevels = "w",
                             x = "x",
                             y = "y",
                             m = "m",
                             fit = fit,
                             mc_ci = TRUE,
                             mc_out = fit_mc_out)
out
```

get_one_cond_indirect_effect

*Get The Conditional Indirect Effect for One Row of
'cond_indirect_effects' Output*

Description

Return the conditional indirect effect of one row of the output of [cond_indirect_effects\(\)](#).

Usage

```
get_one_cond_indirect_effect(object, row)

get_one_cond_effect(object, row)

print_all_cond_indirect_effects(object, ...)

print_all_cond_effects(object, ...)
```

Arguments

object	The output of cond_indirect_effects() .
row	The row number of the row to be retrieved.
...	Optional arguments to be passed to the print method of the output of indirect_effect() and cond_indirect()

Details

[get_one_cond_indirect_effect\(\)](#) extracts the corresponding output of [cond_indirect\(\)](#) from the requested row.

[get_one_cond_effect\(\)](#) is an alias of [get_one_cond_indirect_effect\(\)](#).

[print_all_cond_indirect_effects\(\)](#) loops over the conditional effects and print all of them.

[print_all_cond_effects\(\)](#) is an alias of [print_all_cond_indirect_effects\(\)](#).

Value

[get_one_cond_indirect_effect\(\)](#) returns an indirect-class object, similar to the output of [indirect_effect\(\)](#) and [cond_indirect\(\)](#). See [indirect_effect\(\)](#) and [cond_indirect\(\)](#) for details on these classes.

[print_all_cond_indirect_effects\(\)](#) returns the object invisibly. Called for its side effect.

See Also

[cond_indirect_effects](#)

Examples

```
library(lavaan)
dat <- modmed_x1m3w4y1
mod <-
"
m1 ~ x + w1 + x:w1
m2 ~ m1
y ~ m2 + x + w4 + m2:w4
```

```

"
fit <- sem(mod, dat,
            meanstructure = TRUE, fixed.x = FALSE,
            se = "none", baseline = FALSE)
est <- parameterEstimates(fit)

# Examples for cond_indirect():

# Conditional effects from x to m1
# when w1 is equal to each of the default levels
out1 <- cond_indirect_effects(x = "x", y = "m1",
                               wlevels = c("w1", "w4"), fit = fit)
get_one_cond_indirect_effect(out1, 3)

# Conditional Indirect effect from x1 through m1 to y,
# when w1 is equal to each of the levels
out2 <- cond_indirect_effects(x = "x", y = "y", m = c("m1", "m2"),
                               wlevels = c("w1", "w4"), fit = fit)
get_one_cond_indirect_effect(out2, 4)

print_all_cond_indirect_effects(out2, digits = 2)

```

get_prod*Product Terms (if Any) Along a Path*

Description

Identify the product term(s), if any, along a path in a model and return the term(s), with the variables involved and the coefficient(s) of the term(s).

Usage

```
get_prod(
  x,
  y,
  operator = ":",
  fit = NULL,
  est = NULL,
  data = NULL,
  expand = FALSE,
  skip_indicators = TRUE
)
```

Arguments

x	Character. Variable name.
y	Character. Variable name.

operator	Character. The string used to indicate a product term. Default is ":", used in both <code>lm()</code> and <code>lavaan::sem()</code> for observed variables.
fit	The fit object. Currently only supports a <code>lavaan::lavaan</code> object. It can also be a <code>lavaan.mi</code> object returned by <code>lavaan.mi::lavaan.mi()</code> or its wrapper, such as <code>lavaan.mi::sem.mi()</code> .
est	The output of <code>lavaan::parameterEstimates()</code> . If NULL, the default, it will be generated from fit. If supplied, fit will be ignored.
data	Data frame (optional). If supplied, it will be used to identify the product terms.
expand	Whether products of more than two terms will be searched. FALSE by default.
skip_indicators	Whether observed indicators are skipped from the search for product terms. Default is TRUE.

Details

This function is used by several functions in `manymome` to identify product terms along a path. If possible, this is done by numerically checking whether a column in a dataset is the product of two other columns. If not possible (e.g., the "product term" is the "product" of two latent variables, formed by the products of indicators), then it requires the user to specify an operator.

The detailed workflow of this function can be found in the article https://sfcheung.github.io/manymome/articles/get_prod.html

This function is not intended to be used by users. It is exported such that advanced users or developers can use it.

Value

If at least one product term is found, it returns a list with these elements:

- prod: The names of the product terms found.
- b: The coefficients of these product terms.
- w: The variable, other than x, in each product term.
- x: The x-variable, that is, where the path starts.
- y: The y-variable, that is, where the path ends.

It returns NA if no product term is found along the path.

Examples

```
dat <- modmed_x1m3w4y1
library(lavaan)
mod <-
"
m1 ~ x    + w1 + x:w1
m2 ~ m1   + w2 + m1:w2
m3 ~ m2
y ~ m3   + w4 + m3:w4 + x + w3 + x:w3 + x:w4
"
```

```

fit <- sem(model = mod,
            data = dat,
            meanstructure = TRUE,
            fixed.x = FALSE)

# One product term
get_prod(x = "x", y = "m1", fit = fit)
# Two product terms
get_prod(x = "x", y = "y", fit = fit)
# No product term
get_prod(x = "m2", y = "m3", fit = fit)

```

index_of_mome

Index of Moderated Mediation and Index of Moderated Moderated Mediation

Description

It computes the index of moderated mediation and the index of moderated moderated mediation proposed by Hayes (2015, 2018).

Usage

```

index_of_mome(
  x,
  y,
  m = NULL,
  w = NULL,
  fit = NULL,
  boot_ci = FALSE,
  level = 0.95,
  boot_out = NULL,
  R = 100,
  seed = NULL,
  progress = TRUE,
  mc_ci = FALSE,
  mc_out = NULL,
  ci_type = NULL,
  ci_out = NULL,
  boot_type = c("perc", "bc"),
  skip_indicators = TRUE,
  ...
)

index_of_momome(
  x,
  y,

```

```

m = NULL,
w = NULL,
z = NULL,
fit = NULL,
boot_ci = FALSE,
level = 0.95,
boot_out = NULL,
R = 100,
seed = NULL,
progress = TRUE,
mc_ci = FALSE,
mc_out = NULL,
ci_type = NULL,
ci_out = NULL,
boot_type = c("perc", "bc"),
skip_indicators = TRUE,
...
)

```

Arguments

x	Character. The name of the predictor at the start of the path.
y	Character. The name of the outcome variable at the end of the path.
m	A vector of the variable names of the mediator(s). The path goes from the first mediator successively to the last mediator. If NULL, the default, the path goes from x to y.
w	Character. The name of the moderator.
fit	The fit object. Can be a lavaan::lavaan-class object, a list of lm() outputs, or an object created by lm2list() . It can also be a lavaan.mi object returned by lavaan.mi::lavaan.mi() or its wrapper, such as lavaan.mi::sem.mi() .
boot_ci	Logical. Whether bootstrap confidence interval will be formed. Default is FALSE.
level	The level of confidence for the bootstrap confidence interval. Default is .95.
boot_out	If boot_ci is TRUE, users can supply pregenerated bootstrap estimates. This can be the output of do_boot() . For indirect_effect() and cond_indirect_effects() , this can be the output of a previous call to cond_indirect_effects() , indirect_effect() , or cond_indirect() with bootstrap confidence intervals requested. These stored estimates will be reused such that there is no need to do bootstrapping again. If not supplied, the function will try to generate them from fit.
R	Integer. If boot_ci is TRUE, boot_out is NULL, and bootstrap standard errors not requested if fit is a lavaan-class object, this function will do bootstrapping on fit. R is the number of bootstrap samples. Default is 100. For Monte Carlo simulation, this is the number of replications.
seed	If bootstrapping or Monte Carlo simulation is conducted, this is the seed for the bootstrapping or simulation. Default is NULL and seed is not set.
progress	Logical. Display bootstrapping progress or not. Default is TRUE.

mc_ci	Logical. Whether Monte Carlo confidence interval will be formed. Default is FALSE.
mc_out	If <code>mc_ci</code> is TRUE, users can supply pregenerated Monte Carlo estimates. This can be the output of <code>do_mc()</code> . For <code>indirect_effect()</code> and <code>cond_indirect_effects()</code> , this can be the output of a previous call to <code>cond_indirect_effects()</code> , <code>indirect_effect()</code> , or <code>cond_indirect()</code> with Monte Carlo confidence intervals requested. These stored estimates will be reused such that there is no need to do Monte Carlo simulation again. If not supplied, the function will try to generate them from <code>fit</code> .
ci_type	The type of confidence intervals to be formed. Can be either "boot" (bootstrapping) or "mc" (Monte Carlo). If not supplied or is NULL, will check other arguments (e.g, <code>boot_ci</code> and <code>mc_ci</code>). If supplied, will override <code>boot_ci</code> and <code>mc_ci</code> .
ci_out	If <code>ci_type</code> is supplied, this is the corresponding argument. If <code>ci_type</code> is "boot", this argument will be used as <code>boot_out</code> . If <code>ci_type</code> is "mc", this argument will be used as <code>mc_out</code> .
boot_type	If bootstrap confidence interval is to be formed, the type of bootstrap confidence interval. The supported types are "perc" (percentile bootstrap confidence interval, the default and recommended type) and "bc" (bias-corrected, or BC, bootstrap confidence interval).
skip_indicators	Whether observed indicators are skipped from the search for product terms. Default is TRUE.
...	Arguments to be passed to <code>cond_indirect_effects()</code>
z	Character. The name of the second moderator, for computing the index of moderated moderated mediation.

Details

The function `index_of_mome()` computes the *index of moderated mediation* proposed by Hayes (2015). It supports any path in a model with one (and only one) component path moderated. For example, $x \rightarrow m1 \rightarrow m2 \rightarrow y$ with $x \rightarrow m1$ moderated by w . It measures the change in indirect effect when the moderator increases by one unit.

The function `index_of_momome()` computes the *index of moderated moderated mediation* proposed by Hayes (2018). It supports any path in a model, with two component paths moderated, each by one moderator. For example, $x \rightarrow m1 \rightarrow m2 \rightarrow y$ with $x \rightarrow m1$ moderated by w and $m2 \rightarrow y$ moderated by z . It measures the change in the index of moderated mediation of one moderator when the other moderator increases by one unit.

Value

It returns a `cond_indirect_diff`-class object. This class has a `print` method (`print.cond_indirect_diff()`), a `coef` method for extracting the index (`coef.cond_indirect_diff()`), and a `confint` method for extracting the confidence interval if available (`confint.cond_indirect_diff()`).

Functions

- `index_of_mome()`: Compute the index of moderated mediation.
- `index_of_momome()`: Compute the index of moderated moderated mediation.

References

Hayes, A. F. (2015). An index and test of linear moderated mediation. *Multivariate Behavioral Research*, 50(1), 1-22. doi:10.1080/00273171.2014.962683

Hayes, A. F. (2018). Partial, conditional, and moderated moderated mediation: Quantification, inference, and interpretation. *Communication Monographs*, 85(1), 4-40. doi:10.1080/03637751.2017.1352100

See Also

[cond_indirect_effects\(\)](#)

Examples

```
library(lavaan)
dat <- modmed_x1m3w4y1
dat$xw1 <- dat$x * dat$w1
mod <-
"
m1 ~ a * x + f * w1 + d * xw1
y ~ b * m1 + cp * x
ind_mome := d * b
"
fit <- sem(mod, dat,
            meanstructure = TRUE, fixed.x = FALSE,
            se = "none", baseline = FALSE)
est <- parameterEstimates(fit)

# R should be at least 2000 or even 5000 in real research.
# parallel is set to TRUE by default.
# Therefore, in research, the argument parallel can be omitted.
out_mome <- index_of_mome(x = "x", y = "y", m = "m1", w = "w1",
                           fit = fit,
                           boot_ci = TRUE,
                           R = 42,
                           seed = 4314,
                           parallel = FALSE,
                           progress = FALSE)

out_mome
coef(out_mome)
# From lavaan
print(est[19, ], nd = 8)
confint(out_mome)
```

```
library(lavaan)
dat <- modmed_x1m3w4y1
```

```

dat$xw1 <- dat$x * dat$w1
dat$m1w4 <- dat$m1 * dat$w4
mod <-
"
m1 ~ a * x + f1 * w1 + d1 * xw1
y ~ b * m1 + f4 * w4 + d4 * m1w4 + cp * x
ind_momome := d1 * d4
"
fit <- sem(mod, dat,
            meanstructure = TRUE, fixed.x = FALSE,
            se = "none", baseline = FALSE)
est <- parameterEstimates(fit)

# See the example of index_of_mome on how to request
# bootstrap confidence interval.
out_momome <- index_of_momome(x = "x", y = "y", m = "m1",
                                 w = "w1", z = "w4",
                                 fit = fit)
out_momome
coef(out_momome)
print(est[32, ], nd = 8)

```

indirect_effects_from_list

Coefficient Table of an 'indirect_list' Class Object

Description

Create a coefficient table for the point estimates and confidence intervals (if available) in the output of [many_indirect_effects\(\)](#).

Usage

```
indirect_effects_from_list(object, add_sig = TRUE, pvalue = FALSE, se = FALSE)
```

Arguments

object	The output of many_indirect_effects() or other functions that return an object of the class <code>indirect_list</code> .
add_sig	Whether a column of significance test results will be added. Default is TRUE.
pvalue	Logical. If TRUE, asymmetric p -values based on bootstrapping will be added available. Default is FALSE.
se	Logical. If TRUE and confidence intervals are available, the standard errors of the estimates are also added. They are simply the standard deviations of the bootstrap estimates or Monte Carlo simulated values, depending on the method used to form the confidence intervals.

Details

If bootstrapping confidence interval was requested, this method has the option to add p -values computed by the method presented in Asparouhov and Muthén (2021). Note that these p -values is asymmetric bootstrap p -values based on the distribution of the bootstrap estimates. They are not computed based on the distribution under the null hypothesis.

For a p -value of a , it means that a $100(1 - a)\%$ bootstrapping confidence interval will have one of its limits equal to 0. A confidence interval with a higher confidence level will include zero, while a confidence interval with a lower confidence level will exclude zero.

Value

A data frame with the indirect effect estimates and confidence intervals (if available). It also has A string column, "Sig", for #' significant test results if add_sig is TRUE and confidence intervals are available.

References

Asparouhov, A., & Muthén, B. (2021). Bootstrap p-value computation. Retrieved from <https://www.statmodel.com/download/Bootstrap%20-%20Pvalue.pdf>

See Also

[many_indirect_effects\(\)](#)

Examples

```
library(lavaan)
data(data_serial_parallel)
mod <-
"
m11 ~ x + c1 + c2
m12 ~ m11 + x + c1 + c2
m2 ~ x + c1 + c2
y ~ m12 + m2 + m11 + x + c1 + c2
"
fit <- sem(mod, data_serial_parallel,
           fixed.x = FALSE)

# All indirect paths from x to y
paths <- all_indirect_paths(fit,
                           x = "x",
                           y = "y")
paths

# Indirect effect estimates
out <- many_indirect_effects(paths,
                             fit = fit)
out

# Create a data frame of the indirect effect estimates
```

```
out_df <- indirect_effects_from_list(out)
out_df
```

indirect_i

Indirect Effect (No Bootstrapping)

Description

It computes an indirect effect, optionally conditional on the value(s) of moderator(s) if present.

Usage

```
indirect_i(
  x,
  y,
  m = NULL,
  fit = NULL,
  est = NULL,
  implied_stats = NULL,
  wvalues = NULL,
  standardized_x = FALSE,
  standardized_y = FALSE,
  computation_digits = 5,
  prods = NULL,
  get_prods_only = FALSE,
  data = NULL,
  expand = TRUE,
  warn = TRUE,
  allow_mixing_lav_and_obs = TRUE,
  group = NULL,
  est_vcov = NULL,
  df_residual = NULL,
  skip_indicators = TRUE
)
```

Arguments

x	Character. The name of the predictor at the start of the path.
y	Character. The name of the outcome variable at the end of the path.
m	A vector of the variable names of the mediator(s). The path goes from the first mediator successively to the last mediator. If NULL, the default, the path goes from x to y.
fit	The fit object. Currently only supports <code>lavaan::lavaan</code> objects. Support for lists of <code>lm()</code> output is implemented by high level functions such as <code>indirect_effect()</code> and <code>cond_indirect_effects()</code> . It can also be a <code>lavaan.mi</code> object returned by <code>lavaan.mi::lavaan.mi()</code> or its wrapper, such as <code>lavaan.mi::sem.mi()</code> .

est	The output of <code>lavaan::parameterEstimates()</code> . If NULL, the default, it will be generated from <code>fit</code> . If supplied, <code>fit</code> will be ignored.
implied_stats	Implied means, variances, and covariances of observed variables and latent variables (if any), of the form of the output of <code>lavaan::lavInspect()</code> with what set to "implied", but with means extracted with what set to "mean.ov" and "mean.lv". The standard deviations are extracted from this object for standardization. Default is NULL, and implied statistics will be computed from <code>fit</code> if required.
wvalues	A numeric vector of named elements. The names are the variable names of the moderators, and the values are the values to which the moderators will be set to. Default is NULL.
standardized_x	Logical. Whether <code>x</code> will be standardized. Default is FALSE.
standardized_y	Logical. Whether <code>y</code> will be standardized. Default is FALSE.
computation_digits	The number of digits in storing the computation in text. Default is 3.
prods	The product terms found. For internal use.
get_prods_only	IF TRUE, will quit early and return the product terms found. The results can be passed to the <code>prod</code> argument when calling this function. Default is FALSE. For internal use.
data	Data frame (optional). If supplied, it will be used to identify the product terms. For internal use.
expand	Whether products of more than two terms will be searched. TRUE by default. For internal use.
warn	If TRUE, the default, the function will warn against possible misspecification, such as not setting the value of a moderator which moderate one of the component path. Set this to FALSE will suppress these warnings. Suppress them only when the moderators are omitted intentionally.
allow_mixing_lav_and_obs	If TRUE, it accepts a path with both latent variables and observed variables. Default is TRUE.
group	Either the group number as appeared in the <code>summary()</code> or <code>lavaan::parameterEstimates()</code> output of an lavaan-class object, or the group label as used in the lavaan-class object. Used only when the number of groups is greater than one. Default is NULL.
est_vcov	A list of variance-covariance matrix of estimates, one for each response variable (y-variable). Used only for models fitted by <code>stats::lm()</code> for now. It is used to compute the standard error for a path with no mediator, and both <code>x</code> and <code>y</code> are not standardized.
df_residual	A numeric vector of the residual degrees of freedom for the model of each response variable (y-variable). Used only for models fitted by <code>stats::lm()</code> for now. It is used to compute the <i>p</i> -value and confidence interval for a path with no mediator and both <code>x</code> and <code>y</code> are not standardized.
skip_indicators	Whether observed indicators are skipped from the search for product terms. Default is TRUE.

Details

This function is a low-level function called by `indirect_effect()`, `cond_indirect_effects()`, and `cond_indirect()`, which call this function multiple times if bootstrap confidence interval is requested.

This function usually should not be used directly. It is exported for advanced users and developers

Value

It returns an `indirect`-class object. This class has the following methods: `coef.indirect()`, `print.indirect()`. The `confint.indirect()` method is used only when called by `cond_indirect()` or `cond_indirect_effects()`.

See Also

`indirect_effect()`, `cond_indirect_effects()`, and `cond_indirect()`, the high level functions that should usually be used.

Examples

```
library(lavaan)
dat <- modmed_x1m3w4y1
mod <-
"
m1 ~ a1 * x    + b1 * w1 + d1 * x:w1
m2 ~ a2 * m1   + b2 * w2 + d2 * m1:w2
m3 ~ a3 * m2   + b3 * w3 + d3 * m2:w3
y   ~ a4 * m3   + b4 * w4 + d4 * m3:w4
"
fit <- sem(mod, dat, meanstructure = TRUE,
           fixed.x = FALSE, se = "none", baseline = FALSE)
est <- parameterEstimates(fit)

wvalues <- c(w1 = 5, w2 = 4, w3 = 2, w4 = 3)

# Compute the conditional indirect effect by indirect_i()
indirect_1 <- indirect_i(x = "x", y = "y", m = c("m1", "m2", "m3"), fit = fit,
                           wvalues = wvalues)

# Manually compute the conditional indirect effect
indirect_2 <- (est[est$label == "a1", "est"] +
                 wvalues["w1"] * est[est$label == "d1", "est"] *
                 (est[est$label == "a2", "est"] +
                  wvalues["w2"] * est[est$label == "d2", "est"]) *
                 (est[est$label == "a3", "est"] +
                  wvalues["w3"] * est[est$label == "d3", "est"]) *
                 (est[est$label == "a4", "est"] +
                  wvalues["w4"] * est[est$label == "d4", "est"]))
# They should be the same
coef(indirect_1)
indirect_2
```

indirect_proportion	<i>Proportion of Effect Mediated</i>
---------------------	--------------------------------------

Description

It computes the proportion of effect mediated along a pathway.

Usage

```
indirect_proportion(x, y, m = NULL, fit = NULL)
```

Arguments

x	The name of the x variable. Must be supplied as a quoted string.
y	The name of the y variable. Must be supplied as a quoted string.
m	A vector of the variable names of the mediator(s). The path goes from the first mediator successively to the last mediator. Cannot be NULL for this function.
fit	The fit object. Can be a <code>lavaan::lavaan</code> object or a list of <code>lm()</code> outputs. It can also be a <code>lavaan.mi</code> object returned by <code>lavaan.mi::lavaan.mi()</code> or its wrapper, such as <code>lavaan.mi::sem.mi()</code> .

Details

The proportion of effect mediated along a path from x to y is the indirect effect along this path divided by the total effect from x to y (Alwin & Hauser, 1975). This total effect is equal to the sum of all indirect effects from x to y and the direct effect from x to y.

To ensure that the proportion can indeed be interpreted as a proportion, this function computes the proportion only if the signs of all the indirect and direct effects from x to y are same (i.e., all effects positive or all effects negative).

Value

An `indirect_proportion` class object. It is a list-like object with these major elements:

- proportion: The proportion of effect mediated.
- x: The name of the x-variable.
- y: The name of the y-variable.
- m: A character vector of the mediator(s) along a path. The path runs from the first element to the last element.

This class has a `print` method and a `coef` method.

References

Alwin, D. F., & Hauser, R. M. (1975). The decomposition of effects in path analysis. *American Sociological Review*, 40(1), 37. doi:10.2307/2094445

See Also

[print.indirect_proportion\(\)](#) for the `print` method, and [coef.indirect_proportion\(\)](#) for the `coef` method.

Examples

```
library(lavaan)
dat <- data_med
head(dat)
mod <-
"
m ~ x + c1 + c2
y ~ m + x + c1 + c2
"
fit <- sem(mod, dat, fixed.x = FALSE)
out <- indirect_proportion(x = "x",
                           y = "y",
                           m = "m",
                           fit = fit)
out
```

lm2boot_out

*Bootstrap Estimates for lm Outputs***Description**

Generate bootstrap estimates for models in a list of 'lm' outputs.

Usage

```
lm2boot_out(
  outputs,
  R = 100,
  seed = NULL,
  progress = TRUE,
  compute_implied_stats = TRUE
)

lm2boot_out_parallel(
  outputs,
  R = 100,
  seed = NULL,
  parallel = FALSE,
  ncores = max(parallel::detectCores(logical = FALSE) - 1, 1),
  make_cluster_args = list(),
  progress = TRUE,
  compute_implied_stats = TRUE
)
```

Arguments

outputs	A list of <code>lm</code> class objects, or the output of <code>lm2list()</code> (i.e., an <code>lm_list</code> -class object).
R	The number of bootstrap samples. Default is 100.
seed	The seed for the random resampling. Default is <code>NULL</code> .
progress	Logical. Display progress or not. Default is <code>TRUE</code> .
compute_implied_stats	If <code>TRUE</code> , default, implied statistics will be computed for each bootstrap sample. Letting users to disable this is an experimental features to let the process run faster.
parallel	Logical. Whether parallel processing will be used. Default is <code>NULL</code> .
ncores	Integer. The number of CPU cores to use when <code>parallel</code> is <code>TRUE</code> . Default is the number of non-logical cores minus one (one minimum). Will raise an error if greater than the number of cores detected by <code>parallel::detectCores()</code> . If <code>ncores</code> is set, it will override <code>make_cluster_args</code> .
make_cluster_args	A named list of additional arguments to be passed to <code>parallel::makeCluster()</code> . For advanced users. See <code>parallel::makeCluster()</code> for details. Default is <code>list()</code> .

Details

This function is for advanced users. `do_boot()` is a function users should try first because `do_boot()` has a general interface for input-specific functions like this one.

It does nonparametric bootstrapping to generate bootstrap estimates of the regression coefficients in the regression models of a list of `lm()` outputs, or an `lm_list`-class object created by `lm2list()`. The stored estimates can be used by `indirect_effect()`, `cond_indirect_effects()`, and related functions in forming bootstrapping confidence intervals for effects such as indirect effect and conditional indirect effects.

This approach removes the need to repeat bootstrapping in each call to `indirect_effect()`, `cond_indirect_effects()`, and related functions. It also ensures that the same set of bootstrap samples is used in all subsequent analyses.

Value

A `boot_out`-class object that can be used for the `boot_out` argument of `indirect_effect()`, `cond_indirect_effects()`, and related functions for forming bootstrapping confidence intervals. The object is a list with the number of elements equal to the number of bootstrap samples. Each element is a list of the parameter estimates and sample variances and covariances of the variables in each bootstrap sample.

Functions

- `lm2boot_out()`: Generate bootstrap estimates using one process (serial, without parallelization).
- `lm2boot_out_parallel()`: Generate bootstrap estimates using parallel processing.

See Also

[do_boot\(\)](#), the general purpose function that users should try first before using this function.

Examples

```
data(data_med_mod_ab1)
dat <- data_med_mod_ab1
lm_m <- lm(m ~ x*w + c1 + c2, dat)
lm_y <- lm(y ~ m*w + x + c1 + c2, dat)
lm_out <- lm2list(lm_m, lm_y)
# In real research, R should be 2000 or even 5000
# In real research, no need to set progress to FALSE
# Progress is displayed by default.
lm_boot_out <- lm2boot_out(lm_out, R = 100, seed = 1234,
                           progress = FALSE)
out <- cond_indirect_effects(wlevels = "w",
                             x = "x",
                             y = "y",
                             m = "m",
                             fit = lm_out,
                             boot_ci = TRUE,
                             boot_out = lm_boot_out)
out
```

lm2list

Join 'lm()' Output to Form an 'lm_list'-Class Object

Description

The resulting model can be used by [indirect_effect\(\)](#), [cond_indirect_effects\(\)](#), or [cond_indirect\(\)](#) as a path method, as if fitted by [lavaan::sem\(\)](#).

Usage

```
lm2list(...)
```

Arguments

... The [lm\(\)](#) outputs to be grouped in a list.

Details

If a path model with mediation and/or moderation is fitted by a set of regression models using [lm\(\)](#), this function can combine them to an object of the class `lm_list` that represents a path model, as one fitted by structural equation model functions such as [lavaan::sem\(\)](#). This class of object can be used by some functions, such as [indirect_effect\(\)](#), [cond_indirect_effects\(\)](#), and [cond_indirect\(\)](#) as if they were the output of fitting a path model, with the regression coefficients treated as path coefficients.

The regression outputs to be combined need to meet the following requirements:

- All models must be connected to at least one another model. That is, a regression model must either have (a) at least one predictor that is the outcome variable of another model, or (b) its outcome variable the predictor of another model.
- All models must be fitted to the same sample. This implies that the sample size must be the same in all analysis.

Value

It returns an `lm_list`-class object that forms a path model represented by a set of regression models. This class has a `summary` method that shows the summary of each regression model stored (see `summary.lm_list()`), and a `print` method that prints the models stored (see `print.lm_list()`).

See Also

`summary.lm_list()` and `print.lm_list()` for related methods, `indirect_effect()` and `cond_indirect_effects()` which accept `lm_list`-class objects as input.

Examples

lm_from_lavaan_list 'lavaan'-class to 'lm_from_lavaan_list'-Class

Description

Converts the regression models in a lavaan-class model to an lm_from_lavaan_list-class object.

Usage

```
lm_from_lavaan_list(fit)
```

Arguments

fit	A lavaan-class object, usually the output of <code>lavaan::lavaan()</code> or its wrappers.
-----	---

Details

It identifies all dependent variables in a lavaan model and creates an lm_from_lavaan-class object for each of them.

This is an advanced helper used by `plot.cond_indirect_effects()`. Exported for advanced users and developers.

Value

An lm_from_lavaan_list-class object, which is a list of lm_from_lavaan objects. It has a predict-method (`predict.lm_from_lavaan_list()`) for computing the predicted values from one variable to another.

See Also

[predict.lm_from_lavaan_list](#)

Examples

```
library(lavaan)
data(data_med)
mod <-
"
m ~ a * x + c1 + c2
y ~ b * m + x + c1 + c2
"
fit <- sem(mod, data_med, fixed.x = FALSE)
fit_list <- lm_from_lavaan_list(fit)
tmp <- data.frame(x = 1, c1 = 2, c2 = 3, m = 4)
predict(fit_list, x = "x", y = "y", m = "m", newdata = tmp)
```

Description

Mathematic operators for 'indirect'-class object, the output of `indirect_effect()` and `cond_indirect()`.

Usage

```
## S3 method for class 'indirect'
e1 + e2

## S3 method for class 'indirect'
e1 - e2
```

Arguments

e1	An 'indirect'-class object.
e2	An 'indirect'-class object.

Details

For now, only + operator and - operator are supported. These operators can be used to estimate and test a function of effects between the same pair of variables.

For example, they can be used to compute and test the total effects along different paths. They can also be used to compute and test the difference between the effects along two paths.

The operators will check whether an operation is valid. An operation is not valid if

1. the two paths do not start from the same variable,
2. the two paths do not end at the same variable,
3. moderators are involved but they are not set to the same values in both objects, and
4. bootstrap estimates stored in `boot_out`, if any, are not identical.
5. Monte Carlo simulated estimates stored in `mc_out`, if any, are not identical.

If bootstrap estimates are stored and both objects used the same type of bootstrap confidence interval, that type will be used. Otherwise, percentile bootstrap confidence interval, the recommended method, will be used.

Multigroup Models:

Since Version 0.1.14.2, support for multigroup models has been added for models fitted by `lavaan`. Both bootstrapping and Monte Carlo confidence intervals are supported. These operators can be used to compute and test the difference of an indirect effect between two groups. This can also be used to compute and test the difference between a function of effects between groups, for example, the total indirect effects between two groups.

The operators are flexible and allow users to do many possible computations. Therefore, users need to make sure that the function of effects is meaningful.

Value

An 'indirect'-class object with a list of effects stored. See [indirect_effect\(\)](#) on details for this class.

See Also

[indirect_effect\(\)](#) and [cond_indirect\(\)](#)

Examples

```
library(lavaan)
dat <- modmed_x1m3w4y1
mod <-
"
m1 ~ a1 * x + d1 * w1 + e1 * x:w1
m2 ~ m1 + a2 * x
y ~ b1 * m1 + b2 * m2 + cp * x
"
fit <- sem(mod, dat,
            meanstructure = TRUE, fixed.x = FALSE,
            se = "none", baseline = FALSE)
est <- parameterEstimates(fit)
hi_w1 <- mean(dat$w1) + sd(dat$w1)

# Examples for cond_indirect():

# Conditional effect from x to m1 when w1 is 1 SD above mean
out1 <- cond_indirect(x = "x", y = "y", m = c("m1", "m2"),
                       wvalues = c(w1 = hi_w1), fit = fit)
out2 <- cond_indirect(x = "x", y = "y", m = c("m2"),
                       wvalues = c(w1 = hi_w1), fit = fit)
out3 <- cond_indirect(x = "x", y = "y",
                       wvalues = c(w1 = hi_w1), fit = fit)

out12 <- out1 + out2
out12
out123 <- out1 + out2 + out3
out123
coef(out1) + coef(out2) + coef(out3)

# Multigroup model with indirect effects

dat <- data_med_mg
mod <-
"
m ~ x + c1 + c2
y ~ m + x + c1 + c2
"
fit <- sem(mod, dat, meanstructure = TRUE, fixed.x = FALSE, se = "none", baseline = FALSE,
           group = "group")

# If a model has more than one group,
```

```

# the argument 'group' must be set.
ind1 <- indirect_effect(x = "x",
                        y = "y",
                        m = "m",
                        fit = fit,
                        group = "Group A")
ind1
ind2 <- indirect_effect(x = "x",
                        y = "y",
                        m = "m",
                        fit = fit,
                        group = 2)
ind2

# Compute the difference in indirect effects between groups
ind2 - ind1

```

merge_mod_levels*Merge the Generated Levels of Moderators***Description**

Merge the levels of moderators generated by [mod_levels\(\)](#) into a data frame.

Usage

```
merge_mod_levels(...)
```

Arguments

... The output from [mod_levels\(\)](#), or a list of levels generated by [mod_levels_list\(\)](#).

Details

It merges the levels of moderators generated by [mod_levels\(\)](#) into a data frame, with each row represents a combination of the levels. The output is to be used by [cond_indirect_effects\(\)](#).

Users usually do not need to use this function because [cond_indirect_effects\(\)](#) will merge the levels internally if necessary. This function is used when users need to customize the levels for each moderator and so cannot use [mod_levels_list\(\)](#) or the default levels in [cond_indirect_effects\(\)](#).

Value

A wlevels-class object, which is a data frame of the combinations of levels, with additional attributes about the levels.

See Also

[mod_levels\(\)](#) on generating the levels of a moderator.

Examples

```
data(data_med_mod_ab)
dat <- data_med_mod_ab
# Form the levels from a list of lm() outputs
lm_m <- lm(m ~ x*w1 + c1 + c2, dat)
lm_y <- lm(y ~ m*w2 + x + w1 + c1 + c2, dat)
lm_out <- lm2list(lm_m, lm_y)
w1_levels <- mod_levels(lm_out, w = "w1")
w1_levels
w2_levels <- mod_levels(lm_out, w = "w2")
w2_levels
merge_mod_levels(w1_levels, w2_levels)
```

modmed_x1m3w4y1

Sample Dataset: Moderated Serial Mediation

Description

Generated from a serial mediation model with one predictor, three mediators, and one outcome variable, with one moderator in each stage.

Usage

modmed_x1m3w4y1

Format

A data frame with 200 rows and 11 variables:

- x** Predictor. Numeric.
- w1** Moderator 1. Numeric.
- w2** Moderator 2. Numeric.
- w3** Moderator 3. Numeric.
- w4** Moderator 4. Numeric.
- m1** Mediator 1. Numeric.
- m2** Mediator 2. Numeric.
- m3** Mediator 3. Numeric.
- y** Outcome variable. Numeric.
- gp** Three values: "earth", "mars", "venus". String.
- city** Four values: "alpha", "beta", "gamma", "sigma". String.

mod_levels	<i>Create Levels of Moderators</i>
------------	------------------------------------

Description

Create levels of moderators to be used by `indirect_effect()`, `cond_indirect_effects()`, and `cond_indirect()`.

Usage

```
mod_levels(
  w,
  fit,
  w_type = c("auto", "numeric", "categorical"),
  w_method = c("sd", "percentile"),
  sd_from_mean = c(-1, 0, 1),
  percentiles = c(0.16, 0.5, 0.84),
  extract_gp_names = TRUE,
  prefix = NULL,
  values = NULL,
  reference_group_label = NULL,
  descending = TRUE
)

mod_levels_list(
  ...,
  fit,
  w_type = "auto",
  w_method = "sd",
  sd_from_mean = NULL,
  percentiles = NULL,
  extract_gp_names = TRUE,
  prefix = NULL,
  descending = TRUE,
  merge = FALSE
)
```

Arguments

- w** Character. The names of the moderator. If the moderator is categorical with 3 or more groups, this is the vector of the indicator variables.
- fit** The fit object. Can be a `lavaan::lavaan` object or a list of `lm()` outputs. It can also be a `lavaan.mi` object returned by `lavaan.mi::lavaan.mi()` or its wrapper, such as `lavaan.mi::sem.mi()`. If it is a single model fitted by `lm()`, it will be automatically converted to a list by `lm2list()`.
- w_type** Character. Whether the moderator is a "numeric" variable or a "categorical" variable. If "auto", the function will try to determine the type automatically.

w_method	Character, either "sd" or "percentile". If "sd", the levels are defined by the distance from the mean in terms of standard deviation. If "percentile", the levels are defined in percentiles.
sd_from_mean	A numeric vector. Specify the distance in standard deviation from the mean for each level. Default is <code>c(-1, 0, 1)</code> for <code>mod_levels()</code> . For <code>mod_levels_list()</code> , the default is <code>c(-1, 0, 1)</code> when there is only one moderator, and <code>c(-1, 1)</code> when there are more than one moderator. Ignored if <code>w_method</code> is not equal to "sd".
percentiles	A numeric vector. Specify the percentile (in proportion) for each level. Default is <code>c(.16, .50, .84)</code> for <code>mod_levels()</code> , corresponding approximately to one standard deviation below mean, mean, and one standard deviation above mean in a normal distribution. For <code>mod_levels_list()</code> , default is <code>c(.16, .50, .84)</code> if there is one moderator, and <code>c(.16, .84)</code> when there are more than one moderator. Ignored if <code>w_method</code> is not equal to "percentile".
extract_gp_names	Logical. If TRUE, the default, the function will try to determine the name of each group from the variable names.
prefix	Character. If <code>extract_gp_names</code> is TRUE and <code>prefix</code> is supplied, it will be removed from the variable names to create the group names. Default is NULL, and the function will try to determine the prefix automatically.
values	For numeric moderators, a numeric vector. These are the values to be used and will override other options. For categorical moderators, a named list of numeric vector, each vector has length equal to the number of indicator variables. If the vector is named, the names will be used to label the values. For example, if set to <code>list(gp1 = c(0, 0), gp3 = c(0, 1))</code> , two levels will be returned, one named <code>gp1</code> with the indicator variables equal to 0 and 0, the other named <code>gp3</code> with the indicator variables equal to 0 and 1. Default is NULL.
reference_group_label	For categorical moderator, if the label for the reference group (group with all indicators equal to zero) cannot be determined, the default label is "Reference". To change it, set <code>reference_group_label</code> to the desired label. Ignored if <code>values</code> is set.
descending	If TRUE (default), the rows are sorted in descending order for numerical moderators: The highest value on the first row and the lowest values on the last row. For user supplied values, the first value is on the last row and the last value is on the first row. If FALSE, the rows are sorted in ascending order.
...	The names of moderators variables. For a categorical variable, it should be a vector of variable names.
merge	If TRUE, <code>mod_levels_list()</code> will call <code>merge_mod_levels()</code> and return the merged levels. Default is FALSE.

Details

It creates values of a moderator that can be used to compute conditional effect or conditional indirect effect. By default, for a numeric moderator, it uses one standard deviation below mean, mean, and one standard deviation above mean. The percentiles of these three levels in a normal distribution (16th, 50th, and 84th) can also be used. For categorical variable, it will simply collect the unique categories in the data.

The generated levels are then used by `cond_indirect()` and `cond_indirect_effects()`.

If a model has more than one moderator, `mod_levels_list()` can be used to generate combinations of levels. The output can then be passed to `cond_indirect_effects()` to compute the conditional effects or conditional indirect effects for all the combinations.

Value

`mod_levels()` returns a `wlevels`-class object which is a data frame with additional attributes about the levels.

`mod_levels_list()` returns a list of `wlevels`-class objects, or a `wlevels`-class object which is a data frame of the merged levels if `merge = TRUE`.

Functions

- `mod_levels()`: Generate levels for one moderator.
- `mod_levels_list()`: Generate levels for several moderators.

See Also

`cond_indirect_effects()` for computing conditional indirect effects; `merge_mod_levels()` for merging levels of moderators.

Examples

```
library(lavaan)
data(data_med_mod_ab)
dat <- data_med_mod_ab
# Form the levels from a list of lm() outputs
lm_m <- lm(m ~ x*w1 + c1 + c2, dat)
lm_y <- lm(y ~ m*w2 + x + w1 + c1 + c2, dat)
lm_out <- lm2list(lm_m, lm_y)
w1_levels <- mod_levels(lm_out, w = "w1")
w1_levels
w2_levels <- mod_levels(lm_out, w = "w2")
w2_levels
# Indirect effect from x to y through m, at the first levels of w1 and w2
cond_indirect(x = "x", y = "y", m = "m",
               fit = lm_out,
               wvalues = c(w1 = w1_levels$w1[1],
                           w2 = w2_levels$w2[1]))
# Can form the levels based on percentiles
w1_levels2 <- mod_levels(lm_out, w = "w1", w_method = "percentile")
w1_levels2
# Form the levels from a lavaan output
# Compute the product terms before fitting the model
dat$mw2 <- dat$m * dat$w2
mod <-
"
m ~ x + w1 + x:w1 + c1 + c2
y ~ m + x + w1 + w2 + mw2 + c1 + c2
"
```

```

fit <- sem(mod, dat, fixed.x = FALSE)
cond_indirect(x = "x", y = "y", m = "m",
              fit = fit,
              wvalues = c(w1 = w1_levels$w1[1],
                          w2 = w2_levels$w2[1]))
# Can pass all levels to cond_indirect_effects()
# First merge the levels by merge_mod_levels()
w1w2_levels <- merge_mod_levels(w1_levels, w2_levels)
cond_indirect_effects(x = "x", y = "y", m = "m",
                      fit = fit,
                      wlevels = w1w2_levels)

# mod_levels_list() forms a combinations of levels in one call
# It returns a list, by default.
# Form the levels from a list of lm() outputs
# "merge = TRUE" is optional. cond_indirect_effects will merge the levels
# automatically.
w1w2_levels <- mod_levels_list("w1", "w2", fit = fit, merge = TRUE)
w1w2_levels
cond_indirect_effects(x = "x", y = "y", m = "m",
                      fit = fit, wlevels = w1w2_levels)
# Can work without merge = TRUE:
w1w2_levels <- mod_levels_list("w1", "w2", fit = fit)
w1w2_levels
cond_indirect_effects(x = "x", y = "y", m = "m",
                      fit = fit, wlevels = w1w2_levels)

```

plot.cond_indirect_effects

Plot Conditional Effects

Description

Plot the conditional effects for different levels of moderators.

Usage

```

## S3 method for class 'cond_indirect_effects'
plot(
  x,
  x_label,
  w_label = "Moderator(s)",
  y_label,
  title,

```

```

x_from_mean_in_sd = 1,
x_method = c("sd", "percentile"),
x_percentiles = c(0.16, 0.84),
x_sd_to_percentiles = NA,
note_standardized = TRUE,
no_title = FALSE,
line_width = 1,
point_size = 5,
graph_type = c("default", "tumble"),
use_implied_stats = TRUE,
facet_grid_cols = NULL,
facet_grid_rows = NULL,
facet_grid_args = list(as.table = FALSE, labeller = "label_both"),
digits = 4,
...
)

```

Arguments

<code>x</code>	The output of <code>cond_indirect_effects()</code> . (Named <code>x</code> because it is required in the naming of arguments of the plot generic function.)
<code>x_label</code>	The label for the X-axis. Default is the value of the predictor in the output of <code>cond_indirect_effects()</code> .
<code>w_label</code>	The label for the legend for the lines. Default is "Moderator(s)".
<code>y_label</code>	The label for the Y-axis. Default is the name of the response variable in the model.
<code>title</code>	The title of the graph. If not supplied, it will be generated from the variable names or labels (in <code>x_label</code> , <code>y_label</code> , and <code>w_label</code>). If "", no title will be printed. This can be used when the plot is for manuscript submission and figures are required to have no titles.
<code>x_from_mean_in_sd</code>	How many SD from mean is used to define "low" and "high" for the focal variable. Default is 1.
<code>x_method</code>	How to define "high" and "low" for the focal variable levels. Default is in terms of the standard deviation of the focal variable, "sd". If equal to "percentile", then the percentiles of the focal variable in the dataset is used. If the focal variable is a latent variable, only "sd" can be used.
<code>x_percentiles</code>	If <code>x_method</code> is "percentile", then this argument specifies the two percentiles to be used, divided by 100. It must be a vector of two numbers. The default is <code>c(.16, .84)</code> , the 16th and 84th percentiles, which corresponds approximately to one SD below and above mean for a normal distribution, respectively.
<code>x_sd_to_percentiles</code>	If <code>x_method</code> is "percentile" and this argument is set to a number, this number will be used to determine the percentiles to be used. The lower percentile is the percentile in a normal distribution that is <code>x_sd_to_percentiles</code> SD below the mean. The upper percentile is the percentile in a normal distribution that is <code>x_sd_to_percentiles</code> SD above the mean. Therefore, if <code>x_sd_to_percentiles</code>

	is set to 1, then the lower and upper percentiles are 16th and 84th, respectively. Default is NA.
note_standardized	If TRUE, will check whether a variable has SD nearly equal to one. If yes, will report this in the plot. Default is TRUE.
no_title	If TRUE, title will be suppressed. Default is FALSE.
line_width	The width of the lines as used in <code>ggplot2::geom_segment()</code> . Default is 1.
point_size	The size of the points as used in <code>ggplot2::geom_point()</code> . Default is 5.
graph_type	If "default", the typical line-graph with equal end-points will be plotted. If "tumble", then the tumble graph proposed by Bodner (2016) will be plotted. Default is "default" for single-group models, and "tumble" for multigroup models.
use_implied_stats	For a multigroup model, if TRUE, the default, model implied statistics will be used in computing the means and SDs, which take into equality constraints, if any. If FALSE, then the raw data is used to compute the means and SDs. For latent variables, model implied statistics are always used.
facet_grid_cols, facet_grid_rows	If either or both of them are set to character vector(s) of moderator names, then <code>ggplot2::facet_grid()</code> will be used to plot the graph, with <code>facet_grid_cols</code> used as cols and <code>facet_grid_rows</code> used as rows when calling <code>ggplot2::facet_grid()</code> .
facet_grid_args	The list of arguments to be used in calling <code>ggplot2::facet_grid()</code> . Ignored if <code>ggplot2::facet_grid()</code> is not used.
digits	The number of decimal places to be printed for numerical moderators when <code>facet_grid</code> is used. Default is 4.
...	Additional arguments. Ignored.

Details

This function is a plot method of the output of `cond_indirect_effects()`. It will use the levels of moderators in the output.

It plots the conditional effect from `x` to `y` in a model for different levels of the moderators. For multigroup models, the group will be the 'moderator' and one line is drawn for each group.

It does not support conditional indirect effects. If there is one or more mediators in `x`, it will raise an error.

Multigroup Models:

Since Version 0.1.14.2, support for multigroup models has been added for models fitted by `lavaan`. If the effect for each group is drawn, the `graph_type` is automatically switched to "tumble" and the means and SDs in each group will be used to determine the locations of the points.

If the multigroup model has any equality constraints, the implied means and/or SDs may be different from those of the raw data. For example, the mean of the `x`-variable may be constrained to be equal in this model. To plot the tumble graph using the model implied means and SDs, set `use_implied_stats` to TRUE.

Latent Variables:

A path that involves a latent x-variable and/or a latent y-variable can be plotted. Because the latent variables have no observed data, the model implied statistics will always be used to get the means and SDs to compute values such as the low and high points of the x-variable.

Value

A ggplot2 graph. Plotted if not assigned to a name. It can be further modified like a usual ggplot2 graph.

References

Bodner, T. E. (2016). Tumble graphs: Avoiding misleading end point extrapolation when graphing interactions from a moderated multiple regression analysis. *Journal of Educational and Behavioral Statistics*, 41(6), 593-604. [doi:10.3102/1076998616657080](https://doi.org/10.3102/1076998616657080)

See Also

[cond_indirect_effects\(\)](#)

Examples

```
library(lavaan)
dat <- modmed_x1m3w4y1
n <- nrow(dat)
set.seed(860314)
dat$gp <- sample(c("gp1", "gp2", "gp3"), n, replace = TRUE)
dat <- cbind(dat, factor2var(dat$gp, prefix = "gp", add_rownames = FALSE))

# Categorical moderator

mod <-
"
m3 ~ m1 + x + gpgp2 + gpgp3 + x:gpgp2 + x:gpgp3
y ~ m2 + m3 + x
"
fit <- sem(mod, dat, meanstructure = TRUE, fixed.x = FALSE)
out_mm_1 <- mod_levels(c("gpgp2", "gpgp3"),
                       sd_from_mean = c(-1, 1),
                       fit = fit)
out_1 <- cond_indirect_effects(wlevels = out_mm_1, x = "x", y = "m3", fit = fit)
plot(out_1)
plot(out_1, graph_type = "tumble")

# Numeric moderator

dat <- modmed_x1m3w4y1
mod2 <-
"
m3 ~ m1 + x + w1 + x:w1
y ~ m3 + x
"
```

```

fit2 <- sem(mod2, dat, meanstructure = TRUE, fixed.x = FALSE)
out_mm_2 <- mod_levels("w1",
                        w_method = "percentile",
                        percentiles = c(.16, .84),
                        fit = fit2)
out_mm_2
out_2 <- cond_indirect_effects(wlevels = out_mm_2, x = "x", y = "m3", fit = fit2)
plot(out_2)
plot(out_2, graph_type = "tumble")

# Multigroup models

dat <- data_med_mg
mod <-
"
m ~ x + c1 + c2
y ~ m + x + c1 + c2
"
fit <- sem(mod, dat, meanstructure = TRUE, fixed.x = FALSE, se = "none", baseline = FALSE,
           group = "group")

# For a multigroup model, group will be used as
# a moderator
out <- cond_indirect_effects(x = "m",
                               y = "y",
                               fit = fit)
out
plot(out)

```

plot.q_mediation *Plot Method for the Output of 'q_mediation' Family*

Description

Plot the path model fitted by the family of 'q_mediation' functions.

Usage

```

## S3 method for class 'q_mediation'
plot(
  x,
  standardized = FALSE,
  size_variables = NULL,
  size_path_labels = NULL,
  nchar_variables = NULL,
  nchar_path_labels = NULL,

```

```

  digits = 2,
  rsquares = TRUE,
  sigs = TRUE,
  margins = c(5, 5, 5, 5),
  v_pos = c("middle", "lower", "upper"),
  v_preference = c("upper", "lower"),
  print_indirect = TRUE,
  indirect_standardized = c("none", "stdx", "stdy", "stdxy"),
  size_indirect = 1,
  plot_now = TRUE,
  ...
  )

  indirect_on_plot(
    q_meditation_output = NULL,
    digits = 2,
    size_indirect = 1,
    indirect_standardized = c("none", "stdx", "stdy", "stdxy"),
    margins = c(5, 5, 5, 5),
    original_plot = NULL
  )

```

Arguments

x The output of [q_meditation\(\)](#), [q_simple_meditation\(\)](#), [q_serial_meditation\(\)](#), and [q_parallel_meditation\(\)](#). (Named x because it is required in the naming of arguments of the plot generic function.)

standardized Logical. If TRUE, betaS in the printout of [q_meditation\(\)](#) family will be used in the figure, with only numerical variables standardized. If FALSE, the default, then the original (unstandardized) coefficients will be used.

size_variables The size of the observed variables (the "rectangles"), to be passed to sizeMan of [semPlot::semPaths\(\)](#). Default is NULL and the size is determined internally based on the number of variables.

size_path_labels The size of the edge labels (parameter estimates), to be passed to edge.label.cex of [semPlot::semPaths\(\)](#). Default is NULL and the size is determined internally based on the number of variables in the plot.

nchar_variables The number of characters to be displayed for each variable. To be passed to nCharNodes of [semPlot::semPaths\(\)](#). Default is NULL, equivalent to 0 for nCharNodes, to disable abbreviating the variable names.

nchar_path_labels The number of characters to be displayed for each label for a path. To be passed to nCharEdges of [semPlot::semPaths\(\)](#). Default is NULL, equivalent to 0 for nCharEdges, to disable abbreviating the labels.

digits The number of digits to be printed after the decimals. To be passed to nDigits of [semPlot::semPaths\(\)](#). Default is 2.

rsquares	Logical. If TRUE, the default, R-squares will be drawn instead of error variances for mediators and outcome variables (the y variables).
sigs	Logical. If TRUE, the default, significance test results will be marked by asterisks, based on the same <i>p</i> -values for R-squares displayed when printing the output of the <code>q_meditation()</code> family.
margins	The margins of the plot. A numeric vector of four values: bottom, left, top, and right. Passed to the <code>mar</code> argument of <code>semPlot::semPaths()</code> .
v_pos	How the mediators are to be positioned vertically. If set to "middle", with one x variable and one y variable, the mediators will tend to be placed around the horizontal line joining x and y. If set to "upper", they will be placed along or above this line. If set to "lower", they will be placed along or below this line. Note that this only affects the initial positions. The positions will be further adjusted based on the free paths in the model. This argument is to be passed to <code>semtools::auto_layout_meditation()</code> .
v_preference	The preference in shifting the mediators upward ("upper") or downward ("lower") to avoid blocking or overlapping with any paths in the models. It is used only when <code>v_pos</code> is "middle". If <code>v_pos</code> is "lower", then <code>v_preference</code> will be forced to be "lower". If <code>v_pos</code> is "upper", then <code>v_preference</code> will be forced to be "upper". This argument is to be passed to <code>semtools::auto_layout_meditation()</code> .
print_indirect	Logical. Whether the indirect effect(s), and total indirect effect if applicable, will be printed on the plot. Default is TRUE. Used only if <code>plot_now</code> is TRUE. Confidence intervals, if stored, will be printed, at the level of confidence used when doing the analysis.
indirect_standardized	If <code>print_indirect</code> is TRUE, which type of effects are to be printed: "none" for the unstandardized (raw) indirect effects, "stdx" for the effects with x standardized, "stdy" for the effects with y standardized, and "stdxy" for the effects with both x and y standardized.
size_indirect	The size used when printing the indirect effects. The final size is determined by multiplying the final value <code>size_path_labels</code> (determined internally if it is set to NULL) by this value. If equal to 1, then the size used in printing the indirect effects should be "close" to the size of numbers on the paths.
plot_now	If TRUE, the default, the plot will be plotted when calling this method.
...	For the <code>plot</code> method, these are optional arguments to be passed to <code>semPlot::semPaths()</code> to generate the initial plot, before being adjusted by <code>semtools::auto_layout_meditation()</code> .
q_meditation_output	The original object used to generate the plot (the output of the <code>q_meditation()</code> family). Indirect effects will be retrieved from this output.
original_plot	The plot generated by the <code>plot</code> method. If supplied, a new plot will be generated and then the indirect effects will be printed on this new plot. If NULL, the default, the indirect effects will be printed on the existing plot. Space will be added to make room for the indirect effects only if this argument is set. If <code>original_plot</code> is not used, make sure there is enough room at the bottom for the indirect effects.

Details

This method requires the `semtools` and `semPlot` packages. They are not installed by default. Install them first before using the `plot` method.

This method draws the path models fitted by `q_mediati()`, `q_simple_mediati()`, `q_serial_mediati()`, and `q_parallel_mediati()`, with path coefficients and R-squares.

It will try to set positions of the variables automatically, following the left-to-right convention: x variables on the left, y variables on the right, mediators between them, and arrows (paths) flow from left to right. The figure should usually be usable. If not, it can be further modified by helper functions such as those in `semtools` that can manipulate a `qgraph` object. For example, `semtools::move_node()` can be used to adjust the position of a variable in the plot.

The helper function `indirect_on_plot()` adds the indirect effect estimates (as well as confidence intervals and *p*-values, if available) to a plot. The `plot` method will add these effects by default, and so users usually do not need to use this function. However, if the plot needs to be modified before being drawn, this function can be used to add the effects after drawing the modified plot.

Value

The `plot` method returns a `qgraph` object generated by `semPlot::semPaths()`, which is plotted by default unless `plot_now` is set to `FALSE`. It can be further modified by other functions that work on a `qgraph` object, such as those from `semtools`.

The function `indirect_on_plot()` returns the object set to `q_mediati_output` invisibly. It is called for its side-effect.

Examples

```
# These examples require the package
# semtools (version 0.3.2 or above).

# CI disabled in these examples.
# Please see the help page of these functions on forming
# confidence intervals for the indirect effects.

# ===== Simple mediation

out <- q_simple_mediati(x = "x",
                         y = "y",
                         m = "m",
                         cov = c("c2", "c1"),
                         boot_ci = FALSE,
                         data = data_med)
plot(out)

# ===== Serial mediation

out <- q_serial_mediati(x = "x",
                         y = "y",
                         m = c("m1", "m2"),
                         cov = c("c2", "c1"),
                         boot_ci = FALSE,
```

```

data = data_serial)
plot(out)
# Standardized effects
plot(out,
      standardized = TRUE,
      indirect_standardized = "stdxy")

# ===== Parallel mediation

out <- q_parallel_meditation(x = "x",
                               y = "y",
                               m = c("m1", "m2"),
                               cov = c("c2", "c1"),
                               boot_ci = FALSE,
                               data = data_parallel)

plot(out)
plot(out,
      v_pos = "lower")
plot(out,
      v_pos = "upper")

# ===== A user-specified mediation model

out <- q_meditation(x = "x1",
                      y = "y1",
                      model = c("x1 -> m11 -> m2 -> y1",
                               "x1 -> m12 -> m2 -> y1"),
                      cov = c("c2", "c1"),
                      boot_ci = FALSE,
                      data = data_med_complicated)
plot(out)

```

plot_effect_vs_w

Plot an Effect Against a Moderator

Description

It plots an effect, direct or indirect, against a moderator, with confidence band if available.

Usage

```

plot_effect_vs_w(
  object,
  w = NULL,
  w_label = NULL,
  effect_label = NULL,
  add_zero_line = TRUE,
  always_draw_zero_line = FALSE,

```

```

  line_linewidth = 1,
  line_color = "blue",
  shade_the_band = TRUE,
  draw_the_intervals = TRUE,
  band_fill_color = "lightgrey",
  band_alpha = 0.5,
  intervals_color = "black",
  intervals_linetype = "longdash",
  intervals_linewidth = 1,
  zero_line_color = "grey",
  zero_line_linewidth = 1,
  zero_line_linetype = "solid",
  line_args = list(),
  band_args = list(),
  intervals_args = list(),
  zero_line_args = list(),
  level = 0.95
)

fill_wlevels(to_fill, cond_out = NULL, k = 21)

```

Arguments

object	The output of cond_indirect_effects() .
w	The name of the moderator. Must be present in object. If NULL, the default, and object has only one moderator, then it will be set to that moderator. Because this function currently only supports a path with only one moderator, this argument can be left as NULL for now.
w_label	The label of the horizontal axis. If NULL, the default, it will be <code>paste0("Moderator:", w)</code> .
effect_label	The label of the vertical axis. If NULL, the default, it will be generated from the path.
add_zero_line	Whether a horizontal line at zero will be drawn. Default is TRUE.
always_draw_zero_line	If FALSE, the default, then the line at zero, if requested will be drawn only if zero is within the range of the plot. If TRUE, then the line at zero will always be drawn.
line_linewidth	The width of the line of the effect for each level of the moderator, to be used by ggplot2::geom_line() . Default is 1. Always overrides the value of line_args.
line_color	The color of the line of the effect for each level of the moderator, to be used by ggplot2::geom_line() . Default is "blue". Always overrides the value of line_args.
shade_the_band	If TRUE, the default, a confidence band will be drawn as a region along the line if confidence intervals can be retrieved from object.
draw_the_intervals	If TRUE, the default, two lines will be drawn for the confidence intervals along the line if they can be retrieved from object.

band_fill_color	The color of of the confidence band, to be used by <code>ggplot2::geom_ribbon()</code> . Default is "lightgrey". Always overrides the value of <code>band_args</code> .
band_alpha	A number from 0 to 1 for the level of transparency of the confidence band, to be used by <code>ggplot2::geom_ribbon()</code> . Default is .50. Always overrides the value of <code>band_args</code> .
intervals_color	The color of the lines of the confidence intervals, to be used by <code>ggplot2::geom_line()</code> . Default is "black". Always overrides the value of <code>intervals_args</code> .
intervals_linetype	The line type of the lines of the confidence intervals, to be used by <code>ggplot2::geom_line()</code> . Default is "longdash". Always overrides the value of <code>intervals_args</code> .
intervals_linewidth	The line width of the lines of the confidence intervals, to be used by <code>ggplot2::geom_line()</code> . Default is 1. Always overrides the value of <code>intervals_args</code> .
zero_line_color	The color of the line at zero, to be used by <code>ggplot2::geom_line()</code> . Default is "grey". Always overrides the value of <code>zero_line_args</code> .
zero_line_linewidth	The line width of the line at zero, to be used by <code>ggplot2::geom_line()</code> . Default is 1. Always overrides the value of <code>zero_line_args</code> .
zero_line_linetype	The line type of the line at zero, to be used by <code>ggplot2::geom_line()</code> . Default is "solid". Always overrides the value of <code>zero_line_args</code> .
line_args	A named list of additional arguments to be passed to <code>ggplot2::geom_line()</code> for the line of the effect against moderator. Default is <code>list()</code> .
band_args	A named list of additional arguments to be passed to <code>ggplot2::geom_ribbon()</code> for the confidence band. Default is <code>list()</code> .
intervals_args	A named list of additional arguments to be passed to <code>ggplot2::geom_line()</code> for the lines of confidence intervals. Default is <code>list()</code> .
zero_line_args	A named list of additional arguments to be passed to <code>ggplot2::geom_line()</code> for the line at zero. Default is <code>list()</code> .
level	The level of confidence for the confidence intervals computed from the original standard errors. Used only for paths without mediators and both x- and y-variables are not standardized.
to_fill	The output of <code>cond_indirect_effects()</code> or <code>pseudo_johnson_neyman()</code> , for which additional levels of the moderator will be added.
cond_out	If <code>to_fill</code> is the output of <code>pseudo_johnson_neyman()</code> , the original output of <code>cond_indirect_effects()</code> used in the call to <code>pseudo_johnson_neyman()</code> need to be supplied through this argument.
k	The desired number of levels of the moderator.

Details

It receives an output of `cond_indirect_effects()` and plot the effect against the moderator. The effect can be an indirect effect or a direct effect.

It uses the levels of the moderator stored in the output of `cond_indirect_effects()`. Therefore, the desired levels of the moderator to be plotted needs to be specified when calling `cond_indirect_effects()`, as illustrated in the example.

Currently, this function only supports a path with exactly one moderator, and the moderator is a numeric variable.

Using Original Standard Errors:

If the following conditions are met, the stored standard errors, if available, will be used to form the confidence intervals:

- Confidence intervals have not been formed (e.g., by bootstrapping or Monte Carlo).
- The path has no mediators.
- The model has only one group.
- The path is moderated by one or more moderator.
- Both the x-variable and the y-variable are not standardized.

If the model is fitted by OLS regression (e.g., using `stats::lm()`), then the variance-covariance matrix of the coefficient estimates will be used, and confidence intervals are computed from the t statistic.

If the model is fitted by structural equation modeling using `lavaan`, then the variance-covariance computed by `lavaan` will be used, and confidence intervals are computed from the z statistic.

Caution:

If the model is fitted by structural equation modeling and has moderators, the standard errors, p -values, and confidence interval computed from the variance-covariance matrices for conditional effects can only be trusted if all covariances involving the product terms are free. If any of them are fixed, for example, fixed to zero, it is possible that the model is not invariant to linear transformation of the variables.

The function `fill_wlevels()` is a helper to automatically fill in additional levels of the moderators, to plot a graph with smooth confidence band. It accepts the output of `cond_indirect_effects()` or `pseudo_johnson_neyman()`, finds the range of the values of the moderator, and returns an output of `cond_indirect_effects()` with the desired number of levels within this range. It is intended to be a helper. If it does not work, users can still get the desired number of levels by setting the values manually when calling `cond_indirect_effects()`.

Value

`plot_effect_vs_w()` returns a ggplot2 graph. Plotted if not assigned to a name. It can be further modified like a usual ggplot2 graph.

`fill_wlevels()` returns an updated output of `cond_indirect_effects()` with the desired number of levels of the moderator.

See Also

`cond_indirect_effects()`

Examples

```

dat <- data_med_mod_a
lm_m <- lm(m ~ x*w + c1 + c2, dat)
lm_y <- lm(y ~ m + x + c1 + c2, dat)
fit_lm <- lm2list(lm_m, lm_y)
# Set R to a large value in real research.
boot_out_lm <- do_boot(fit_lm,
                        R = 50,
                        seed = 54532,
                        parallel = FALSE,
                        progress = FALSE)

# Compute the conditional indirect effects
# from 2 SD below mean to 2 SD above mean of the moderator,
# by setting sd_from_mean of cond_indirect_effects().
# Set length.out to a larger number for a smooth graph.
out_lm <- cond_indirect_effects(wlevels = "w",
                                  x = "x",
                                  y = "y",
                                  m = "m",
                                  fit = fit_lm,
                                  sd_from_mean = seq(-2, 2, length.out = 10),
                                  boot_ci = TRUE,
                                  boot_out = boot_out_lm)
p <- plot_effect_vs_w(out_lm)
p
# The output is a ggplot2 graph and so can be further customized
library(ggplot2)
# Add the line for the mean of w, the moderator
p2 <- p + geom_vline(xintercept = mean(dat$w),
                      color = "red")
p2

# Use fill_wlevels to add moderator levels:

dat <- data_med_mod_a
lm_m <- lm(m ~ x*w + c1 + c2, dat)
lm_y <- lm(y ~ m + x + c1 + c2, dat)
fit_lm <- lm2list(lm_m, lm_y)
wlevels <- mod_levels(w = "w",
                       sd_from_mean = c(-3, 0, 3),
                       fit = fit_lm)
wlevels
cond_out <- cond_indirect_effects(wlevels = wlevels,
                                    x = "x",
                                    y = "m",
                                    fit = fit_lm)
cond_out
# Only 3 points
p1 <- plot_effect_vs_w(cond_out)
p1

```

```
# Increase the number of levels to 15
cond_out_filled <- fill_wlevels(cond_out,
                                    k = 15)
cond_out_filled
p2 <- plot_effect_vs_w(cond_out_filled)
p2
```

predict.lm_from_lavaan

Predicted Values of a 'lm_from_lavaan'-Class Object

Description

Compute the predicted values based on the model stored in a 'lm_from_lavaan'-class object.

Usage

```
## S3 method for class 'lm_from_lavaan'
predict(object, newdata, ...)
```

Arguments

<code>object</code>	A 'lm_from_lavaan'-class object.
<code>newdata</code>	Required. A data frame of the new data. It must be a data frame.
<code>...</code>	Additional arguments. Ignored.

Details

An `lm_from_lavaan`-class method that converts a regression model for a variable in a `lavaan` model to a `formula` object. This function uses the stored model to compute predicted values using user-supplied data.

This is an advanced helper used by `plot.cond_indirect_effects()`. Exported for advanced users and developers.

Value

A numeric vector of the predicted values, with length equal to the number of rows of user-supplied data.

See Also

`lm_from_lavaan_list()`

Examples

```
library(lavaan)
data(data_med)
mod <-
  "
m ~ a * x + c1 + c2
y ~ b * m + x + c1 + c2
"
fit <- sem(mod, data_med, fixed.x = FALSE)
fit_list <- lm_from_lavaan_list(fit)
tmp <- data.frame(x = 1, c1 = 2, c2 = 3, m = 4)
predict(fit_list$m, newdata = tmp)
predict(fit_list$y, newdata = tmp)
```

`predict.lm_from_lavaan_list`

Predicted Values of an 'lm_from_lavaan_list'-Class Object

Description

It computes the predicted values based on the models stored in an 'lm_from_lavaan_list'-class object.

Usage

```
## S3 method for class 'lm_from_lavaan_list'
predict(object, x = NULL, y = NULL, m = NULL, newdata, ...)
```

Arguments

<code>object</code>	A 'lm_from_lavaan'-class object.
<code>x</code>	The variable name at the start of a path.
<code>y</code>	The variable name at the end of a path.
<code>m</code>	Optional. The mediator(s) from <code>x</code> to <code>y</code> . A numeric vector of the names of the mediators. The path goes from the first element to the last element. For example, if <code>m = c("m1", "m2")</code> , then the path is $x \rightarrow m1 \rightarrow m2 \rightarrow y$.
<code>newdata</code>	Required. A data frame of the new data. It must be a data frame.
<code>...</code>	Additional arguments. Ignored.

Details

An `lm_from_lavaan_list`-class object is a list of `lm_from_lavaan`-class objects.

This is an advanced helper used by `plot.cond_indirect_effects()`. Exported for advanced users and developers.

Value

A numeric vector of the predicted values, with length equal to the number of rows of user-supplied data.

See Also

[lm_from_lavaan_list\(\)](#)

Examples

```
library(lavaan)
data(data_med)
mod <- "
m ~ a * x + c1 + c2
y ~ b * m + x + c1 + c2
"
fit <- sem(mod, data_med, fixed.x = FALSE)
fit_list <- lm_from_lavaan_list(fit)
tmp <- data.frame(x = 1, c1 = 2, c2 = 3, m = 4)
predict(fit_list, x = "x", y = "y", m = "m", newdata = tmp)
```

predict.lm_list *Predicted Values of an 'lm_list'-Class Object*

Description

Compute the predicted values based on the models stored in an 'lm_list'-class object.

Usage

```
## S3 method for class 'lm_list'
predict(object, x = NULL, y = NULL, m = NULL, newdata, ...)
```

Arguments

object	An 'lm_list'-class object.
x	The variable name at the start of a path.
y	The variable name at the end of a path.
m	Optional. The mediator(s) from x to y. A numeric vector of the names of the mediators. The path goes from the first element to the last element. For example, if m = c("m1", "m2"), then the path is x -> m1 -> m2 -> y.
newdata	Required. A data frame of the new data. It must be a data frame.
...	Additional arguments. Ignored.

Details

An `lm`-list-class object is a list of `lm`-class objects, this function is similar to the `stats::predict()` method of `lm()` but it works on a system defined by a list of regression models.

This is an advanced helper used by some functions in this package. Exported for advanced users.

Value

A numeric vector of the predicted values, with length equal to the number of rows of user-supplied data.

See Also

`lm2list()`

Examples

```
data(data_serial_parallel)
lm_m11 <- lm(m11 ~ x + c1 + c2, data_serial_parallel)
lm_m12 <- lm(m12 ~ m11 + x + c1 + c2, data_serial_parallel)
lm_m2 <- lm(m2 ~ x + c1 + c2, data_serial_parallel)
lm_y <- lm(y ~ m11 + m12 + m2 + x + c1 + c2, data_serial_parallel)
# Join them to form a lm_list-class object
lm_serial_parallel <- lm2list(lm_m11, lm_m12, lm_m2, lm_y)
lm_serial_parallel
summary(lm_serial_parallel)
newdat <- data_serial_parallel[3:5, ]
predict(lm_serial_parallel,
       x = "x",
       y = "y",
       m = "m2",
       newdata = newdat)
```

`print.all_paths` *Print 'all_paths' Class Object*

Description

Print the content of 'all_paths'-class object, which can be generated by `all_indirect_paths()`.

Usage

```
## S3 method for class 'all_paths'
print(x, ...)
```

Arguments

<code>x</code>	A 'all_paths'-class object.
<code>...</code>	Optional arguments.

Details

This function is used to print the paths identified in a readable format.

Value

x is returned invisibly. Called for its side effect.

Author(s)

Shu Fai Cheung <https://orcid.org/0000-0002-9871-9448>

See Also

[all_indirect_paths\(\)](#)

Examples

```
library(lavaan)
data(data_serial_parallel)
mod <- "
m11 ~ x + c1 + c2
m12 ~ m11 + x + c1 + c2
m2 ~ x + c1 + c2
y ~ m12 + m2 + m11 + x + c1 + c2
"
fit <- sem(mod, data_serial_parallel,
           fixed.x = FALSE)
# All indirect paths
out1 <- all_indirect_paths(fit)
out1
```

print.boot_out

Print a boot_out-Class Object

Description

Print the content of the output of [do_boot\(\)](#) or related functions.

Usage

```
## S3 method for class 'boot_out'
print(x, ...)
```

Arguments

- x The output of [do_boot\(\)](#), or any boot_out-class object returned by similar functions.
- ... Other arguments. Not used.

Value

`x` is returned invisibly. Called for its side effect.

Examples

```

data(data_med_mod_ab1)
dat <- data_med_mod_ab1
lm_m <- lm(m ~ x*w + c1 + c2, dat)
lm_y <- lm(y ~ m*w + x + c1 + c2, dat)
lm_out <- lm2list(lm_m, lm_y)
# In real research, R should be 2000 or even 5000
# In real research, no need to set parallel to FALSE
# In real research, no need to set progress to FALSE
# Progress is displayed by default.
lm_boot_out <- do_boot(lm_out, R = 100,
                       seed = 1234,
                       progress = FALSE,
                       parallel = FALSE)
# Print the output of do_boot()
lm_boot_out

library(lavaan)
data(data_med_mod_ab1)
dat <- data_med_mod_ab1
dat$"x:w" <- dat$x * dat$w
dat$"m:w" <- dat$m * dat$w
mod <-
"
m ~ x + w + x:w + c1 + c2
y ~ m + w + m:w + x + c1 + c2
"
fit <- sem(model = mod, data = dat, fixed.x = FALSE,
           se = "none", baseline = FALSE)
# In real research, R should be 2000 or even 5000
# In real research, no need to set progress to FALSE
# In real research, no need to set parallel to FALSE
# Progress is displayed by default.
fit_boot_out <- do_boot(fit = fit,
                       R = 40,
                       seed = 1234,
                       parallel = FALSE,
                       progress = FALSE)
# Print the output of do_boot()
fit_boot_out

```

Description

Print the output of `cond_indirect_diff()`.

Usage

```
## S3 method for class 'cond_indirect_diff'
print(x, digits = 3, pvalue = FALSE, pvalue_digits = 3, se = FALSE, ...)
```

Arguments

<code>x</code>	The output of <code>cond_indirect_diff()</code> .
<code>digits</code>	The number of decimal places in the printout.
<code>pvalue</code>	Logical. If TRUE, asymmetric p -value based on bootstrapping will be printed if available. Default is FALSE.
<code>pvalue_digits</code>	Number of decimal places to display for the p -value. Default is 3.
<code>se</code>	Logical. If TRUE and confidence intervals are available, the standard errors of the estimates are also printed. They are simply the standard deviations of the bootstrap estimates or Monte Carlo simulated values, depending on the method used to form the confidence intervals.
<code>...</code>	Optional arguments. Ignored.

Details

The `print` method of the `cond_indirect_diff`-class object.

If bootstrapping confidence interval was requested, this method has the option to print a p -value computed by the method presented in Asparouhov and Muthén (2021). Note that this p -value is asymmetric bootstrap p -value based on the distribution of the bootstrap estimates. It is not computed based on the distribution under the null hypothesis.

For a p -value of a , it means that a $100(1 - a)\%$ bootstrapping confidence interval will have one of its limits equal to 0. A confidence interval with a higher confidence level will include zero, while a confidence interval with a lower confidence level will exclude zero.

Value

It returns `x` invisibly. Called for its side effect.

References

Asparouhov, A., & Muthén, B. (2021). Bootstrap p-value computation. Retrieved from <https://www.statmodel.com/download/Bootstrap%20-%20Pvalue.pdf>

See Also

`cond_indirect_diff()`

```
print.cond_indirect_effects
    Print a 'cond_indirect_effects' Class Object
```

Description

Print the content of the output of [cond_indirect_effects\(\)](#)

Usage

```
## S3 method for class 'cond_indirect_effects'
print(
  x,
  digits = 3,
  annotation = TRUE,
  pvalue = NULL,
  pvalue_digits = 3,
  se = NULL,
  level = 0.95,
  se_ci = TRUE,
  ...
)

## S3 method for class 'cond_indirect_effects'
as.data.frame(
  x,
  row.names = NULL,
  optional = NULL,
  digits = 3,
  add_sig = TRUE,
  pvalue = NULL,
  pvalue_digits = 3,
  se = NULL,
  level = 0.95,
  se_ci = TRUE,
  to_string = FALSE,
  ...
)
```

Arguments

- x The output of [cond_indirect_effects\(\)](#).
- digits Number of digits to display. Default is 3.
- annotation Logical. Whether the annotation after the table of effects is to be printed. Default is TRUE.

pvalue	Logical. If TRUE, asymmetric p -values based on bootstrapping will be printed if available. Default to FALSE if confidence intervals have already computed. Default to TRUE if no confidence intervals have been computed and the original standard errors are to be used. See Details on when the original standard errors will be used by default.
pvalue_digits	Number of decimal places to display for the p -values. Default is 3.
se	Logical. If TRUE and confidence intervals are available, the standard errors of the estimates are also printed. They are simply the standard deviations of the bootstrap estimates or Monte Carlo simulated values, depending on the method used to form the confidence intervals. Default to FALSE if confidence intervals are available. Default to TRUE if no confidence intervals have been computed and the original standard errors are to be used. See Details on when the original standard errors will be used by default.
level	The level of confidence for the confidence intervals computed from the original standard errors. Used only for paths without mediators and both x- and y-variables are not standardized.
se_ci	Logical. If TRUE and confidence interval has not been computed, the function will try to compute them from stored standard errors if the original standard errors are to be used. Ignored if confidence intervals have already been computed. Default to TRUE.
...	Other arguments. Not used.
row.names	Not used. Included to be compatible with the generic method.
optional	Not used. Included to be compatible with the generic method.
add_sig	Whether a column of significance test results will be added. Default is TRUE.
to_string	If TRUE, numeric columns will be converted to string columns, formatted based on digits and pvalue_digits. For printing. Default is FALSE.

Details

The print method of the cond_indirect_effects-class object.

If bootstrapping confidence intervals were requested, this method has the option to print p -values computed by the method presented in Asparouhov and Muthén (2021). Note that these p -values are asymmetric bootstrap p -values based on the distribution of the bootstrap estimates. They not computed based on the distribution under the null hypothesis.

For a p -value of a , it means that a $100(1 - a)\%$ bootstrapping confidence interval will have one of its limits equal to 0. A confidence interval with a higher confidence level will include zero, while a confidence interval with a lower confidence level will exclude zero.

Using Original Standard Errors:

If these conditions are met, the stored standard errors, if available, will be used test an effect and form it confidence interval:

- Confidence intervals have not been formed (e.g., by bootstrapping or Monte Carlo).
- The path has no mediators.
- The model has only one group.
- The path is moderated by one or more moderator.

- Both the x-variable and the y-variable are not standardized.

If the model is fitted by OLS regression (e.g., using `stats::lm()`), then the variance-covariance matrix of the coefficient estimates will be used, and the *p*-value and confidence intervals are computed from the *t* statistic.

If the model is fitted by structural equation modeling using `lavaan`, then the variance-covariance computed by `lavaan` will be used, and the *p*-value and confidence intervals are computed from the *z* statistic.

Caution:

If the model is fitted by structural equation modeling and has moderators, the standard errors, *p*-values, and confidence interval computed from the variance-covariance matrices for conditional effects can only be trusted if all covariances involving the product terms are free. If any of them are fixed, for example, fixed to zero, it is possible that the model is not invariant to linear transformation of the variables.

The method `as.data.frame()` for `cond_indirect_effects` objects is used to convert this class of objects to data frames. Used internally by the `print` method but can also be used for getting a data frame with columns such as *p*-values and standard errors added.

Value

The `print`-method returns `x` invisibly. Called for its side effect.

The `as.data.frame`-method returns a data frame with the conditional effects and confidence intervals (if available), as well as other columns requested.

Functions

- `as.data.frame(cond_indirect_effects)`: The `as.data.frame`-method for `cond_indirect_effects` objects. Used internally by the `print`-method but can also be used directly.

References

Asparouhov, A., & Muthén, B. (2021). Bootstrap p-value computation. Retrieved from <https://www.statmodel.com/download/Bootstrap%20-%20Pvalue.pdf>

See Also

`cond_indirect_effects()` and `cond_effects()`

Examples

```
library(lavaan)
dat <- modmed_x1m3w4y1
mod <-
"
m1 ~ a1 * x + d1 * w1 + e1 * x:w1
m2 ~ a2 * x
y ~ b1 * m1 + b2 * m2 + cp * x
"
fit <- sem(mod, dat,
```

```

meanstructure = TRUE, fixed.x = FALSE, se = "none", baseline = FALSE)

# Conditional effects from x to m1 when w1 is equal to each of the default levels
cond_indirect_effects(x = "x", y = "m1",
                       wlevels = "w1", fit = fit)

# Conditional Indirect effect from x1 through m1 to y,
# when w1 is equal to each of the default levels
out <- cond_indirect_effects(x = "x", y = "y", m = "m1",
                             wlevels = "w1", fit = fit)
out

print(out, digits = 5)

print(out, annotation = FALSE)

# Convert to data frames
as.data.frame(out)

as.data.frame(out, to_string = TRUE)

```

print.delta_med *Print a 'delta_med' Class Object*

Description

Print the content of a delta_med-class object.

Usage

```
## S3 method for class 'delta_med'
print(x, digits = 3, level = NULL, full = FALSE, boot_type, ...)
```

Arguments

x	A delta_med-class object.
digits	The number of digits after the decimal. Default is 3.
level	The level of confidence of bootstrap confidence interval, if requested when created. If NULL, the default, the level requested when calling delta_med() is used. If not null, then this level will be used.
full	Logical. Whether additional information will be printed. Default is FALSE.
boot_type	If bootstrap confidence interval is to be formed, the type of bootstrap confidence interval. The supported types are "perc" (percentile bootstrap confidence interval, the recommended method) and "bc" (bias-corrected, or BC, bootstrap confidence interval). If not supplied, the stored boot_type will be used.
...	Optional arguments. Ignored.

Details

It prints the output of `delta_med()`, which is a `delta_med`-class object.

Value

`x` is returned invisibly. Called for its side effect.

Author(s)

Shu Fai Cheung <https://orcid.org/0000-0002-9871-9448>

See Also

[delta_med\(\)](#)

Examples

```
library(lavaan)
dat <- data_med
mod <-
"
m ~ x
y ~ m + x
"
fit <- sem(mod, dat)
dm <- delta_med(x = "x",
                 y = "y",
                 m = "m",
                 fit = fit)
dm
print(dm, full = TRUE)

# Call do_boot() to generate
# bootstrap estimates
# Use 2000 or even 5000 for R in real studies
# Set parallel to TRUE in real studies for faster bootstrapping
boot_out <- do_boot(fit,
                      R = 45,
                      seed = 879,
                      parallel = FALSE,
                      progress = FALSE)
# Remove 'progress = FALSE' in practice
dm_boot <- delta_med(x = "x",
                      y = "y",
                      m = "m",
                      fit = fit,
                      boot_out = boot_out,
                      progress = FALSE)
dm_boot
confint(dm_boot)
confint(dm_boot,
        level = .90)
```

print.indirect *Print an 'indirect' Class Object*

Description

Print the content of the output of [indirect_effect\(\)](#) or [cond_indirect\(\)](#).

Usage

```
## S3 method for class 'indirect'
print(
  x,
  digits = 3,
  pvalue = NULL,
  pvalue_digits = 3,
  se = NULL,
  level = 0.95,
  se_ci = TRUE,
  wrap_computation = TRUE,
  ...
)
```

Arguments

<code>x</code>	The output of indirect_effect() or cond_indirect() .
<code>digits</code>	Number of digits to display. Default is 3.
<code>pvalue</code>	Logical. If TRUE, asymmetric p -values based on bootstrapping will be printed if available. Default to FALSE if confidence intervals have already computed. Default to TRUE if no confidence intervals have been computed and the original standard errors are to be used. See Details on when the original standard errors will be used by default. Default is NULL and its value determined as stated above.
<code>pvalue_digits</code>	Number of decimal places to display for the p -value. Default is 3.
<code>se</code>	Logical. If TRUE and confidence interval has been formed, the standard error of the estimates are also printed. It is simply the standard deviation of the bootstrap estimates or Monte Carlo simulated values, depending on the method used to form the confidence intervals. Default to FALSE if confidence interval has been formed. Default to TRUE if no confidence interval has been computed and the original standard errors are to be used. See Details on when the original standard errors will be used by default. Default is NULL and its value determined as stated above.
<code>level</code>	The level of confidence for the confidence interval computed from the original standard errors. Used only for paths without mediators and both x- and y-variables are not standardized.

se_ci	Logical. If TRUE and confidence interval has not been computed, the function will try to compute them from stored standard error if the original standard error is to be used. Ignored if confidence interval has already been computed. Default to TRUE.
wrap_computation	Logical. If TRUE, the default, long computational symbols and values will be wrapped to fit to the screen width.
...	Other arguments. Not used.

Details

The print method of the `indirect`-class object.

If bootstrapping confidence interval was requested, this method has the option to print a p -value computed by the method presented in Asparouhov and Muthén (2021). Note that this p -value is asymmetric bootstrap p -value based on the distribution of the bootstrap estimates. It is not computed based on the distribution under the null hypothesis.

For a p -value of a , it means that a $100(1 - a)\%$ bootstrapping confidence interval will have one of its limits equal to 0. A confidence interval with a higher confidence level will include zero, while a confidence interval with a lower confidence level will exclude zero.

We recommend using confidence interval directly. Therefore, p -value is not printed by default. Nevertheless, users who need it can request it by setting `pvalue` to TRUE.

Using Original Standard Errors:

If these conditions are met, the stored standard error, if available, will be used to test an effect and form its confidence interval:

- Confidence interval has not been formed (e.g., by bootstrapping or Monte Carlo).
- The path has no mediators.
- The model has only one group.
- Both the x-variable and the y-variable are not standardized.

If the model is fitted by OLS regression (e.g., using `stats::lm()`), then the variance-covariance matrix of the coefficient estimates will be used, and the p -value and confidence interval are computed from the t statistic.

If the model is fitted by structural equation modeling using `lavaan`, then the variance-covariance computed by `lavaan` will be used, and the p -value and confidence interval are computed from the z statistic.

Caution:

If the model is fitted by structural equation modeling and has moderators, the standard errors, p -values, and confidence interval computed from the variance-covariance matrices for conditional effects can only be trusted if all covariances involving the product terms are free. If any some of them are fixed, for example, fixed to zero, it is possible that the model is not invariant to linear transformation of the variables.

Value

`x` is returned invisibly. Called for its side effect.

References

Asparouhov, A., & Muthén, B. (2021). Bootstrap p-value computation. Retrieved from <https://www.statmodel.com/download/Bootstrap%20-%20Pvalue.pdf>

See Also

[indirect_effect\(\)](#) and [cond_indirect\(\)](#)

Examples

```
library(lavaan)
dat <- modmed_x1m3w4y1
mod <-
"
m1 ~ a1 * x    + b1 * w1 + d1 * x:w1
m2 ~ a2 * m1   + b2 * w2 + d2 * m1:w2
m3 ~ a3 * m2   + b3 * w3 + d3 * m2:w3
y   ~ a4 * m3   + b4 * w4 + d4 * m3:w4
"
fit <- sem(mod, dat,
           meanstructure = TRUE, fixed.x = FALSE,
           se = "none", baseline = FALSE)
est <- parameterEstimates(fit)

wvalues <- c(w1 = 5, w2 = 4, w3 = 2, w4 = 3)

indirect_1 <- cond_indirect(x = "x", y = "y",
                             m = c("m1", "m2", "m3"),
                             fit = fit,
                             wvalues = wvalues)
indirect_1

dat <- modmed_x1m3w4y1
mod2 <-
"
m1 ~ a1 * x
m2 ~ a2 * m1
m3 ~ a3 * m2
y   ~ a4 * m3 + x
"
fit2 <- sem(mod2, dat,
           meanstructure = TRUE, fixed.x = FALSE,
           se = "none", baseline = FALSE)
est <- parameterEstimates(fit)

indirect_2 <- indirect_effect(x = "x", y = "y",
                             m = c("m1", "m2", "m3"),
                             fit = fit2)
indirect_2
print(indirect_2, digits = 5)
```

print.indirect_list *Print an 'indirect_list' Class Object*

Description

Print the content of the output of [many_indirect_effects\(\)](#).

Usage

```
## S3 method for class 'indirect_list'
print(
  x,
  digits = 3,
  annotation = TRUE,
  pvalue = FALSE,
  pvalue_digits = 3,
  se = FALSE,
  for_each_path = FALSE,
  ...
)
```

Arguments

x	The output of many_indirect_effects() .
digits	Number of digits to display. Default is 3.
annotation	Logical. Whether the annotation after the table of effects is to be printed. Default is TRUE.
pvalue	Logical. If TRUE, asymmetric <i>p</i> -values based on bootstrapping will be printed if available.
pvalue_digits	Number of decimal places to display for the <i>p</i> -values. Default is 3.
se	Logical. If TRUE and confidence intervals are available, the standard errors of the estimates are also printed. They are simply the standard deviations of the bootstrap estimates or Monte Carlo simulated values, depending on the method used to form the confidence intervals.
for_each_path	Logical. If TRUE, each of the paths will be printed individually, using the print-method of the output of indirect_effect() . Default is FALSE.
...	Other arguments. If for_each_path is TRUE, they will be passed to the print method of the output of indirect_effect() . Ignored otherwise.

Details

The print method of the indirect_list-class object.

If bootstrapping confidence interval was requested, this method has the option to print a *p*-value computed by the method presented in Asparouhov and Muthén (2021). Note that this *p*-value is

asymmetric bootstrap p -value based on the distribution of the bootstrap estimates. It is not computed based on the distribution under the null hypothesis.

For a p -value of a , it means that a $100(1 - a)\%$ bootstrapping confidence interval will have one of its limits equal to 0. A confidence interval with a higher confidence level will include zero, while a confidence interval with a lower confidence level will exclude zero.

Value

`x` is returned invisibly. Called for its side effect.

References

Asparouhov, A., & Muthén, B. (2021). Bootstrap p-value computation. Retrieved from <https://www.statmodel.com/download/Bootstrap%20-%20Pvalue.pdf>

See Also

[many_indirect_effects\(\)](#)

Examples

```
library(lavaan)
data(data_serial_parallel)
mod <-
  "
m11 ~ x + c1 + c2
m12 ~ m11 + x + c1 + c2
m2 ~ x + c1 + c2
y ~ m12 + m2 + m11 + x + c1 + c2
"
fit <- sem(mod, data_serial_parallel,
           fixed.x = FALSE)
# All indirect paths from x to y
paths <- all_indirect_paths(fit,
                           x = "x",
                           y = "y")
paths
# Indirect effect estimates
out <- many_indirect_effects(paths,
                             fit = fit)
out
```

```
print.indirect_proportion
  Print an 'indirect_proportion'-Class Object
```

Description

Print the content of an 'indirect_proportion'-class object, the output of [indirect_proportion\(\)](#).

Usage

```
## S3 method for class 'indirect_proportion'
print(x, digits = 3, annotation = TRUE, ...)
```

Arguments

x	An 'indirect_proportion'-class object.
digits	Number of digits to display. Default is 3.
annotation	Logical. Whether additional information should be printed. Default is TRUE.
...	Optional arguments. Not used.

Details

The `print` method of the `indirect_proportion`-class object, which is produced by [indirect_proportion\(\)](#). In addition to the proportion of effect mediated, it also prints additional information such as the path for which the proportion is computed, and all indirect path(s) from the x-variable to the y-variable.

To get the proportion as a scalar, use the `coef` method of `indirect_proportion` objects.

Value

`x` is returned invisibly. Called for its side effect.

See Also

[indirect_proportion\(\)](#)

Examples

```
library(lavaan)
dat <- data_med
head(dat)
mod <-
"
m ~ x + c1 + c2
y ~ m + x + c1 + c2
"
fit <- sem(mod, dat, fixed.x = FALSE)
out <- indirect_proportion(x = "x",
```

```

y = "y",
m = "m",
fit = fit)
out
print(out, digits = 5)

```

print.lm_list	<i>Print an lm_list-Class Object</i>
---------------	--------------------------------------

Description

Print the content of the output of [lm2list\(\)](#).

Usage

```
## S3 method for class 'lm_list'
print(x, ...)
```

Arguments

x	The output of lm2list() .
...	Other arguments. Not used.

Value

x is returned invisibly. Called for its side effect.

Examples

```

data(data_serial_parallel)
lm_m11 <- lm(m11 ~ x + c1 + c2, data_serial_parallel)
lm_m12 <- lm(m12 ~ m11 + x + c1 + c2, data_serial_parallel)
lm_m2 <- lm(m2 ~ x + c1 + c2, data_serial_parallel)
lm_y <- lm(y ~ m11 + m12 + m2 + x + c1 + c2, data_serial_parallel)
# Join them to form a lm_list-class object
lm_serial_parallel <- lm2list(lm_m11, lm_m12, lm_m2, lm_y)
lm_serial_parallel
```

print.mc_out	<i>Print a mc_out-Class Object</i>
--------------	------------------------------------

Description

Print the content of the output of [do_mc\(\)](#) or related functions.

Usage

```
## S3 method for class 'mc_out'  
print(x, ...)
```

Arguments

- x The output of [do_mc\(\)](#), or any mc_out-class object returned by similar functions.
- ... Other arguments. Not used.

Value

x is returned invisibly. Called for its side effect.

Examples

```
library(lavaan)  
data(data_med_mod_ab1)  
dat <- data_med_mod_ab1  
mod <-  
"  
m ~ x + w + x:w + c1 + c2  
y ~ m + w + m:w + x + c1 + c2  
"  
fit <- sem(mod, dat)  
# In real research, R should be 5000 or even 10000  
mc_out <- do_mc(fit, R = 100, seed = 1234)  
  
# Print the output of do_boot()  
mc_out
```

pseudo_johnson_neyman *Pseudo Johnson-Neyman Probing*

Description

Use the pseudo Johnson-Neyman approach (Hayes, 2022) to find the range of values of a moderator in which the conditional effect is not significant.

Usage

```
pseudo_johnson_neyman(
  object = NULL,
  w_lower = NULL,
  w_upper = NULL,
  optimize_method = c("uniroot", "optimize"),
  extendInt = c("no", "yes", "downX", "upX"),
  tol = .Machine$double.eps^0.25,
  level = 0.95
)

johnson_neyman(
  object = NULL,
  w_lower = NULL,
  w_upper = NULL,
  optimize_method = c("uniroot", "optimize"),
  extendInt = c("no", "yes", "downX", "upX"),
  tol = .Machine$double.eps^0.25,
  level = 0.95
)

## S3 method for class 'pseudo_johnson_neyman'
print(x, digits = 3, ...)
```

Arguments

object	A <code>cond_indirect_effects</code> -class object, which is the output of cond_indirect_effects() .
w_lower	The smallest value of the moderator when doing the search. If set to <code>NULL</code> , the default, it will be 10 standard deviations below mean, which should be small enough.
w_upper	The largest value of the moderator when doing the search. If set to <code>NULL</code> , the default, it will be 10 standard deviations above mean, which should be large enough.
optimize_method	The optimization method to be used. Either <code>"uniroot"</code> (the default) or <code>"optimize"</code> , corresponding to <code>stats::uniroot()</code> and <code>stats::optimize()</code> , respectively.

extendInt	Used by <code>stats::uniroot()</code> . If "no", then search will be conducted strictly within <code>c(w_lower, w_upper)</code> . Otherwise, the range is extended based on this argument if the solution is not found. Please refer to <code>stats::uniroot()</code> for details.
tol	The tolerance level used by both <code>stats::uniroot()</code> and <code>stats::optimize()</code> .
level	The level of confidence of the confidence level. One minus this level is the level of significance. Default is .95, equivalent to a level of significance of .05.
x	The output of <code>pseudo_johnson_neyman()</code> .
digits	Number of digits to display. Default is 3.
...	Other arguments. Not used.

Details

This function uses the pseudo Johnson-Neyman approach proposed by Hayes (2022) to find the values of a moderator at which a conditional effect is "nearly just significant" based on confidence interval. If an effect is moderated, there will be two such points (though one can be very large or small) forming a range. The conditional effect is not significant within this range, and significant outside this range, based on the confidence interval.

This function receives the output of `cond_indirect_effects()` and search for, within a specific range, the two values of the moderator at which the conditional effect is "nearly just significant", that is, the confidence interval "nearly touches" zero.

Note that numerical method is used to find the points. Therefore, strictly speaking, the effects at the end points are still either significant or not significant, even if the confidence limit is very close to zero.

Though numerical method is used, if the test is conducted using the standard error (see below), the result is equivalent to the (true) Johnson-Neyman (1936) probing. The function `johnson_neyman()` is just an alias to `pseudo_johnson_neyman()`, with the name consistent with what it does in this special case.

Supported Methods:

This function supports models fitted by `lm()`, `lavaan::sem()`, and `lavaan.mi::sem.mi()`. This function also supports both bootstrapping and Monte Carlo confidence intervals. It also supports conditional direct paths (no mediator) and conditional indirect paths (with one or more mediator), with x and/or y standardized.

Requirements:

To be eligible for using this function, one of these conditions must be met:

- One form of confidence intervals (e.g., bootstrapping or Monte Carlo) must have been requested (e.g., setting `boot_ci = TRUE` or `mc_ci = TRUE`) when calling `cond_indirect_effects()`.
- Tests can be done using stored standard errors: A path with no mediator and both the x- and y-variables are not standardized.

For pre-computed confidence intervals, the confidence level of the confidence intervals adopted when calling `cond_indirect_effects()` will be used by this function.

For tests conducted by standard errors, the argument `level` is used to control the level of significance.

Possible failures:

Even if a path has only one moderator, it is possible that no solution, or more than one solution, is/are found if the relation between this moderator and the conditional effect is not linear.

Solution may also be not found if the conditional effect is significant over a wide range of value of the moderator.

It is advised to use `plot_effect_vs_w()` to examine the relation between the effect and the moderator first before calling this function.

Speed:

Note that, for conditional indirect effects, the search can be slow because the confidence interval needs to be recomputed for each new value of the moderator.

Limitations:

- This function currently only supports a path with only one moderator,
- This function does not yet support multigroup models.

Value

A list of the class `pseudo_johnson_neyman` (with a print method, `print.pseudo_johnson_neyman()`). It has these major elements:

- `cond_effects`: An output of `cond_indirect_effects()` for the two levels of the moderator found.
- `w_min_valid`: Logical. If TRUE, the conditional effect is just significant at the lower level of the moderator found, and so is significant below this point. If FALSE, then the lower level of the moderator found is just the lower bound of the range searched, that is, `w_lower`.
- `w_max_valid`: Logical. If TRUE, the conditional effect is just significant at the higher level of the moderator found, and so is significant above this point. If FALSE, then the higher level of the moderator found is just the upper bound of the range searched, that is, `w_upper`.

Methods (by generic)

- `print(pseudo_johnson_neyman)`: Print method for output of `pseudo_johnson_neyman()`.

References

Johnson, P. O., & Neyman, J. (1936). Test of certain linear hypotheses and their application to some educational problems. *Statistical Research Memoirs*, 1, 57–93.

Hayes, A. F. (2022). *Introduction to mediation, moderation, and conditional process analysis: A regression-based approach* (Third edition). The Guilford Press.

See Also

`cond_indirect_effects()`

Examples

```

library(lavaan)

dat <- data_med_mod_a
dat$wx <- dat$x * dat$w
mod <-
"
m ~ x + w + wx
y ~ m + x
"
fit <- sem(mod, dat)

# In real research, R should be 2000 or even 5000
# In real research, no need to set parallel and progress to FALSE
# Parallel processing is enabled by default and
# progress is displayed by default.
boot_out <- do_boot(fit,
                      R = 40,
                      seed = 4314,
                      parallel = FALSE,
                      progress = FALSE)
out <- cond_indirect_effects(x = "x", y = "y", m = "m",
                             wlevels = "w",
                             fit = fit,
                             boot_ci = TRUE,
                             boot_out = boot_out)

# Visualize the relation first
plot_effect_vs_w(out)

out_jn <- pseudo_johnson_neyman(out)
out_jn

# Plot the range
plot_effect_vs_w(out_jn$cond_effects)

```

q_meditation

Mediation Models By Regression or SEM

Description

Simple-to-use functions for fitting linear models by regression or structural equation modeling and testing indirect effects, using just one function.

Usage

```
q_meditation(
  x,
```

```
  y,
  m = NULL,
  cov = NULL,
  data = NULL,
  boot_ci = TRUE,
  mc_ci = FALSE,
  level = 0.95,
  R = 100,
  seed = NULL,
  ci_type = NULL,
  boot_type = c("perc", "bc"),
  model = NULL,
  fit_method = c("lm", "regression", "sem", "lavaan"),
  missing = "fiml",
  fixed.x = TRUE,
  sem_args = list(),
  na.action = "na.pass",
  parallel = TRUE,
  ncores = max(parallel::detectCores(logical = FALSE) - 1, 1),
  progress = TRUE
)

q_simple_mediati
on(
  x,
  y,
  m = NULL,
  cov = NULL,
  data = NULL,
  boot_ci = TRUE,
  mc_ci = FALSE,
  level = 0.95,
  R = 100,
  seed = NULL,
  ci_type = NULL,
  boot_type = c("perc", "bc"),
  fit_method = c("lm", "regression", "sem", "lavaan"),
  missing = "fiml",
  fixed.x = TRUE,
  sem_args = list(),
  na.action = "na.pass",
  parallel = TRUE,
  ncores = max(parallel::detectCores(logical = FALSE) - 1, 1),
  progress = TRUE
)

q_serial_mediati
on(
  x,
  y,
```

```
m = NULL,
cov = NULL,
data = NULL,
boot_ci = TRUE,
mc_ci = FALSE,
level = 0.95,
R = 100,
seed = NULL,
ci_type = NULL,
boot_type = c("perc", "bc"),
fit_method = c("lm", "regression", "sem", "lavaan"),
missing = "fiml",
fixed.x = TRUE,
sem_args = list(),
na.action = "na.pass",
parallel = TRUE,
ncores = max(parallel::detectCores(logical = FALSE) - 1, 1),
progress = TRUE
)

q_parallel_moderation(
  x,
  y,
  m = NULL,
  cov = NULL,
  data = NULL,
  boot_ci = TRUE,
  mc_ci = FALSE,
  level = 0.95,
  R = 100,
  seed = NULL,
  ci_type = NULL,
  boot_type = c("perc", "bc"),
  fit_method = c("lm", "regression", "sem", "lavaan"),
  missing = "fiml",
  fixed.x = TRUE,
  sem_args = list(),
  na.action = "na.pass",
  parallel = TRUE,
  ncores = max(parallel::detectCores(logical = FALSE) - 1, 1),
  progress = TRUE
)

## S3 method for class 'q_moderation'
print(
  x,
  digits = 4,
  annotation = TRUE,
```

```

pvalue = TRUE,
pvalue_digits = 4,
se = TRUE,
for_each_path = FALSE,
se_ci = TRUE,
wrap_computation = TRUE,
lm_ci = TRUE,
lm_beta = TRUE,
lm_ci_level = 0.95,
sem_style = c("lm", "lavaan"),
...
)

```

Arguments

x	For <code>q_mediati</code> on(), <code>q_simple_mediati</code> on(), <code>q_serial_mediati</code> on(), and <code>q_parallel_mediati</code> on(), it is the name of the predictor. For the print method of these functions, x is the output of these functions.
y	The name of the outcome.
m	A character vector of the name(s) of the mediator(s). For a simple mediation model, it must has only one name. For serial and parallel mediation models, it can have one or more names. For a serial mediation models, the direction of the paths go from the first names to the last names. For example, <code>c("m1", "m3", "m4")</code> denoted that the path is <code>m1 -> m3 -> m4</code> .
cov	The names of the covariates, if any. If it is a character vector, then the outcome (y) and all mediators (m) regress on all the covariates. If it is a named list of character vectors, then the covariates in an element predict only the variable with the name of this element. For example, <code>list(m1 = "c1", dv = c("c2", "c3"))</code> indicates that c1 predicts "m1", while c2 and c3 predicts "dv". Default is NULL, no covariates.
data	The data frame. Note that listwise deletion will be used and only cases with no missing data on all variables in the model (e.g., x, m, y and cov) will be retained.
boot_ci	Logical. Whether bootstrap confidence interval will be formed. Default is TRUE.
mc_ci	Logical. Whether Monte Carlo confidence interval will be formed. Default is FALSE. Only supported if <code>fit_method</code> is "sem" or "lavaan".
level	The level of confidence of the confidence interval. Default is .95 (for 95% confidence intervals).
R	The number of bootstrap samples. Default is 100. Should be set to 5000 or at least 10000.
seed	The seed for the random number generator. Default is NULL. Should nearly always be set to an integer to make the results reproducible.
ci_type	The type of confidence intervals to be formed. Can be either "boot" (bootstrapping) or "mc" (Monte Carlo). If not supplied or is NULL, will check other arguments (e.g, <code>boot_ci</code> and <code>mc_ci</code>). If supplied, will override <code>boot_ci</code> and <code>mc_ci</code> . If <code>fit_method</code> is "regression" or "lm", then only "boot" is supported.

boot_type	The type of the bootstrap confidence intervals. Default is "perc", percentile confidence interval. Set "bc" for bias-corrected confidence interval. Ignored if ci_type is not "boot".
model	The type of model. For q_mediation() , it can be "simple" (simple mediation model), "serial" (serial mediation model), or "parallel" (parallel mediation model). It is recommended to call the corresponding wrappers directly (q_simple_mediation() , q_serial_mediation() , and q_parallel_mediation()) instead of call q_mediation() .
fit_method	How the model is to be fitted. If set to "lm" or "regression", linear regression will be used (fitted by stats::lm()). If set to "sem" or "lavaan", structural equation modeling will be used and the model will be fitted by lavaan::sem() . Default is "lm".
missing	If fit_method is set to "sem" or "lavaan", this argument determine how missing data is handled. The default value is "fiml" and full information maximum likelihood will be used to handle missing data. Please refer to lavaan::lavOptions for other options.
fixed.x	If fit_method is set to "sem" or "lavaan", this determines whether the observed predictors ("x" variables, including control variables) are treated as fixed variables or random variables. Default is TRUE, to mimic the same implicit setting in regression fitted by stats::lm() .
sem_args	If fit_method is set to "sem" or "lavaan", this is a named list of arguments to be passed to lavaan::sem() . Arguments listed here will not override missing and fixed.x.
na.action	How missing data is handled. Used only when fit_method is set to "sem" or "lavaan". If "na.pass", the default, then all data will be passed to lavaan, and full information maximum likelihood (fiml) will be used to handle missing data. If "na.omit", then listwise deletion will be used.
parallel	If TRUE, default, parallel processing will be used when doing bootstrapping.
ncores	Integer. The number of CPU cores to use when parallel is TRUE. Default is the number of non-logical cores minus one (one minimum). Will raise an error if greater than the number of cores detected by parallel::detectCores() . If ncores is set, it will override make_cluster_args in do_boot() .
progress	Logical. Display progress or not.
digits	Number of digits to display. Default is 4.
annotation	Logical. Whether the annotation after the table of effects is to be printed. Default is TRUE.
pvalue	Logical. If TRUE, asymmetric <i>p</i> -values based on bootstrapping will be printed if available. Default is TRUE.
pvalue_digits	Number of decimal places to display for the <i>p</i> -values. Default is 4.
se	Logical. If TRUE and confidence intervals are available, the standard errors of the estimates are also printed. They are simply the standard deviations of the bootstrap estimates. Default is TRUE.
for_each_path	Logical. If TRUE, each of the paths will be printed individually, using the print-method of the output of indirect_effect() . Default is FALSE.

se_ci	Logical. If TRUE and confidence interval has not been computed, the function will try to compute them from stored standard error if the original standard error is to be used. Ignored if confidence interval has already been computed. Default is TRUE.
wrap_computation	Logical. If TRUE, the default, long computational symbols and values will be wrapped to fit to the screen width.
lm_ci	If TRUE, when printing the regression results of <code>stats::lm()</code> , confidence interval based on t statistic and standard error will be computed and added to the output. Default is TRUE.
lm_beta	If TRUE, when printing the regression results of <code>stats::lm()</code> , standardized coefficients are computed and included in the printout. Only numeric variables will be computed, and any derived terms, such as product terms, will be formed <i>after</i> standardization. Default is TRUE.
lm_ci_level	The level of confidence of the confidence interval. Ignored if lm_ci is not TRUE.
sem_style	How the for the model is to be printed if the model is fitted by structural equation modeling (using lavaan). Default is "lm" and the results will be printed in a style similar to that of <code>summary()</code> output of <code>stats::lm()</code> . If "lavaan", the results will be printed in usual lavaan style.
...	Other arguments. If for_each_path is TRUE, they will be passed to the print method of the output of <code>indirect_effect()</code> . Ignored otherwise.

Details

The family of "q" (quick) functions are for testing mediation effects in common models. These functions do the following in one single call:

- Fit the linear models.
- Compute and test all the indirect effects.

They are easy-to-use and are suitable for common models with mediators. For now, there are "q" functions for these models:

- A simple mediation: One predictor (x), one mediator (m), one outcome (y), and optionally some control variables (covariates) (`q_simple_mediation()`)
- A serial mediation model: One predictor (x), one or more mediators (m), one outcome (y), and optionally some control variables (covariates). The mediators positioned sequentially between x and y (`q_serial_mediation()`):
 - $x \rightarrow m1 \rightarrow m2 \rightarrow \dots \rightarrow y$
- A parallel mediation model: One predictor (x), one or more mediators (m), one outcome (y), and optionally some control variables (covariates). The mediators positioned in parallel between x and y (`q_parallel_mediation()`):
 - $x \rightarrow m1 \rightarrow y$
 - $x \rightarrow m2 \rightarrow y$
 - ...

- An arbitrary mediation model: One predictor (x), one or more mediators (m), one outcome (y), and optionally some control variables (covariates). The mediators positioned in an arbitrary form between x and y, as long as there are no feedback loops (`q_mediation()`). For example:

- x -> m1
- m1 -> m21 -> y
- m1 -> m22 -> y
- ...

Users only need to specify the x, m, and y variables, and covariates or control variables, if any (by cov), and the functions will automatically identify all indirect effects and total effects.

Note that they are *not* intended to be flexible. For more complex models, it is recommended to fit the models manually, either by structural equation modelling (e.g., `lavaan::sem()`) or by regression analysis using `stats::lm()` or `lmhelps::many_lm()`. See https://sfcheung.github.io/manymome/articles/med_lm.html for an illustration on how to compute and test indirect effects for an arbitrary mediation model.

Specifying a Model of an Arbitrary Form:

If a custom model is to be estimated, instead of setting `model` to a name of the form ("simple", "serial", or "parallel"), set `model` to the paths between x and y. It can take one of the following two forms:

A character vector, each element a string of a path, with variable names connected by "->" (the spaces are optional):

```
c("x -> m11 -> m12 -> y",
  "x -> m2 -> y")
```

A list of character vectors, each vector is a vector of names representing a path, going from the first element to the last element:

```
list(c("x", "m11", "m12", "y"),
     c("x", "m2", "y"))
```

The two forms above specify the same model.

Paths not included are fixed to zero (i.e., does not "exist" in the model). A path can be specified more than once if this can enhance readability. For example:

```
c("x1 -> m1 -> m21 -> y1",
  "x1 -> m1 -> m22 -> y1")
```

The path "x1 -> m1" appears twice, to indicate two different pathways from x1 to y1.

Workflow:

The coefficients of the model can be estimated by one of these two methods: OLS (ordinary least squares) regression (setting `fit_method` to "regression" or "lm"), or path analysis (SEM, structural equation modeling, by setting `fit_method` to "sem" or "lavaan").

Regression:

This is the workflow of the "q" functions when estimating the coefficients by regression:

- Do listwise deletion based on all the variables used in the models.
- Generate the regression models based on the variables specified.

- Fit all the models by OLS regression using `stats::lm()`.
- Call `all_indirect_paths()` to identify all indirect paths.
- Call `many_indirect_effects()` to compute all indirect effects and form their confidence intervals.
- Call `total_indirect_effect()` to compute the total indirect effect.
- Return all the results for printing.

The output of the "q" functions have a `print` method for printing all the major results.

Path Analysis:

This is the workflow of the "q" functions when estimating the coefficients by path analysis (SEM):

- By default, cases with missing data only on the mediators and the outcome variable will be retained, and full information maximum likelihood (FIML) will be used to estimate the coefficients. (Controlled by `missing`, default to "fiml") using `lavaan::sem()`.
- Generate the SEM (lavaan) model syntax based on the model specified.
- Fit the model by path analysis using `lavaan::sem()`.
- Call `all_indirect_paths()` to identify all indirect paths.
- Call `many_indirect_effects()` to compute all indirect effects and form their confidence intervals.
- Call `total_indirect_effect()` to compute the total indirect effect.
- Return all the results for printing.

Testing the Indirect Effects:

Two methods are available for testing the indirect effects: nonparametric bootstrap confidence intervals (`ci_type` set to "boot") and Monte Carlo confidence intervals (`ci_type` set to "mc").

If the coefficients are estimated by OLS regression, only nonparametric bootstrap confidence intervals are supported.

If the coefficients are estimated by path analysis (SEM), then both methods are supported.

Printing the Results:

The output of the "q" functions have a `print` method for printing all the major results.

Notes:

Flexibility:

The "q" functions are designed to be easy to use. They are not designed to be flexible. For maximum flexibility, fit the models manually and call functions such as `indirect_effect()` separately. See https://sfcheung.github.io/manymome/articles/med_lm.html for illustrations.

Monte Carlo Confidence Intervals:

We do not recommend using Monte Carlo confidence intervals for models fitted by regression because the covariances between parameter estimates are assumed to be zero, which may not be the case in some models. Therefore, the "q" functions do not support Monte Carlo confidence intervals if OLS regression is used.

Value

The function `q_meditation()` returns a `q_meditation` class object, with its `print` method.

The function `q_simple_meditation()` returns a `q_simple_meditation` class object, which is a subclass of `q_meditation`.

The function `q_serial_meditation()` returns a `q_serial_meditation` class object, which is a subclass of `q_meditation`.

The function `q_parallel_meditation()` returns a `q_parallel_meditation` class object, which is a subclass of `q_meditation`.

Methods (by generic)

- `print(q_meditation)`: The `print` method of the outputs of `q_meditation()`, `q_simple_meditation()`, `q_serial_meditation()`, and `q_parallel_meditation()`.

Functions

- `q_meditation()`: The general "q" function for common mediation models. Not to be used directly.
- `q_simple_meditation()`: A wrapper of `q_meditation()` for simple mediation models (a model with only one mediator).
- `q_serial_meditation()`: A wrapper of `q_meditation()` for serial mediation models.
- `q_parallel_meditation()`: A wrapper of `q_meditation()` for parallel mediation models.

Author(s)

Idea to fit a model by structural equation modeling by Rong wei Sun <https://orcid.org/0000-0003-0034-1422>, implemented by Shu Fai Cheung <https://orcid.org/0000-0002-9871-9448>.

See Also

`lmhelpers::many_lm()` for fitting several regression models using model syntax, `indirect_effect()` for computing and testing a specific path, `all_indirect_paths()` for identifying all paths in a model, `many_indirect_effects()` for computing and testing indirect effects along several paths, and `total_indirect_effect()` for computing and testing the total indirect effects.

Examples

```
# ===== A user-specified mediation model

# Set R to 5000 or 10000 in real studies
# Remove 'parallel' or set it to TRUE for faster bootstrapping
# Remove 'progress' or set it to TRUE to see a progress bar

out <- q_meditation(x = "x1",
                     y = "y1",
                     model = c("x1 -> m11 -> m2 -> y1",
                             "x1 -> m12 -> m2 -> y1"),
                     cov = c("c2", "c1"),
```

```

data = data_med_complicated,
R = 40,
seed = 1234,
parallel = FALSE,
progress = FALSE)
# Suppressed printing of p-values due to the small R
# Remove `pvalue = FALSE` when R is large
print(out,
      pvalue = FALSE)

# ===== Simple mediation

# Set R to 5000 or 10000 in real studies
# Remove 'parallel' or set it to TRUE for faster bootstrapping
# Remove 'progress' or set it to TRUE to see a progress bar

out <- q_simple_mediati(x = "x",
                         y = "y",
                         m = "m",
                         cov = c("c2", "c1"),
                         data = data_med,
                         R = 20,
                         seed = 1234,
                         parallel = FALSE,
                         progress = FALSE)
# Suppressed printing of p-values due to the small R
# Remove `pvalue = FALSE` when R is large
print(out,
      pvalue = FALSE)

# # Different control variables for m and y
# out <- q_simple_mediati(x = "x",
#                         y = "y",
#                         m = "m",
#                         cov = list(m = "c1",
#                                    y = c("c1", "c2")),
#                         data = data_med,
#                         R = 100,
#                         seed = 1234,
#                         parallel = FALSE,
#                         progress = FALSE)
# out

# ===== Serial mediation

# Set R to 5000 or 10000 in real studies
# Remove 'parallel' or set it to TRUE for faster bootstrapping
# Remove 'progress' or set it to TRUE to see a progress bar

# out <- q_serial_mediati(x = "x",
#                         y = "y",

```



```

#                                     m2 = c("c2", "c1"),
#                                     y = "c2"),
#                                     data = data_parallel,
#                                     R = 100,
#                                     seed = 1234,
#                                     parallel = FALSE,
#                                     progress = FALSE)
# out

```

simple_mediati on_latent

Sample Dataset: A Simple Latent Mediation Model

Description

Generated from a simple mediation model among xthree latent factors, fx, fm, and fy, xeach has three indicators.

Usage

simple_mediati on_latent

Format

A data frame with 200 rows and 11 variables:

x1 Indicator of fx. Numeric.
x2 Indicator of fx. Numeric.
x3 Indicator of fx. Numeric.
m1 Indicator of fm. Numeric.
m2 Indicator of fm. Numeric.
m3 Indicator of fm. Numeric.
y1 Indicator of fy. Numeric.
y2 Indicator of fy. Numeric.
y3 Indicator of fy. Numeric.

Details

The model:

```

fx =~ x1 + x2 + x3
fm =~ m1 + m2 + m3
fy =~ y1 + y2 + y3
fm ~ a * fx
fy ~ b * fm + cp * fx
indirect := a * b

```

subsetting_cond_indirect_effects

Extraction Methods for 'cond_indirect_effects' Outputs

Description

For subsetting a 'cond_indirect_effects'-class object.

Usage

```
## S3 method for class 'cond_indirect_effects'
x[i, j, drop = if (missing(i)) TRUE else length(j) == 1]
```

Arguments

x	A 'cond_indirect_effects'-class object.
i	A numeric vector of row number(s), a character vector of row name(s), or a logical vector of row(s) to be selected.
j	A numeric vector of column number(s), a character vector of column name(s), or a logical vector of column(s) to be selected.
drop	Whether dropping a dimension if it only have one row/column.

Details

Customized `[` for 'cond_indirect_effects'-class objects, to ensure that these operations work as they would be on a data frame object, while information specific to conditional effects is modified correctly.

Value

A 'cond_indirect_effects'-class object. See [cond_indirect_effects\(\)](#) for details on this class.

Examples

```
library(lavaan)
dat <- modmed_x1m3w4y1
mod <-
"
m1 ~ x + w1 + x:w1
m2 ~ m1
y ~ m2 + x + w4 + m2:w4
"
fit <- sem(mod, dat, meanstructure = TRUE, fixed.x = FALSE, se = "none", baseline = FALSE)
est <- parameterEstimates(fit)

# Examples for cond_indirect():

# Conditional effects from x to m1 when w1 is equal to each of the levels
```

```

out1 <- cond_indirect_effects(x = "x", y = "m1",
                               wlevels = "w1", fit = fit)
out1[2, ]

# Conditional Indirect effect from x1 through m1 to y,
# when w1 is equal to each of the levels
out2 <- cond_indirect_effects(x = "x", y = "y", m = c("m1", "m2"),
                               wlevels = c("w1", "w4"), fit = fit)
out2[c(1, 3), ]

```

subsetting_wlevels *Extraction Methods for a 'wlevels'-class Object*

Description

For subsetting a 'wlevels'-class object. Attributes related to the levels will be preserved if appropriate.

Usage

```

## S3 method for class 'wlevels'
x[i, j, drop = if (missing(i)) TRUE else length(j) == 1]

## S3 replacement method for class 'wlevels'
x[i, j] <- value

## S3 replacement method for class 'wlevels'
x[[i, j]] <- value

```

Arguments

x	A 'wlevels'-class object.
i	A numeric vector of row number(s), a character vector of row name(s), or a logical vector of row(s) to be selected.
j	A numeric vector of column number(s), a character vector of column name(s), or a logical vector of column(s) to be selected.
drop	Whether dropping a dimension if it only have one row/column.
value	Ignored.

Details

Customized [`for 'wlevels'-class objects, to ensure that these operations work as they would be on a data frame object, while information specific to a wlevels-class object modified correctly.`

The assignment methods [`<-` and `[[<-` for wlevels-class objects will raise an error. This class of objects should be created by [mod_levels\(\)](#) or related functions.

Subsetting the output of `mod_levels()` is possible but not recommended. It is more reliable to generate the levels using `mod_levels()` and related functions. Nevertheless, there are situations in which subsetting is preferred.

Value

A 'wlevels'-class object. See `mod_levels()` and `merge_mod_levels()` for details on this class.

See Also

`mod_levels()`, `mod_levels_list()`, and `merge_mod_levels()`

Examples

```
data(data_med_mod_ab)
dat <- data_med_mod_ab
# Form the levels from a list of lm() outputs
lm_m <- lm(m ~ x*w1 + c1 + c2, dat)
lm_y <- lm(y ~ m*w2 + x + w1 + c1 + c2, dat)
lm_out <- lm2list(lm_m, lm_y)
w1_levels <- mod_levels(lm_out, w = "w1")
w1_levels
w1_levels[2, ]
w1_levels[c(2, 3), ]

dat <- data_med_mod_serial_cat
lm_m1 <- lm(m1 ~ x*w1 + c1 + c2, dat)
lm_y <- lm(y ~ m1 + x + w1 + c1 + c2, dat)
lm_out <- lm2list(lm_m1, lm_y)
w1gp_levels <- mod_levels(lm_out, w = "w1")
w1gp_levels
w1gp_levels[2, ]
w1gp_levels[3, ]

merged_levels <- merge_mod_levels(w1_levels, w1gp_levels)
merged_levels

merged_levels[4:6, ]
merged_levels[1:3, c(2, 3)]
merged_levels[c(1, 4, 7), 1, drop = FALSE]
```

summary.lm_list *Summary of an lm_list-Class Object*

Description

The summary of content of the output of `lm2list()`.

Usage

```
## S3 method for class 'lm_list'
summary(object, betaselect = FALSE, ci = FALSE, level = 0.95, ...)

## S3 method for class 'summary_lm_list'
print(x, digits = 3, digits_decimal = NULL, ...)
```

Arguments

object	The output of <code>lm2list()</code> .
betaselect	If TRUE, standardized coefficients are computed and included in the printout. Only numeric variables will be computed, and any derived terms, such as product terms, will be formed <i>after</i> standardization. Default is FALSE.
ci	If TRUE, confidence interval based on t statistic and standard error will be computed and added to the output. Default is FALSE.
level	The level of confidence of the confidence interval. Ignored if ci is not TRUE.
...	Other arguments. Not used.
x	An object of class <code>summary_lm_list</code> .
digits	The number of significant digits in printing numerical results.
digits_decimal	The number of digits after the decimal in printing numerical results. Default is NULL. If set to an integer, numerical results in the coefficient table will be printed according this setting, and digits will be ignored.

Value

`summary.lm_list()` returns a `summary_lm_list`-class object, which is a list of the `summary()` outputs of the `lm()` outputs stored.

`print.summary_lm_list()` returns x invisibly. Called for its side effect.

Functions

- `print(summary_lm_list)`: Print method for output of summary for `lm_list`.

Examples

```
data(data_serial_parallel)
lm_m11 <- lm(m11 ~ x + c1 + c2, data_serial_parallel)
lm_m12 <- lm(m12 ~ m11 + x + c1 + c2, data_serial_parallel)
lm_m2 <- lm(m2 ~ x + c1 + c2, data_serial_parallel)
lm_y <- lm(y ~ m11 + m12 + m2 + x + c1 + c2, data_serial_parallel)
# Join them to form a lm_list-class object
lm_serial_parallel <- lm2list(lm_m11, lm_m12, lm_m2, lm_y)
lm_serial_parallel
summary(lm_serial_parallel)
```

terms.lm_from_lavaan *Model Terms of an 'lm_from_lavaan'-Class Object*

Description

It extracts the terms object from an lm_from_lavaan-class object.

Usage

```
## S3 method for class 'lm_from_lavaan'  
terms(x, ...)
```

Arguments

x	An 'lm_from_lavaan'-class object.
...	Additional arguments. Ignored.

Details

A method for lm_from_lavaan-class that converts a regression model for a variable in a lavaan model to a formula object. This function simply calls [stats::terms\(\)](#) on the formula object to extract the predictors of a variable.

Value

A terms-class object. See [terms.object](#) for details.

See Also

[terms.object](#), [lm_from_lavaan_list\(\)](#)

Examples

```
library(lavaan)  
data(data_med)  
mod <-  
"  
m ~ a * x + c1 + c2  
y ~ b * m + x + c1 + c2  
"  
fit <- sem(mod, data_med, fixed.x = FALSE)  
fit_list <- lm_from_lavaan_list(fit)  
terms(fit_list$m)  
terms(fit_list$y)
```

total_indirect_effect *Total Indirect Effect Between Two Variables*

Description

Compute the total indirect effect between two variables in the paths estimated by [many_indirect_effects\(\)](#).

Usage

```
total_indirect_effect(object, x, y)
```

Arguments

object	The output of many_indirect_effects() , or a list of indirect-class objects.
x	Character. The name of the x variable. All paths starting from x will be included. Can be omitted if all paths have the same x.
y	Character. The name of the y variable. All paths ending at y will be included. Can be omitted if all paths have the same y.

Details

It extracts the indirect-class objects of relevant paths and then add the indirect effects together using the + operator.

Value

An indirect-class object.

See Also

[many_indirect_effects\(\)](#)

Examples

```
library(lavaan)
data(data_serial_parallel)
mod <-
  "
m11 ~ x + c1 + c2
m12 ~ m11 + x + c1 + c2
m2 ~ x + c1 + c2
y ~ m12 + m2 + m11 + x + c1 + c2
"
fit <- sem(mod, data_serial_parallel,
           fixed.x = FALSE)

# All indirect paths, control variables excluded
paths <- all_indirect_paths(fit,
```

```
exclude = c("c1", "c2"))
paths

# Indirect effect estimates
out <- many_indirect_effects(paths,
                               fit = fit)
out

# Total indirect effect from x to y
total_indirect_effect(out,
                      x = "x",
                      y = "y")
```

Index

* **datasets**

- data_med, 36
- data_med_complicated, 36
- data_med_complicated_mg, 37
- data_med_mg, 38
- data_med_mod_a, 39
- data_med_mod_ab, 40
- data_med_mod_ab1, 41
- data_med_mod_b, 42
- data_med_mod_b_mod, 43
- data_med_mod_parallel, 44
- data_med_mod_parallel_cat, 45
- data_med_mod_serial, 46
- data_med_mod_serial_cat, 47
- data_med_mod_serial_parallel, 48
- data_med_mod_serial_parallel_cat, 49
- data_mod, 50
- data_mod2, 50
- data_mod_cat, 51
- data_mome_demo, 52
- data_mome_demo_missing, 53
- data_parallel, 54
- data_sem, 55
- data_serial, 56
- data_serial_parallel, 57
- data_serial_parallel_latent, 58
- modmed_x1m3w4y1, 93
- simple_mediation_latent, 144

+.indirect (math_indirect), 90

-.indirect (math_indirect), 90

[.cond_indirect_effects

- (subsetting_cond_indirect_effects), 145

[.wlevels (subsetting_wlevels), 146

[<- .wlevels (subsetting_wlevels), 146

[[<- .wlevels (subsetting_wlevels), 146

all_indirect_paths, 4

all_indirect_paths(), 4, 5, 21, 113, 114, 140, 141

all_paths_to_df (all_indirect_paths), 4

all_paths_to_df(), 5

as.data.frame.cond_indirect_effects

- (print.cond_indirect_effects), 117

check_path, 6

coef.cond_indirect_diff, 8

coef.cond_indirect_diff(), 27, 77

coef.cond_indirect_effects, 9

coef.cond_indirect_effects(), 23

coef.delta_med, 10

coef.delta_med(), 61, 62

coef.indirect, 11

coef.indirect(), 23, 83

coef.indirect_list, 12

coef.indirect_proportion, 14

coef.indirect_proportion(), 85

coef.lm_from_lavaan, 15

cond_effects (cond_indirect), 16

cond_effects(), 119

cond_indirect, 16

cond_indirect(), 11, 12, 19–23, 32, 33, 62–66, 72, 76, 77, 83, 87, 90, 91, 94, 96, 122, 124

cond_indirect_diff, 26

cond_indirect_diff(), 8, 27, 28, 116

cond_indirect_effects, 72

cond_indirect_effects (cond_indirect), 16

cond_indirect_effects(), 9, 19–23, 26, 27, 29, 30, 62–66, 69–72, 76–78, 81, 83, 86–88, 92, 94, 96, 98–100, 106–108, 117, 119, 130–132, 145

confint.cond_indirect_diff, 28

confint.cond_indirect_diff(), 27, 77

confint.cond_indirect_effects, 29

confint.cond_indirect_effects(), 23

confint.delta_med, 31
confint.delta_med(), 61, 62
confint.indirect, 32
confint.indirect(), 23, 83
confint.indirect_list, 34

data_med, 36
data_med_complicated, 36
data_med_complicated_mg, 37
data_med_mg, 38
data_med_mod_a, 39
data_med_mod_ab, 40
data_med_mod_ab1, 41
data_med_mod_b, 42
data_med_mod_b_mod, 43
data_med_mod_parallel, 44
data_med_mod_parallel_cat, 45
data_med_mod_serial, 46
data_med_mod_serial_cat, 47
data_med_mod_serial_parallel, 48
data_med_mod_serial_parallel_cat, 49
data_mod, 50
data_mod2, 50
data_mod_cat, 51
data_mome_demo, 52, 54
data_mome_demo_missing, 53
data_parallel, 54
data_sem, 55
data_serial, 56
data_serial_parallel, 57
data_serial_parallel_latent, 58
delta_med, 59
delta_med(), 10, 11, 31, 120, 121
do_boot, 23, 62
do_boot(), 19, 20, 22, 23, 60, 65, 69, 76, 86, 87, 114, 137
do_mc, 64
do_mc(), 20, 22, 70, 71, 77, 129

factor2var, 67
fill_wlevels(plot_effect_vs_w), 105
fill_wlevels(), 108
fit2boot_out, 68
fit2boot_out(), 63, 64, 69
fit2boot_out_do_boot(fit2boot_out), 68
fit2boot_out_do_boot(), 63, 64, 69
fit2mc_out, 70
fit2mc_out(), 66, 70

gen_mc_est (do_mc), 64
get_one_cond_effect
 (get_one_cond_indirect_effect), 71
get_one_cond_effect(), 72
get_one_cond_indirect_effect, 71
get_one_cond_indirect_effect(), 72
get_prod, 73
ggplot2::facet_grid(), 99
ggplot2::geom_line(), 106, 107
ggplot2::geom_point(), 99
ggplot2::geom_ribbon(), 107
ggplot2::geom_segment(), 99

igraph::all_simple_paths(), 5
index_of_mome, 75
index_of_mome(), 27, 77
index_of_momome(index_of_mome), 75
index_of_momome(), 27, 77
indirect_effect(cond_indirect), 16
indirect_effect(), 5, 11, 12, 19–23, 32, 33, 62–66, 69–72, 76, 77, 81, 83, 86–88, 90, 91, 94, 122, 124, 125, 137, 138, 140, 141
indirect_effects_from_list, 79
indirect_i, 81
indirect_on_plot(plot.q_mediation), 101
indirect_on_plot(), 104
indirect_proportion, 84
indirect_proportion(), 14, 127

johnson_neyman (pseudo_johnson_neyman), 130
johnson_neyman(), 131

lavaan.mi::lavaan.mi(), 7, 19, 65, 70, 74, 76, 81, 84, 94
lavaan.mi::sem.mi(), 7, 16, 19, 65, 70, 74, 76, 81, 84, 94, 131
lavaan::lav_model_implied(), 61
lavaan::lav_model_set_parameters(), 61
lavaan::lavaan, 4, 19–21, 60, 68, 70, 74, 81, 84, 94
lavaan::lavaan(), 4, 89
lavaan::lavInspect(), 19, 61, 82
lavaan::lavOptions, 137
lavaan::parameterEstimates(), 4, 7, 19–21, 69, 74, 82

lavaan::sem(), 4, 16, 21, 22, 63, 65, 67–70, 74, 87, 131, 137, 139, 140
 lm(), 4, 7, 16, 19–21, 63, 74, 76, 81, 84, 86, 87, 94, 113, 131, 148
 lm2boot_out, 85
 lm2boot_out(), 63, 64
 lm2boot_out_parallel(lm2boot_out), 85
 lm2list, 87
 lm2list(), 4, 5, 7, 19, 63, 76, 86, 94, 113, 128, 147, 148
 lm_from_lavaan_list, 89
 lm_from_lavaan_list(), 15, 110, 112, 149
 lmhelps::many_lm(), 139, 141
 many_indirect_effects(cond_indirect), 16
 many_indirect_effects(), 5, 12, 13, 21–23, 34, 35, 79, 80, 125, 126, 140, 141, 150
 math_indirect, 23, 90
 merge_mod_levels, 92
 merge_mod_levels(), 21, 23, 27, 95, 96, 147
 mod_levels, 94
 mod_levels(), 23, 27, 92, 95, 96, 146, 147
 mod_levels_list(mod_levels), 94
 mod_levels_list(), 21, 92, 95, 96, 147
 modmed_x1m3w4y1, 93
 parallel::detectCores(), 20, 63, 68, 86, 137
 parallel::makeCluster(), 20, 63, 68, 86
 plot.cond_indirect_effects, 97
 plot.cond_indirect_effects(), 15, 89, 110, 111
 plot.q_mediation, 101
 plot_effect_vs_w, 105
 plot_effect_vs_w(), 108, 132
 predict.lm_from_lavaan, 110
 predict.lm_from_lavaan_list, 89, 111
 predict.lm_from_lavaan_list(), 89
 predict.lm_list, 112
 print.all_paths, 113
 print.boot_out, 114
 print.cond_indirect_diff, 115
 print.cond_indirect_diff(), 27, 77
 print.cond_indirect_effects, 117
 print.cond_indirect_effects(), 23
 print.delta_med, 120
 print.delta_med(), 61, 62
 print.indirect, 122
 print.indirect(), 23, 83
 print.indirect_list, 125
 print.indirect_proportion, 127
 print.indirect_proportion(), 85
 print.lm_list, 128
 print.lm_list(), 88
 print.mc_out, 129
 print.pseudo_johnson_neyman
 (pseudo_johnson_neyman), 130
 print.pseudo_johnson_neyman(), 132
 print.q_mediation(q_mediation), 133
 print.summary_lm_list
 (summary.lm_list), 147
 print.summary_lm_list(), 148
 print_all_cond_effects
 (get_one_cond_indirect_effect), 71
 print_all_cond_effects(), 72
 print_all_cond_indirect_effects
 (get_one_cond_indirect_effect), 71
 print_all_cond_indirect_effects(), 72
 pseudo_johnson_neyman, 130
 pseudo_johnson_neyman(), 107, 108, 131, 132
 q_mediation, 133
 q_mediation(), 102–104, 136, 137, 139, 141
 q_parallel_mediation(q_mediation), 133
 q_parallel_mediation(), 102, 104, 136–138, 141
 q_serial_mediation(q_mediation), 133
 q_serial_mediation(), 102, 104, 136–138, 141
 q_simple_mediation(q_mediation), 133
 q_simple_mediation(), 102, 104, 136–138, 141
 semPlot::semPaths(), 102–104
 semtools::auto_layout_mediation(), 103
 semtools::move_node(), 104
 simple_mediation_latent, 144
 stats::lm(), 30, 33, 65, 82, 108, 119, 123, 137–140
 stats::optimize(), 130, 131
 stats::predict(), 113
 stats::terms(), 149

stats::uniroot(), [130, 131](#)
subsetting_cond_indirect_effects, [145](#)
subsetting_wlevels, [146](#)
summary(), [4, 20, 21, 82, 138, 148](#)
summary.lm_list, [147](#)
summary.lm_list(), [88, 148](#)
terms.lm_from_lavaan, [149](#)
terms.object, [149](#)
total_indirect_effect, [150](#)
total_indirect_effect(), [140, 141](#)