

Package ‘virustotal’

December 16, 2025

Title R Client for the VirusTotal API

Version 0.5.0

Author Gaurav Sood [aut, cre]

Maintainer Gaurav Sood <gsood07@gmail.com>

Description Provides a comprehensive R interface to the VirusTotal API (v2 and v3), a Google service that analyzes files and URLs for viruses, worms, trojans and other malware. Features include file/URL scanning, domain categorization, passive DNS information, IP reputation analysis, and comment/voting systems. Implements rate limiting, error handling, and response validation for robust security analysis workflows.

URL <https://github.com/themains/virustotal>,
<https://themains.github.io/virustotal/>,
<http://themains.github.io/virustotal/>

BugReports <https://github.com/themains/virustotal/issues>

Depends R (>= 4.0.0)

License MIT + file LICENSE

VignetteBuilder knitr

Encoding UTF-8

Language en-US

Imports httr (>= 1.4.0), dplyr (>= 1.0.0), base64enc (>= 0.1-3),
jsonlite (>= 1.7.0), checkmate (>= 2.0.0), rlang (>= 1.0.0)

Suggests knitr (>= 1.30), rmarkdown (>= 2.0), testthat (>= 3.0.0),
lintr (>= 3.0.0), httptest (>= 4.0.0), covr, pkgdown, spelling

RoxygenNote 7.3.3

Config/testthat/edition 3

Config/Needs/website pkgdown

NeedsCompilation no

Repository CRAN

Date/Publication 2025-12-16 06:10:12 UTC

Contents

add_comments	2
domain_report	4
download_file	5
file_report	6
get_domain_comments	7
get_domain_info	8
get_domain_relationship	9
get_domain_votes	10
get_file_comments	11
get_file_download_url	12
get_file_relationships	13
get_file_upload_url	14
get_file_votes	15
get_ip_comments	16
get_ip_info	17
get_ip_votes	18
get_url_comments	19
get_url_relationships	20
get_url_votes	21
ip_report	22
post_domain_comments	23
post_domain_votes	24
post_file_comments	25
post_file_votes	26
post_ip_comments	27
post_ip_votes	28
post_url_comments	29
post_url_votes	30
rescan_file	31
scan_file	32
scan_url	33
set_key	34
url_report	34
virustotal_info	35
virustotal_version	36
Index	37

add_comments	<i>Add comments on Files and URLs</i>
--------------	---------------------------------------

Description

Add comments on files and URLs. For instance, flagging false positives, adding details about malware, instructions for cleaning malware, etc.

Usage

```
add_comments(hash = NULL, comment = NULL, ...)
```

Arguments

hash	hash for the resource you want to comment on; Required; String
comment	review; Required; String
...	Additional arguments passed to virustotal2_POST .

Value

data.frame with 2 columns: response_code, verbose_msg

- If the hash is incorrect or a duplicate comment is posted, response_code will be 0
- If the hash is incorrect, verbose_msg will be 'Invalid resource'
- If a duplicate comment is posted, verbose_msg will be 'Duplicate comment'
- If a comment is posted successfully, response_code will be 1 and verbose_msg will be 'Your comment was successfully posted'

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
  
# Before calling the function, set the API key using set_key('api_key_here')  
add_comments(hash='99017f6eebbac24f351415dd410d522d', comment="This is great.")  
  
## End(Not run)
```

`domain_report`*Get Domain Report*

Description

Retrieves comprehensive analysis report for a given domain, including WHOIS information, DNS resolutions, detected URLs, and threat intelligence data.

Usage

```
domain_report(domain, ...)
```

Arguments

<code>domain</code>	Domain name (character string). Required.
<code>...</code>	Additional arguments passed to virustotal_GET

Value

A `virustotal_domain_report` object containing domain analysis results including WHOIS data, DNS resolutions, detected URLs, categories, and threat intelligence

References

<https://docs.virustotal.com/reference/domains>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
# Set API key first  
set_key('your_api_key_here')  
  
# Get domain reports  
report1 <- domain_report("google.com")  
report2 <- domain_report("https://www.example.com/path")  
  
print(report1)  
summary(report1)  
  
## End(Not run)
```

download_file	<i>Download a file from VirusTotal</i>
---------------	--

Description

Download a file from VirusTotal

Usage

```
download_file(hash = NULL, output_path = NULL, ...)
```

Arguments

hash	File hash (MD5, SHA1, or SHA256)
output_path	Local path to save the downloaded file. Optional.
...	Additional arguments passed to virustotal_GET .

Value

Raw file content or saves file to specified path

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:

# Before calling the function, set the API key using set_key('api_key_here')

download_file(hash='99017f6eebbac24f351415dd410d522d',
              output_path='/tmp/downloaded_file')

## End(Not run)
```

`file_report`*Get File Scan Report*

Description

Retrieves detailed analysis results for a file from VirusTotal using the v3 API.

Usage

```
file_report(hash, ...)
```

Arguments

<code>hash</code>	File hash (MD5, SHA1, or SHA256) or analysis ID
<code>...</code>	Additional arguments passed to virustotal_GET

Value

A `virustotal_file_report` object containing file analysis results including antivirus scans, file metadata, and threat detection information

References

<https://docs.virustotal.com/reference/files>

See Also

[set_key](#) for setting the API key, [scan_file](#) for submitting files

Examples

```
## Not run:  
# Set API key first  
set_key('your_api_key_here')  
  
# Get file report using hash  
report <- file_report(hash = '99017f6eebbac24f351415dd410d522d')  
print(report)  
summary(report)  
  
# Convert to data.frame if needed  
df <- as.data.frame(report)  
  
## End(Not run)
```

get_domain_comments	<i>Retrieve comments for an Internet domain</i>
---------------------	---

Description

Retrieve comments for an Internet domain

Usage

```
get_domain_comments(domain = NULL, limit = limit, cursor = cursor, ...)
```

Arguments

domain	domain name. String. Required.
limit	Number of entries. Integer. Optional. Default is 10.
cursor	String. Optional.
...	Additional arguments passed to virustotal_GET .

Value

named list with the following possible items: `BitDefender category`, undetected_referrer_samples, whois_timestamp, detected_downloaded_samples, detected_referrer_samples, `Webutation domain info`, `Alexa category`, undetected_downloaded_samples, resolutions, detected_communicating_samples, `Opera domain info`, `TrendMicro category`, categories, domain_siblings, `BitDefender domain info`, whois, `Alexa domain info`, response_code, verbose_msg, `Websense ThreatSeeker category`, subdomains, `WOT domain info`, detected_urls, `Alexa rank`, undetected_communicating_samples, `Dr.Web category`, pcaps

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:

# Before calling the function, set the API key using set_key('api_key_here')

get_domain_comments("http://www.google.com")
get_domain_comments("http://www.goodsfwr fw.com") # Domain not found

## End(Not run)
```

get_domain_info	<i>Retrieve information about an Internet domain</i>
-----------------	--

Description

Retrieve information about an Internet domain

Usage

```
get_domain_info(domain = NULL, limit = NULL, cursor = NULL, ...)
```

Arguments

domain	domain name. String. Required.
limit	Number of entries. Integer. Optional. Default is 10.
cursor	String. Optional.
...	Additional arguments passed to virustotal_GET .

Value

named list

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
  
# Before calling the function, set the API key using set_key('api_key_here')  
  
get_domain_info("http://www.google.com")  
get_domain_info("http://www.goodsfwr fw.com") # Domain not found  
  
## End(Not run)
```

`get_domain_relationship`*Retrieve related objects to an Internet domain*

Description

Retrieve related objects to an Internet domain

Usage

```
get_domain_relationship(  
    domain = NULL,  
    relationship = "subdomains",  
    limit = NULL,  
    cursor = NULL,  
    ...  
)
```

Arguments

<code>domain</code>	domain name. String. Required.
<code>relationship</code>	relationship name. String. Required. Default is subdomains. For all the options see https://docs.virustotal.com/reference
<code>limit</code>	Number of entries. Integer. Optional. Default is 10.
<code>cursor</code>	String. Optional.
<code>...</code>	Additional arguments passed to virustotal_GET .

Value

named list

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
  
# Before calling the function, set the API key using set_key('api_key_here')  
  
get_domain_relationship("https://www.google.com")  
get_domain_relationship("https://www.goodsfwrwfw.com") # Domain not found
```

```
## End(Not run)
```

get_domain_votes	<i>Retrieve votes for an Internet domain</i>
------------------	--

Description

Retrieve votes for an Internet domain

Usage

```
get_domain_votes(domain = NULL, limit = NULL, cursor = NULL, ...)
```

Arguments

domain	domain name. String. Required.
limit	Number of entries. Integer. Optional. Default is 10.
cursor	String. Optional.
...	Additional arguments passed to virustotal_GET .

Value

named list

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:

# Before calling the function, set the API key using set_key('api_key_here')

get_domain_votes("http://www.google.com")
get_domain_votes("http://www.goodsfwrfrw.com") # Domain not found

## End(Not run)
```

get_file_comments	<i>Retrieve comments for a file</i>
-------------------	-------------------------------------

Description

Retrieve comments for a file

Usage

```
get_file_comments(hash = NULL, limit = NULL, cursor = NULL, ...)
```

Arguments

hash	File hash (MD5, SHA1, or SHA256)
limit	Number of comments to retrieve. Integer. Optional. Default is 10.
cursor	String for pagination. Optional.
...	Additional arguments passed to virustotal_GET .

Value

list containing file comments

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
  
# Before calling the function, set the API key using set_key('api_key_here')  
  
get_file_comments(hash='99017f6eebbac24f351415dd410d522d')  
  
## End(Not run)
```

get_file_download_url *Get download URL for a file*

Description

Get download URL for a file

Usage

```
get_file_download_url(hash = NULL, ...)
```

Arguments

hash	File hash (MD5, SHA1, or SHA256)
...	Additional arguments passed to virustotal_GET .

Value

list containing download URL and metadata

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
  
# Before calling the function, set the API key using set_key('api_key_here')  
  
get_file_download_url(hash='99017f6eebbac24f351415dd410d522d')  
  
## End(Not run)
```

`get_file_relationships`*Retrieve relationships for a file*

Description

Retrieve relationships for a file

Usage

```
get_file_relationships(  
    hash = NULL,  
    relationship = NULL,  
    limit = NULL,  
    cursor = NULL,  
    ...  
)
```

Arguments

<code>hash</code>	File hash (MD5, SHA1, or SHA256)
<code>relationship</code>	Type of relationship: "behaviours", "bundled_files", "compression_parents", "contacted_domains", "contacted_ips", "contacted_urls", "dropped_files", "execution_parents", "itw_domains", "itw_ips", "itw_urls", "overlay_parents", "pcap_parents", "pe_resource_parents", "similar_files", "submissions"
<code>limit</code>	Number of relationships to retrieve. Integer. Optional. Default is 10.
<code>cursor</code>	String for pagination. Optional.
<code>...</code>	Additional arguments passed to virustotal_GET .

Value

list containing file relationships

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:

# Before calling the function, set the API key using set_key('api_key_here')

get_file_relationships(hash='99017f6eebbac24f351415dd410d522d',
                      relationship='contacted_domains')

## End(Not run)
```

get_file_upload_url	<i>Get file upload URL for large files</i>
---------------------	--

Description

Get a special URL for uploading files larger than 32MB to VirusTotal for analysis.

Usage

```
get_file_upload_url(...)
```

Arguments

... Additional arguments passed to [virustotal_GET](#).

Value

list containing upload URL and other metadata

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key, [scan_file](#) for regular file uploads

Examples

```
## Not run:

# Before calling the function, set the API key using set_key('api_key_here')

get_file_upload_url()

## End(Not run)
```

get_file_votes	<i>Retrieve votes for a file</i>
----------------	----------------------------------

Description

Retrieve votes for a file

Usage

```
get_file_votes(hash = NULL, limit = NULL, cursor = NULL, ...)
```

Arguments

hash	File hash (MD5, SHA1, or SHA256)
limit	Number of votes to retrieve. Integer. Optional. Default is 10.
cursor	String for pagination. Optional.
...	Additional arguments passed to virustotal_GET .

Value

list containing file votes

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
  
# Before calling the function, set the API key using set_key('api_key_here')  
  
get_file_votes(hash='99017f6eebbac24f351415dd410d522d')  
  
## End(Not run)
```

get_ip_comments	<i>Retrieve comments for an IP address</i>
-----------------	--

Description

Retrieve comments for an IP address

Usage

```
get_ip_comments(ip = NULL, limit = NULL, cursor = NULL, ...)
```

Arguments

ip	IP Address. String. Required.
limit	Number of entries. Integer. Optional. Default is 10.
cursor	String. Optional.
...	Additional arguments passed to virustotal_GET .

Value

named list

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
  
# Before calling the function, set the API key using set_key('api_key_here')  
  
get_ip_comments("64.233.160.0")  
  
## End(Not run)
```

`get_ip_info`*Retrieve information about an IP address*

Description

Retrieves report on a given domain, including passive DNS, urls detected by at least one url scanner. Gives category of the domain from bitdefender.

Usage

```
get_ip_info(ip = NULL, limit = NULL, cursor = NULL, ...)
```

Arguments

<code>ip</code>	IP address. String. Required.
<code>limit</code>	Number of entries. Integer. Optional. Default is 10.
<code>cursor</code>	String. Optional.
<code>...</code>	Additional arguments passed to virustotal_GET .

Value

named list

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
  
# Before calling the function, set the API key using set_key('api_key_here')  
  
get_ip_info("64.233.160.0")  
  
## End(Not run)
```

get_ip_votes	<i>Retrieve votes for an IP address</i>
--------------	---

Description

Retrieve votes for an IP address

Usage

```
get_ip_votes(ip = NULL, limit = NULL, cursor = NULL, ...)
```

Arguments

ip	IP address. String. Required.
limit	Number of entries. Integer. Optional. Default is 10.
cursor	String. Optional.
...	Additional arguments passed to virustotal_GET .

Value

named list

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
  
# Before calling the function, set the API key using set_key('api_key_here')  
  
get_ip_votes("64.233.160.0")  
  
## End(Not run)
```

get_url_comments	<i>Retrieve comments for a URL</i>
------------------	------------------------------------

Description

Retrieve comments for a URL

Usage

```
get_url_comments(url_id = NULL, limit = NULL, cursor = NULL, ...)
```

Arguments

url_id	URL or URL ID from VirusTotal
limit	Number of comments to retrieve. Integer. Optional. Default is 10.
cursor	String for pagination. Optional.
...	Additional arguments passed to virustotal_GET .

Value

list containing URL comments

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
  
# Before calling the function, set the API key using set_key('api_key_here')  
get_url_comments(url_id='http://www.google.com')  
  
## End(Not run)
```



```
## End(Not run)
```

get_url_votes	<i>Retrieve votes for a URL</i>
---------------	---------------------------------

Description

Retrieve votes for a URL

Usage

```
get_url_votes(url_id = NULL, limit = NULL, cursor = NULL, ...)
```

Arguments

url_id	URL or URL ID from VirusTotal
limit	Number of votes to retrieve. Integer. Optional. Default is 10.
cursor	String for pagination. Optional.
...	Additional arguments passed to virustotal_GET .

Value

list containing URL votes

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
  
# Before calling the function, set the API key using set_key('api_key_here')  
  
get_url_votes(url_id='http://www.google.com')  
  
## End(Not run)
```

`ip_report`*Get IP Address Report*

Description

Retrieves comprehensive analysis report for an IP address, including geolocation, ASN information, DNS resolutions, and detected URLs.

Usage

```
ip_report(ip = NULL, ...)
```

Arguments

<code>ip</code>	a valid IPv4 or IPv6 address; String; Required
<code>...</code>	Additional arguments passed to <code>virustotal_GET</code> .

Value

list containing IP analysis results including geolocation, ASN information, DNS resolutions, detected URLs, and threat intelligence

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:

# Before calling the function, set the API key using set_key('api_key_here')

ip_report(ip="8.8.8.8")
ip_report(ip="2001:4860:4860::8888") # IPv6 example

## End(Not run)
```

post_domain_comments *Add a comment to an Internet domain*

Description

Add a comment to an Internet domain

Usage

```
post_domain_comments(domain = NULL, comment = NULL, ...)
```

Arguments

domain	domain name. String. Required.
comment	vote. String. Required. Any word starting with # in your comment's text will be considered a tag, and added to the comment's tag attribute.
...	Additional arguments passed to virustotal_POST .

Value

named list

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
  
# Before calling the function, set the API key using set_key('api_key_here')  
  
post_domain_comments(domain = "https://google.com", comment = "Great!")  
  
## End(Not run)
```

post_domain_votes	<i>Add a vote for a hostname or domain</i>
-------------------	--

Description

Add a vote for a hostname or domain

Usage

```
post_domain_votes(domain = NULL, vote = NULL, ...)
```

Arguments

domain	domain name. String. Required.
vote	vote. String. Required.
...	Additional arguments passed to virustotal_POST .

Value

named list

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
  
# Before calling the function, set the API key using set_key('api_key_here')  
  
post_domain_votes("http://google.com", vote = "malicious")  
  
## End(Not run)
```

post_file_comments	<i>Add a comment to a file</i>
--------------------	--------------------------------

Description

Add a comment to a file

Usage

```
post_file_comments(hash = NULL, comment = NULL, ...)
```

Arguments

hash	File hash (MD5, SHA1, or SHA256)
comment	Comment text to add
...	Additional arguments passed to virustotal_POST .

Value

list containing response data

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
  
# Before calling the function, set the API key using set_key('api_key_here')  
  
post_file_comments(hash='99017f6eebbac24f351415dd410d522d',  
                   comment='This file appears to be suspicious')  
  
## End(Not run)
```

post_file_votes	<i>Add a vote to a file</i>
-----------------	-----------------------------

Description

Add a vote to a file

Usage

```
post_file_votes(hash = NULL, verdict = NULL, ...)
```

Arguments

hash	File hash (MD5, SHA1, or SHA256)
verdict	Vote verdict: "harmless" or "malicious"
...	Additional arguments passed to virustotal_POST .

Value

list containing response data

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
  
# Before calling the function, set the API key using set_key('api_key_here')  
  
post_file_votes(hash='99017f6eebbac24f351415dd410d522d', verdict='malicious')  
  
## End(Not run)
```

post_ip_comments	<i>Add a comment to an IP address</i>
------------------	---------------------------------------

Description

Add a comment to an IP address

Usage

```
post_ip_comments(ip = NULL, comment = NULL, ...)
```

Arguments

ip	IP address. String. Required.
comment	Comment. String. Required.
...	Additional arguments passed to virustotal_POST .

Value

named list

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
  
# Before calling the function, set the API key using set_key('api_key_here')  
  
post_ip_comments(ip = "64.233.160.0", comment = "test")  
  
## End(Not run)
```

post_ip_votes	<i>Add a vote for a IP address</i>
---------------	------------------------------------

Description

Add a vote for a IP address

Usage

```
post_ip_votes(ip = NULL, vote = NULL, ...)
```

Arguments

ip	IP address. String. Required.
vote	vote. String. Required.
...	Additional arguments passed to virustotal_POST .

Value

named list

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
  
# Before calling the function, set the API key using set_key('api_key_here')  
  
post_ip_votes(ip = "64.233.160.0", vote = "malicious")  
  
## End(Not run)
```

post_url_comments	<i>Add a comment to a URL</i>
-------------------	-------------------------------

Description

Add a comment to a URL

Usage

```
post_url_comments(url_id = NULL, comment = NULL, ...)
```

Arguments

url_id	URL or URL ID from VirusTotal
comment	Comment text to add
...	Additional arguments passed to virustotal_POST .

Value

list containing response data

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:

# Before calling the function, set the API key using set_key('api_key_here')

post_url_comments(url_id='http://www.google.com',
                  comment='This URL appears suspicious')

## End(Not run)
```

post_url_votes	<i>Add a vote to a URL</i>
----------------	----------------------------

Description

Add a vote to a URL

Usage

```
post_url_votes(url_id = NULL, verdict = NULL, ...)
```

Arguments

url_id	URL or URL ID from VirusTotal
verdict	Vote verdict: "harmless" or "malicious"
...	Additional arguments passed to virustotal_POST .

Value

list containing response data

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
  
# Before calling the function, set the API key using set_key('api_key_here')  
  
post_url_votes(url_id='http://www.google.com', verdict='harmless')  
  
## End(Not run)
```

rescan_file	<i>Request rescan of a file</i>
-------------	---------------------------------

Description

Request a new analysis of a file already present in VirusTotal's database. Returns an analysis ID that can be used to retrieve the report using [file_report](#).

Usage

```
rescan_file(hash = NULL, ...)
```

Arguments

hash	File hash (MD5, SHA1, or SHA256) or file ID. String. Required.
...	Additional arguments passed to virustotal_POST .

Value

list containing analysis details and ID

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
  
# Before calling the function, set the API key using set_key('api_key_here')  
  
rescan_file(hash='99017f6eebbac24f351415dd410d522d')  
  
## End(Not run)
```

`scan_file`*Submit a file for scanning*

Description

Uploads a file to VirusTotal for malware analysis using the v3 API.

Usage

```
scan_file(file_path, ...)
```

Arguments

<code>file_path</code>	Required; Path to the file to be scanned
<code>...</code>	Additional arguments passed to virustotal_POST

Value

A `virustotal_file_scan` object containing scan submission results with analysis ID and links for tracking the scan progress

References

<https://docs.virustotal.com/reference/files-scan>

See Also

[set_key](#) for setting the API key, [file_report](#) for retrieving scan results

Examples

```
## Not run:  
# Set API key first  
set_key('your_api_key_here')  
  
# Scan a file  
result <- scan_file(file_path = 'suspicious_file.exe')  
print(result)  
  
## End(Not run)
```

scan_url	<i>Submit URL for scanning</i>
----------	--------------------------------

Description

Submit a URL for analysis. Returns analysis details including an ID that can be used to retrieve the report using [url_report](#)

Usage

```
scan_url(url = NULL, ...)
```

Arguments

url	URL to scan; string; required
...	Additional arguments passed to virustotal_POST .

Value

list containing analysis details and ID

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key

Examples

```
## Not run:  
  
# Before calling the function, set the API key using set_key('api_key_here')  
  
scan_url("http://www.google.com")  
  
## End(Not run)
```

set_key	<i>Set VirusTotal API Key</i>
---------	-------------------------------

Description

Stores your VirusTotal API key in an environment variable for use by other package functions. Get your API key from <https://www.virustotal.com/>.

Usage

```
set_key(api_key)
```

Arguments

api_key	VirusTotal API key (character string). Required.
---------	--

Value

Invisibly returns TRUE on success

References

<https://docs.virustotal.com/reference>

Examples

```
## Not run:  
# Set your API key  
set_key('your_64_character_api_key_here')  
  
# Verify it's set  
Sys.getenv("VirusTotalToken")  
  
## End(Not run)
```

url_report	<i>Get URL Report</i>
------------	-----------------------

Description

Retrieve a scan report for a given URL or URL ID from VirusTotal.

Usage

```
url_report(url_id = NULL, ...)
```

Arguments

url_id URL or URL ID from VirusTotal. String. Required.
 ... Additional arguments passed to [virustotal_GET](#).

Value

list containing URL analysis results including scan details, detection information, and metadata

References

<https://docs.virustotal.com/reference>

See Also

[set_key](#) for setting the API key, [scan_url](#) for submitting URLs

Examples

```
## Not run:

# Before calling the function, set the API key using set_key('api_key_here')

# Get report using URL
url_report("http://www.google.com")

# Get report using URL ID (base64 encoded URL without padding)
url_report("687474703a2f2f7777772e676f66f676c652e636f6d2f")

## End(Not run)
```

virustotal_info	<i>Print package information and configuration status</i>
-----------------	---

Description

Print package information and configuration status

Usage

```
virustotal_info()
```

Value

Invisible NULL

See Also

Other utilities: [cleanup_temp_files\(\)](#), [create_safe_temp_dir\(\)](#), [format_file_size\(\)](#), [is_safe_environment\(\)](#), [utilities](#), [validate_vt_response\(\)](#), [virustotal_version\(\)](#)

virustotal_version	<i>Get package version information</i>
--------------------	--

Description

Get package version information

Usage

```
virustotal_version()
```

Value

Character string with package version

See Also

Other utilities: [cleanup_temp_files\(\)](#), [create_safe_temp_dir\(\)](#), [format_file_size\(\)](#), [is_safe_environment\(\)](#), [utilities](#), [validate_vt_response\(\)](#), [virustotal_info\(\)](#)

Index

- * **authentication**
 - set_key, [34](#)
- * **domain operations**
 - domain_report, [4](#)
- * **file operations**
 - file_report, [6](#)
- * **scanning functions**
 - scan_file, [32](#)
- * **utilities**
 - virustotal_info, [35](#)
 - virustotal_version, [36](#)

[add_comments](#), [2](#)

[cleanup_temp_files](#), [35](#), [36](#)

[create_safe_temp_dir](#), [35](#), [36](#)

[domain_report](#), [4](#)

[download_file](#), [5](#)

[file_report](#), [6](#), [31](#), [32](#)

[format_file_size](#), [35](#), [36](#)

[get_domain_comments](#), [7](#)

[get_domain_info](#), [8](#)

[get_domain_relationship](#), [9](#)

[get_domain_votes](#), [10](#)

[get_file_comments](#), [11](#)

[get_file_download_url](#), [12](#)

[get_file_relationships](#), [13](#)

[get_file_upload_url](#), [14](#)

[get_file_votes](#), [15](#)

[get_ip_comments](#), [16](#)

[get_ip_info](#), [17](#)

[get_ip_votes](#), [18](#)

[get_url_comments](#), [19](#)

[get_url_relationships](#), [20](#)

[get_url_votes](#), [21](#)

[ip_report](#), [22](#)

[is_safe_environment](#), [35](#), [36](#)

[post_domain_comments](#), [23](#)

[post_domain_votes](#), [24](#)

[post_file_comments](#), [25](#)

[post_file_votes](#), [26](#)

[post_ip_comments](#), [27](#)

[post_ip_votes](#), [28](#)

[post_url_comments](#), [29](#)

[post_url_votes](#), [30](#)

[rescan_file](#), [31](#)

[scan_file](#), [6](#), [14](#), [32](#)

[scan_url](#), [33](#), [35](#)

[set_key](#), [3–33](#), [34](#), [35](#)

[url_report](#), [33](#), [34](#)

[utilities](#), [35](#), [36](#)

[validate_vt_response](#), [35](#), [36](#)

[virustotal2_POST](#), [3](#)

[virustotal_GET](#), [4–22](#), [35](#)

[virustotal_info](#), [35](#), [36](#)

[virustotal_POST](#), [23–33](#)

[virustotal_version](#), [35](#), [36](#)